



**THE DATASHEET OF
AQ1051N2S-T**



Spec Sheet

High-Q Multilayer Chip Inductors for High Frequency Applications (HK series Q type / AQ series)

AQ1051N2S-T



■ Features

- Item Summary
1.2nH(± 0.3 nH), 710mA, 0402
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 10000pcs

■ Products characteristics table

CaseSize (EIA/JIS)	0402/1005
Inductance	1.2nH(± 0.3 nH)
Inductance Measuring Frequency	100MHz
Rated Current	710mA
Rated Current 2	930mA (-55 to +85 °C)
DC Resistance (max)	0.07 Ω
DC Resistance (typ)	0.016 Ω
Temperature Range	-55 to +125 °C
Self-resonant Frequency (min)	10000MHz
Q (max)	8
Q Measuring Frequency	100MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

■ External Dimensions



L	1mm ± 0.05
W	0.6mm ± 0.1
T	0.5mm ± 0.05
e	0.175mm ± 0.075

2015.08.06

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
Before making final selection, please check product specification.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View AQ1051N2S-T on WIN SOURCE](#)
-  [Taiyo Yuden Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management