

Botron B1651 Technical Data Sheet



Overview:

ESD safe clear cellulose tape is 2.4 mm thick with a charge decay of <.014 seconds. Available on 3" cores in widths of 1/2", 3/4", 1" and 2" (216' in length). Also 1" cores in widths of 1/2", 3/4" and 1" (108' in length).

PROPERTIES

SPECIFICATIONS

Material:	Transparent Cellulose
Backing:	Cellophane
Adhesive:	Natural Rubber
Core:	3"
Thickness:	2 mils
Static Generation:	<250 volts @50%RH
Size:	1/2", 3/4", 1" & 2"
Adhesion:	66oz/in
Tensile Strength:	90N/25mil
Length:	1" core / 108'
Elongation:	18%
Temperature:	32 - 150 F
Colors:	Clear

AVAILABLE APPLICATIONS

Botron's clear anti static tape is perfect for sealing ESD bags and ESD packing containers. It can also be used for a wide range of workstation applications such as binding, edging and securing.

Product Notes and Features

- Rubber Based Adhesive
- Generates Less Than 250 Volts
- Tensile Strength is 90 N/25mil
- Lead-free RoHS Compliant



PART NUMBERS

B1653 1/2" x 3" core
B1633 3/4" x 3" core
B1613 1" x 3" core
B1623 2" x 3" core

B1651 1/2" x 1" core
B1631 3/4" x 1" core
B1611 1" x 1" core

Botron Company Inc. | 325 W. Melinda Ln Phoenix AZ 85027 | Ph# 623-582-6700 | Fax# 623-582-6776

Disclaimer. All statements of technical information are believed to be true and are based upon tests we believe to be reliable. The proper use and application for this product must be the responsibility of the user.
The statements herein shall have no force or effect.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View B1651 on WIN SOURCE](#)
- [Botron Company Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management