



**THE DATASHEET OF**  
**LR4-900F**



**Specification Status: Released**

**Maximum Electrical Rating**

**Operating Voltage: 20Vdc**  
**Interrupt Current: 100A**

Chip Size: 8 x 33mm

Leads: Nickel 1/2H  
0.3mm nominal thickness


Tape: Polyester (White)  
35 mm nominal width

Solder: Lead-free

Marking (Color: Green) :  
Manufacturer's Mark

XX E90 — Part Identification

□□□□ — Lot Identification



**TABLE I. DIMENSIONS:**

	A		B		C		D		E		F	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
Mm:	45.4	47.6	7.9	8.5	0.9	1.3	4.6	6.2	4.6	6.2	5.9	6.1
In*:	(1.79)	(1.87)	(0.31)	(0.33)	(0.04)	(0.05)	(0.18)	(0.24)	(0.18)	(0.24)	(0.23)	(0.24)

\*Rounded off approximation

**TABLE II. PERFORMANCE RATINGS: As measured in Mueller Kelvin Clips model BU-75K.**

I HOLD	CURRENT TRIP LIMITS									TIME TO TRIP	REFERENC E RESISTAN CE	ONE-HOUR POST-TRIP RESISTANC E	TRIPPED- STATE POWER DISSIPATION					
	AMPS 20°C		AMPS AT 0°C		AMPS AT 20°C		AMPS AT 60°C		AMPS AT 70°C					SECONDS AT 20°C, 45.0A		OHMS AT 20°C		OHMS AT 20°C
	HOLD	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	MIN	MAX	MIN	MAX	MIN	MAX	MAX
	9.0	10.0	18.7	9.0	16.7	6.2	11.6	5.5	10.3	---	5	0.006	0.010	0.006	0.014	3.8		

Agency Recognitions: UL, TUV, CSA

Reference Documents: PS300

Precedence:

Effectivity:Reference

CAUTION:

This specification takes precedence over documents referenced herein.  
documents shall be the issue in effect on the date of invitation for bid.

Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

**MATERIALS INFORMATION:**

**ROHS Compliant**

**ELV Compliant**

**Pb-Free**

Directive 2002/95/EC  
Compliant

Directive 2000/53/EC  
Compliant





Expertise Applied | Answers Delivered

**PolySwitch®**  
**PTC Devices**  
**Overcurrent Protection Device**

**PRODUCT: LR4-900F**

DOCUMENT: SCD25964  
REV LETTER: D  
REV DATE: JULY 26, 2016  
PAGE NO.: 2 OF 2

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, military, aerospace, medical, lifesaving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View LR4-900F on WIN SOURCE](#)

 [Littelfuse Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management