



**THE DATASHEET OF  
G3VM-61E1(TR)**




# G3VM-61B1/E1

MOS FET Relays

## Analog-switching MOS FET Relays for High Switching Currents, with Dielectric Strength of 2.5 kVAC between I/O.



- Upgraded G3VM-61B/E Series.
- Switches minute analog signals.
- Leakage current of 1  $\mu\text{A}$  max. when output relay is open.





Note: The actual product is marked differently from the image shown here.

RoHS compliant

### Application Examples

- Test & Measurement equipment
- Security equipment
- Amusement equipment

### Terminal Arrangement/Internal Connections



Note: The actual product is marked differently from the image shown here.

### List of Models

Package type	Contact form	Terminals	Load voltage (peak value) *	Model	Minimum package quantity	
					Number per tube	Number per tape and reel
DIP6	1a (SPST-NO)	PCB Terminals	60 V	G3VM-61B1	50	-
		Surface-mounting Terminals		G3VM-61E1		
					G3VM-61E1 (TR)	-


\* The AC peak and DC value are given for the load voltage.

### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Item	Symbol	Rating	Unit	Measurement conditions		
Input	LED forward current	$I_F$	50	mA		
	Repetitive peak LED forward current	$I_{FP}$	1	A	100 $\mu\text{s}$ pulses, 100 pps	
	LED forward current reduction rate	$\Delta I_F/^\circ\text{C}$	-0.5	$\text{mA}/^\circ\text{C}$	$T_a \geq 25^\circ\text{C}$	
	LED reverse voltage	$V_R$	5	V		
Connection temperature	$T_J$	125	$^\circ\text{C}$			
Output	Load voltage (AC peak/DC)	$V_{OFF}$	60	V		
	Continuous load current	$I_o$	Connection A	500	mA	Connection A: AC peak/DC Connection B and C: DC
			Connection B	500		
			Connection C	1000		
	ON current reduction rate	$\Delta I_o/^\circ\text{C}$	Connection A	-5	$\text{mA}/^\circ\text{C}$	$T_a \geq 25^\circ\text{C}$
			Connection B	-5		
Connection C			-10			
Connection temperature	$T_J$	125	$^\circ\text{C}$			
Dielectric strength between I/O (See note 1.)	$V_{I-O}$	2500	$V_{rms}$	AC for 1 min		
Ambient operating temperature	$T_a$	-40 to +85	$^\circ\text{C}$	With no icing or condensation		
Ambient storage temperature	$T_{stg}$	-55 to +125	$^\circ\text{C}$	With no icing or condensation		
Soldering temperature	-	260	$^\circ\text{C}$	10 s		

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.


#### Connection Diagram



### Electrical Characteristics ( $T_a = 25^\circ\text{C}$ )

Item	Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions		
Input	LED forward voltage	$V_F$	1.0	1.15	1.3	V	$I_F = 10 \text{ mA}$	
	Reverse current	$I_R$	-	-	10	$\mu\text{A}$	$V_R = 5 \text{ V}$	
	Capacity between terminals	$C_T$	-	30	-	pF	$V = 0, f = 1 \text{ MHz}$	
Output	Trigger LED forward current	$I_{FT}$	-	1.6	3	mA	$I_o = 500 \text{ mA}$	
	Maximum resistance with output ON	$R_{ON}$	Connection A	-	1	2	$\Omega$	$I_F = 5 \text{ mA}, I_o = 500 \text{ mA}$
			Connection B	-	0.5	1	$\Omega$	$I_F = 5 \text{ mA}, I_o = 500 \text{ mA}$
			Connection C	-	0.25	-	$\Omega$	$I_F = 5 \text{ mA}, I_o = 1000 \text{ mA}$
	Current leakage when the relay is open	$I_{LEAK}$	-	-	1.0	$\mu\text{A}$	$V_{OFF} = 60 \text{ V}$	
	Capacity between terminals	$C_{OFF}$	-	130	-	pF	$V = 0, f = 1 \text{ MHz}$	
Capacity between I/O terminals	$C_{I-O}$	-	0.8	-	pF	$f = 1 \text{ MHz}, V_s = 0 \text{ V}$		
Insulation resistance between I/O terminals	$R_{I-O}$	1000	-	-	$\text{M}\Omega$	$V_{I-O} = 500 \text{ VDC}, R_oH \leq 60\%$		
Turn-ON time	$t_{ON}$	-	0.8	2.0	ms	$I_F = 5 \text{ mA}, R_L = 200 \Omega,$		
Turn-OFF time	$t_{OFF}$	-	0.1	0.5	ms	$V_{DD} = 20 \text{ V}$ (See note 2.)		

Note: 2. Turn-ON and Turn-OFF Times




## Recommended Operating Conditions

Use the G3VM under the following conditions so that the Relay will operate properly.


Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	V <sub>DD</sub>	-	-	48	V
Operating LED forward current	I <sub>F</sub>	5	7.5	25	mA
Continuous load current (AC peak/DC)	I <sub>O</sub>	-	-	500	mA
Ambient operating temperature	T <sub>a</sub>	-20	-	65	°C

## Engineering Data


LED forward current vs. Ambient temperature




Continuous load current vs. Ambient temperature




LED forward current vs. LED forward voltage




Continuous load current vs. On-state voltage




On-state resistance vs. Ambient temperature




Trigger LED forward current vs. Ambient temperature




Turn ON, Turn OFF time vs. LED forward current



Turn ON, Turn OFF time vs. Ambient temperature



Current leakage vs. Ambient temperature




## Safety Precautions

- Refer to "Common Precautions" for all G3VM models.

## ■ Appearance


DIP (Dual Inline Package)  
DIP6



Note: The actual product is marked differently from the image shown here.



## ■ Dimensions

(Unit:mm)




### PCB Terminals

Weight: 0.4 g




### Surface-mounting Terminals

Weight: 0.4 g




### PCB Dimensions (BOTTOM VIEW)



### Actual Mounting Pad Dimensions

(Recommended Value, TOP VIEW)



Note: The actual product is marked differently from the image shown here.

- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.

**OMRON Corporation**



ELECTRONIC AND MECHANICAL COMPONENTS COMPANY

Contact: [www.omron.com/ecb](http://www.omron.com/ecb)

Cat. No. **K144-E1-01**  
0412(0412)(O)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View G3VM-61E1\(TR\) on WIN SOURCE](#)
-  [Omron Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management