



**THE DATASHEET OF
BYS459B-1500E3/81**






BYS459-1500, BY5459F-1500 & BY5459B-1500

Vishay General Semiconductor

High Voltage Damper Diodes



FEATURES

- Glass passivated chip junction
- Fast reverse recovery time
- Low switching loss, high efficiency
- Low forward voltage drop
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245 °C (for TO-263AB package)
- Solder dip 260 °C, 40 s (for TO-220AC and ITO-220AC package)
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS
COMPLIANT

TYPICAL APPLICATIONS

For use in high voltage and high frequency rectification of switching mode inverters, converters, freewheeling and ideal for CRT horizontal deflection application.

PRIMARY CHARACTERISTICS

$I_{F(AV)}$	6.5 A
V_{RRM}	1500 V
I_{FSM}	130 A
t_{rr}	350 ns
t_{fr}	250 ns
V_F	1.2 V
$T_J \text{ max.}$	150 °C

MECHANICAL DATA

Case: TO-220AC, ITO-220AC, TO-263AB

Epoxy meets UL 94V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test

Polarity: As marked

Mounting Torque: 10 in-lbs maximum

MAXIMUM RATINGS ($T_A = 25$ °C unless otherwise noted)

PARAMETER	SYMBOL	VALUE	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	1500	V
Maximum working reverse voltage	V_{RWM}	1300	V
Maximum DC blocking voltage	V_{DC}	1500	V
Maximum average forward rectified current	$I_{F(AV)}$	6.5	A
Peak working forward current at $f = 48$ kHz	$I_{F(Peak)}$	12	A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	I_{FSM}	130	A
Operating junction and storage temperature range	T_J, T_{STG}	- 55 to + 150	°C
Isolation voltage (ITO-220AC only) from terminal to heatsink $t = 1$ min	V_{AC}	1500	V

BYS459-1500, BYS459F-1500 & BYS459B-1500



Vishay General Semiconductor

ELECTRICAL CHARACTERISTICS (T _J = 25 °C unless otherwise noted)					
PARAMETER	TEST CONDITIONS		SYMBOL	VALUE	UNIT
Maximum instantaneous forward voltage (1)	I _F = 6.5 A, I _F = 6.5 A,	T _J = 25 °C T _J = 125 °C	V _F	1.3 1.2	V
Maximum DC reverse current	V _{RWM}	T _J = 25 °C T _J = 125 °C	I _R	250 1.0	μA mA
Maximum reverse recovery time	I _F = 1.0 A, di/dt = 50 A/μs, V _R = 30 V		t _{rr}	350	ns
Maximum reverse recovery charge	I _F = 2.0 A, di/dt = 20 A/μs		Q _{rr}	3.0	μC
Maximum forward recovery time	I _F = 6.5 A, di/dt = 52 A/μs		t _{fr}	250	ns
Peak forward recovery overshoot voltage	I _F = 6.5 A, di/dt = 52 A/μs		V _{FP}	20	V

Note:

(1) Pulse test: 300 μs pulse width, 1 % duty cycle

THERMAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted)					
PARAMETER	SYMBOL	BYS459	BYS459F	BYS459B	UNIT
Typical thermal resistance from junction to ambient	R _{θJA}	60	55	60	°C/W

ORDERING INFORMATION (Example)					
PACKAGE	PREFERRED P/N	UNIT WEIGHT (g)	PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
TO-220AC	BYS459-1500-E3/45	1.80	45	50/tube	Tube
ITO-220AC	BYS459F-1500-E3/45	1.95	45	50/tube	Tube
TO-263AB	BYS459B-1500-E3/45	1.77	45	50/tube	Tube
TO-263AB	BYS459B-1500-E3/81	1.77	81	800/reel	Tape and reel

RATINGS AND CHARACTERISTICS CURVES

(T_A = 25 °C unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current



BYS459-1500, BYS459F-1500 & BYS459B-1500

Vishay General Semiconductor




Figure 3. Typical Forward Voltage




Figure 5. Typical Capacitance




Figure 4. Typical Reverse Current





Figure 6. Typical Reverse Recovery Time

BYS459-1500, BYS459F-1500 & BYS459B-1500



Vishay General Semiconductor

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View BY5459B-1500E3/81 on WIN SOURCE](#)

 [Vishay Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management