




THE DATASHEET OF CLF12555T-1R5N-CA

CLF12555T-1R5N-CA

Applications	 Automotive Grade
Feature	Wire Wound Wire Wound Shield Magnetic Shield Ferrite Core Ferrite Core AEC-Q200 AEC-Q200
Series	CLF-CA Series / CLF12555-CA Type
Status	Production




Size	
Length(L)	12.50mm +/-0.30mm
Width(W)	12.10mm +0.30/-0.20mm
Thickness(T)	5.50mm +/-0.35mm
Recommended Land Pattern (A)	2.70mm Nom.
Recommended Land Pattern (B)	8.30mm Nom.
Recommended Land Pattern (C)	3.20mm Nom.

Electrical Characteristics	
Inductance	1.5uH +/-30% at 100kHz
Rated Current (L Change) [Typ.]	16.4A (10% Down)
Rated Current (Temperature Rise) [Typ.]	6.7A (30degC Rise)
DC Resistance [Nom.]	7.3mΩ
DC Resistance [Max.]	9.5mΩ


Other	
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 105degC
Soldering Method	Reflow, Iron Soldering
AEC Q200	Yes
Packing	Blister (Plastic)Taping [330mm Reel]
Package Quantity	500Pcs Min.
Weight	3g

CLF12555T-1R5N-CA


Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




CLF12555T-1R5N-CA



CLF12555T-1R5N-CA




CLF12555T-1R5N-CA




CLF12555T-1R5N-CA

CLF12555T-1R5N-CA

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




CLF12555T-1R5N-CA(Amb. Temp. = 20degC)



CLF12555T-1R5N-CA(DC = 0A)

CLF12555T-1R5N-CA(DC = 3.35A)



CLF12555T-1R5N-CA(Amb. Temp. = 20degC)

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ View [CLF12555T-1R5N-CA](#) on WIN SOURCE
- ⊖ [TDK Corporation](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management