



**THE DATASHEET OF  
EL4093CSZ**



EL4093

300MHz DC-Restored Video Amplifier


FN7159  
Rev 0.00  
January 1996

The EL4093 is a complete DC-restored video amplifier subsystem, featuring low power consumption and high slew rate. It contains a current feedback amplifier and a sample and hold amplifier designed to stabilize video performance. When the HOLD logic input is low, the sample and hold may be used as a general purpose op amp to null the DC offset of the video amplifier. When the HOLD input goes high the sample and hold stores the correction voltage on the hold capacitor to maintain DC correction during the subsequent video scan line.

The sample and hold amplifier contains a current output stage that greatly simplifies its connection to the video amplifier. Its high output impedance also helps to preserve video linearity at low supply voltages. For ease of interfacing, the HOLD input is TTL-compatible. This device has an operational temperature of -40°C to +85°C and is packaged in plastic 16-pin DIP and 16-pin SOIC.

**Pinout**

EL4093  
(16-PIN PDIP, SO)  
TOP VIEW



**Features**

- High accuracy DC restoration for video
- Low supply current of 9.5mA typ.
- 300MHz bandwidth
- 1500V/μs slew rate
- 0.04% differential gain and 0.02° differential phase into 150Ω for NTSC
- 1.5mV max. restored DC offset
- Sample and hold amplifier with fast enable and low leakage
- TTL-compatible HOLD logic input

**Applications**

- Input amplifier in video equipment
- Restoration amplifier in video mixers

**Ordering Information**

PART NUMBER	TEMP. RANGE	PACKAGE	PKG. NO.
EL4093CN	-40°C to +85°C	16-Pin PDIP	MDP0031
EL4093CS	-40°C to +85°C	16-Pin SOIC	MDP0027

**Demo Board**

A demo PCB is available for this product. Request "EL4093 Demo Board."

**Absolute Maximum Ratings** (T<sub>A</sub> = 25°C)

V <sub>S</sub>	V+ to V- Supply Voltage	12.6V	I <sub>OUT2</sub>	S/H amplifier output current	±10mA
V <sub>HOLD</sub>	Voltage at HOLD input (DGND-0.7) to (DGND+5.5V)		I <sub>IN</sub>	Maximum current into other pins	±6mA
V <sub>IN</sub>	Voltage at any other input	V+ to V-	P <sub>D</sub>	Maximum Power Dissipation	See Curves
ΔV <sub>IN</sub>	Difference between Sample and Hold inputs	±8V	T <sub>A</sub>	Operating Ambient Temperature Range	-40°C to +85°C
I <sub>OUT1</sub>	Video amplifier output current	±30mA	T <sub>J</sub>	Operating Junction Temperature	150°C
			T <sub>ST</sub>	Storage Temperature Range	-65°C to +150°C

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

IMPORTANT NOTE: All parameters having Min/Max specifications are guaranteed. Typical values are for information purposes only. Unless otherwise noted, all tests are at the specified temperature and are pulsed tests, therefore: T<sub>J</sub> = T<sub>C</sub> = T<sub>A</sub>

**Open-Loop DC Electrical Specifications** Power supplies at ±5V, T<sub>A</sub> = 25°C

**Sample and Hold**

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNITS
I <sub>S,HOLD</sub>	Total Supply current in HOLD mode		9.5	11.5	mA
I <sub>S,SAMPLE</sub>	Total Supply current in SAMPLE mode		8.5	10.5	mA

**Video Amplifier Section (Not Restored)**

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNITS
V <sub>OS</sub>	Input Offset Voltage		10	110	mV
I <sub>B+</sub>	Non-Inverting Input Bias Current		10	25	μA
I <sub>B-</sub>	Inverting Input Bias Current		15	50	μA
R <sub>OL</sub>	Transimpedance, V <sub>OUT</sub> = ±2.5V, R <sub>L</sub> = 150Ω	150	400		kΩ
V <sub>O</sub>	Output Voltage Swing, R <sub>L</sub> = 150Ω	±3	±3.5		V
I <sub>SC</sub>	Output Short-Circuit Current	60	100		mA

**Open-Loop DC Electrical Specifications** Power supplies at ±5V, T<sub>A</sub> = 25°C

**Sample and Hold Section**

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNITS
V <sub>OS</sub>	Input Offset Voltage		0.5	1.5	mV
TCV <sub>OS</sub>	Average Offset Voltage Drift		6		μV/°C
I <sub>B</sub>	Input Bias Current		1	2	μA
I <sub>OS</sub>	Input Offset Current		10	200	nA
TCI <sub>OS</sub>	Average Offset Current Drift		0.1		nA/°C
V <sub>CM</sub>	Common Mode Input Range	±2.5	±2.8		V
g <sub>M</sub>	Transconductance (R <sub>L</sub> = 500Ω)	5	15		A/V
CMRR	Common Mode Rejection Ratio (V <sub>CM</sub> -2.5V to +2.5V)	70	90		dB
V <sub>IL</sub>	HOLD Logic Input Low (referenced to Digital GND)			0.8	V
V <sub>IH</sub>	HOLD Logic Input High (referenced to Digital GND)	2.0			V
V <sub>GND</sub>	Digital GND Reference Voltage	(V-)		(V+) - 4.0	V
I <sub>DROOP</sub>	Hold Mode Droop Current		10	70	nA
I <sub>CHARGE</sub>	Charge Current Available to C <sub>HOLD</sub>	±5.5	±8.5		mA
V <sub>O</sub>	Output Voltage Swing (R <sub>L</sub> = 10kΩ)	±3	±3.5		V
I <sub>O</sub>	Output Current Swing (R <sub>L</sub> = 0Ω)	±4.5	±5.5		mA

**Closed-Loop AC Electrical Specifications**

Power supplies at  $\pm 5V$ ,  $T_A = 25^\circ C$ ,  $R_F = R_G = 750\Omega$ ,  $R_L = 150\Omega$ ,  $C_L = 5pF$ ,  $C_{IN}$  (parasitic) = 1.8pF

**Video Amplifier Section**

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNITS
BW, -3dB	-3dB Small-Signal Bandwidth		300		MHz
BW, $\pm 0.1dB$	0.1dB Flatness Bandwidth		50		MHz
Peaking	Frequency Response Peaking		0		dB
SR	Slew rate, $V_{OUT}$ between -2V and +2V		1500		V/ $\mu s$
dG	Differential Gain Error, Voffset between -714mV and +714mV		0.04		%
d $\theta$	Differential Phase Error, Voffset between -714mV and +714mV		0.02		°


**Closed-Loop AC Electrical Specifications**

Power supplies at  $\pm 5V$ ,  $T_A = 25^\circ C$ ,  $R_F = R_G = 750\Omega$ ,  $R_L = 150\Omega$ ,  $C_L = 5pF$ ,  $C_{HOLD} = 2.2nF$










**Sample and Hold Section**

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNITS
$\Delta I_{STEP}$	Change in Sample to Hold Output Current Due to Hold Step		0.1		$\mu A$
$\Delta T_{SH}$	Sample to Hold Delay Time		15		ns
$\Delta T_{HS}$	Hold to Sample Delay Time		40		ns
$T_{AC}$	Settling Time to 1% (DC Restored Amplifier Output) Video Amplifier Input from 0 to 1V		2.2		$\mu s$









**Typical Application**











# Typical Performance Curves











Typical Performance Curves (Continued)



**Typical Performance Curves (Continued)**



**Typical Performance Curves (Continued)**



**Applications Information**

**Product Description**

The EL4093 is a high speed DC-restore system containing a current feedback amplifier (CFA) and a sample & hold (S/H) amplifier. The CFA offers a wide 3dB bandwidth of 300MHz and a slew rate of 1500V/μs, making it ideal for high speed video applications such as SVGA. The CFA's excellent differential gain and phase at 3.58MHz also makes it suitable for NTSC applications. Drawing only 9.5mA on ±5V supplies, the EL4093 serves as an excellent choice for those applications requiring both low power and high bandwidth.

The connection between the CFA and sample & hold (the Autozero interface) has been greatly simplified. The output of the sample & hold is a high impedance current source, allowing direct connection to the CFA inverting input for autozero purposes. In addition, special circuitry within the sample & hold provides a charge current of 8.5mA in sample mode, resulting in a sample hold current ratio (ratio of charging current to droop current) of approx. 1,000,000.

**Theory of Operation**

In video applications, DC restoration moves the backporch or black level to a fixed DC reference. The EL4093 uses a CFA in feedback with a sample & hold to provide DC restoration.

Figure 1 shows how the two are connected to provide this function; the S/H compares the output of the CFA to a DC reference, and any difference between them causes an output current from the S/H. This “autozero” current is fed to the CFA inverting input, the effect of which is to move the CFA output towards the reference voltage. This autozero mechanism settles when the CFA output is one  $V_{OS}$  away from the reference (the  $V_{OS}$  here refers to the S/H offset voltage).




FIGURE 1.

The autozero mechanism is typically active for only a short period of each video line. Figure 2 shows a NTSC video signal along with the EL4581 back porch output. The back porch signal is used to drive the HOLD input of the EL4093, and we see that the EL4093 is in sample mode for only 3.5 $\mu$ s of each line. It is during this time that the autozero mechanism attempts to drive the CFA output towards the reference voltage, at the same time putting a correction voltage onto the hold capacitor  $C_{HOLD}$ . During the rest of the line (60 $\mu$ s) the EL4093 is in hold mode, but DC correction is maintained by the voltage on  $C_{HOLD}$ .




FIGURE 2.

**Power Supply Bypassing and Printed Circuit Board Layout**

As with any high frequency device, good printed circuit board layout is necessary for optimum performance. Ground plane construction is highly recommended. Lead lengths should be as short as possible. The power supply pins must be well bypassed to reduce the risk of oscillation. In the EL4093 there

are two sets of supply pins: V+1/V-1 provide power for the CFA, and V+2/V-2 are for the S/H amplifier. Good performance can be achieved using only one set of bypass capacitors, although they must be close to the V+1/V-1 pins since that is where the high frequency currents flow. The combination of a 4.7 $\mu$ F tantalum capacitor in parallel with a 0.01 $\mu$ F capacitor has been shown to work well. Chip capacitors are recommended for the 0.01 $\mu$ F bypass to minimize lead inductance.

For good AC performance, parasitic capacitance should be kept to a minimum, especially at the CFA inverting input. Ground plane construction should be used, but it should be removed from the area near the inverting input to minimize any stray capacitance at that node. Chip resistors are recommended for  $R_F$  and  $R_G$ , and use of sockets should be avoided if possible. Sockets add parasitic inductance and capacitance which will result in some additional peaking and overshoot.

If the CFA is configured for non-inverting gain, then one should also pay attention to the trace leading to the +input. The inductance of a long trace (> 3') can form a resonant network with the amplifier input, resulting in high frequency oscillations around 700MHz. In such cases a 50 $\Omega$ –100 $\Omega$  series resistor placed close to the +input would isolate this inductance and damp out the resonance.

**Capacitance at the Inverting Input**

Any manufacturer’s high-speed voltage or current feedback amplifier can be affected by stray capacitance at the inverting input. For inverting gains this parasitic capacitance has little effect because the inverting input is a virtual ground, but for non-inverting gains this capacitance (in conjunction with the feedback and gain resistors) creates a pole in the feedback path of the amplifier. This pole, if low enough in frequency, has the same destabilizing effect as a zero in the forward open-loop response. Hence it is important to minimize the stray capacitance at this node by removing the nearby ground plane. In addition, since the S/H output connects to this node, it is important to minimize the trace capacitance. Good practice here would be to connect the two pins with a short trace directly underneath the chip.

**Feedback Resistor Values**

The EL4093 has been optimized for a gain of +2 with  $R_F = 750\Omega$ . This value of feedback resistor gives a 3dB bandwidth of 300MHz at a gain of +2 driving a 150 $\Omega$  load. Since the amplifier inside the EL4093 uses current mode feedback, it is possible to change the value of  $R_F$  to adjust the bandwidth. Shown in the table below are optimum feedback resistor values for different closed loop gains.

GAIN	OPTIMUM RF	BW (MHz)	PEAKING (dB)
+1	910	314	0.2

GAIN	OPTIMUM RF	BW (MHz)	PEAKING (dB)
+2	750	300	0
+5	470	294	0.2
-1	680	300	0

**Autozero Interface**

The autozero interface refers to the connection between the S/H output and the CFA inverting input. This interface has been greatly simplified compared to that of the EL2090, in that the S/H output is a high impedance current source. The S/H output can be connected directly to the inverting input, and its high impedance greatly reduces the interaction between the sample & hold and the gain setting resistors. Another virtue of this interface is better gain linearity as the autozero current changes. For example, at an autozero current of 0mA the output impedance is about 5MΩ, dropping to 1MΩ as the autozero current increases to 3mA. Using  $R_F = R_G = 750\Omega$ , the closed loop gain changes only by 0.025% in this interval.

**Autozero Range**

The autozero range is defined as the difference between the input DC level and the reference voltage to restore to. The size of this range is a function of the gain setting resistors used and the S/H output current swing. For a gain of +2 the optimum feedback resistor is 750Ω, and the available S/H output current is ±5.5mA minimum. To determine the autozero range for this case, we refer to Figure 3 below.




FIGURE 3.

Suppose that the input DC level is +V<sub>DC</sub>, and that the reference voltage is 0V. We know that in feedback, the following two conditions will exist on the CFA: first, its output will be equal to 0V (due to autozero), and second, its V<sub>IN-</sub> voltage is equal to the V<sub>IN+</sub> voltage (i.e. V<sub>IN-</sub> = +V<sub>DC</sub>). So we have a potential difference of +V<sub>DC</sub> across both R<sub>F</sub> and R<sub>G</sub>, resulting in a current I<sub>RF</sub> = I<sub>RG</sub> = V<sub>DC</sub>/750Ω that must flow into each of them. This current I<sub>AZ</sub> = (I<sub>RF</sub> + I<sub>RG</sub>) must come from the S/H output. Since the maximum that I<sub>AZ</sub> can be is 5.5mA, we can solve for V<sub>DC</sub> using the following:

$$I_{AZ} = \pm 5.5mA = 2 \left( \frac{V_{DC}}{750\Omega} \right)$$

and see that V<sub>DC</sub> = ±2V. This range can easily accommodate most video signals.

As another example, consider the case where we are restoring to a reference voltage of +0.75V. Using the same reasoning as above, a current I<sub>RF</sub> = (V<sub>DC</sub> - 0.75V)/R<sub>F</sub> must flow through R<sub>F</sub>, and a current I<sub>RG</sub> = V<sub>DC</sub>/R<sub>G</sub> must go into R<sub>G</sub>. Again, our boundary condition is that I<sub>RF</sub> + I<sub>RG</sub> ≤ ±5.5mA, and we can solve for the allowable V<sub>DC</sub> values using the following:

$$\pm 5.5mA = \frac{V_{DC} - 0.75V}{750\Omega} + \frac{V_{DC}}{750\Omega}$$

Hence V<sub>DC</sub> must be between +2.4V to -1.7V. This example illustrates that when the reference changes, the autozero range also changes. In general, the user should determine the autozero range for his/her application, and ensure that the input signal is within this range during the autozero period.

**Autozero Loop Bandwidth**

The gain-bandwidth product (GBWP) of the autozero loop is determined by the size of the hold capacitor, the value of R<sub>F</sub>, and the transconductances (gm's) of the S/H amplifier. To begin, the S/H amplifier is modeled as in Figure 4. First, the input stage transconductance is represented by gm<sub>1</sub>, with the compensation capacitor given by C<sub>HOLD</sub>. This stage's GBWP is thus gm<sub>1</sub>/(2π • C<sub>HOLD</sub>) = 1/(2π • (350Ω)(2.2nF)) = 207kHz. Next, since the S/H has a current output, its output stage can be modeled as a transconductance gm<sub>2</sub>, in this case having a value of 1/(500Ω). The current from gm<sub>2</sub> then flows through the I to V converter made up of the CFA and R<sub>F</sub> to produce a voltage gain. Thus the GBWP of the overall loop is given by:

$$GBWP = \frac{gm_1}{2\pi \times C_{HOLD}} (gm_2 \times R_F)$$




FIGURE 4.

With  $R_F = 750\Omega$ , a GBWP of 310kHz is obtained. Note however that this is the small signal GBWP. As mentioned earlier, the sample and hold has special boost circuits built in which provides  $\pm 8.5\text{mA}$  of charge current during full slew. These boost circuits turn on when the S/H input differential voltage exceeds  $\pm 50\text{mV}$ . When the boosters are turned on,  $gm_1$  greatly increases and the circuit becomes nonlinear. Thus some stability issues are associated with the boosters, and they will be addressed in a later section.

**Charge Injection and Hold Step**

Charge injection refers to the charge transferred to the hold capacitor when switching to the HOLD mode. The charge should ideally be 0, but due to stray capacitive coupling and other effects, is typically 0.1pC in the EL4093. This charge changes the hold capacitor voltage by  $\Delta V = \Delta Q / C_{\text{HOLD}}$ , and this  $\Delta V$  is multiplied by the output stage transconductance ( $gm_2$ ) to produce a change in S/H output current. This last quantity is listed as the spec  $\Delta I_{\text{STEP}}$ , and is calculated using the following:

$$\Delta I_{\text{STEP}} = \left( \frac{\Delta Q}{C_{\text{HOLD}}} \right) \times gm_2$$

For  $C_{\text{HOLD}} = 2.2\text{nF}$  and  $gm_2 = 1/(500\Omega)$ ,  $\Delta I_{\text{STEP}}$  has a typical value of 100nA. This change in S/H output current flows through  $R_F$ , shifting the CFA output voltage. However, as we shall soon see, this shift is negligible. Assuming  $R_F = 750\Omega$ ,  $\Delta I_{\text{STEP}}$  is impressed across  $R_F$  to give  $(750\Omega)(100\text{nA}) = 0.08\text{mV}$  of change at the CFA output.

**Droop Rate**

When the S/H amplifier is in HOLD mode, there is a small current that leaks from the switch into the hold capacitor. This quantity is termed the droop current, and is typically 10nA in the EL4093. This droop current produces a ramp in the hold


capacitor voltage, which in turn produces a similar effect at the CFA output. The Droop Rate at the CFA output can be found using the equation below:

$$\text{Droop} = \frac{I_{\text{DROOP}}}{C_{\text{HOLD}}} (gm_2 \times R_F)$$

Assuming  $R_F = 750\Omega$  and  $C_{\text{HOLD}} = 2.2\text{nF}$ , the drift in the CFA output due to droop current is about  $7\mu\text{V}/\mu\text{s}$ . Recall that in NTSC applications, there is about  $60\mu\text{s}$  between autozero periods. Thus there is  $7\mu\text{V}/\mu\text{s}(60\mu\text{s}) = 0.4\text{mV}$ , or less than 0.1 IRE, of drift over each NTSC scan line. This drift is negligible in most applications.

**Choice of Hold Capacitor**

The EL4093 has been designed to work with a hold capacitor of 2.2nF. With this value of  $C_{\text{HOLD}}$ , the droop rate and hold step are negligibly small for most applications. In addition, with the special boost circuits inside the S/H, fast acquisition is possible even using a hold capacitor of this size. Figure 5 shows the input and output of the DC-restored amplifier while the S/H is in sample mode. Applying a +1V step to the non-inverting input of the CFA, the output of the CFA jumps to +2V. The S/H, however, then tries to autozero the system by driving the CFA output back to the reference voltage. Since the input differential across the S/H is initially +2V, the boost circuits turn on and supply 8.5mA of charge current to the hold capacitor. The boost circuit remains on until the CFA output has come to within 50mV of the reference. Note that this event took only 320ns; settling to within 1% of the final value takes another 2 $\mu\text{s}$ . Thus for a 1V input step, acquisition takes only one to two NTSC scan lines.



**FIGURE 5. AUTOZERO MECHANISM RESTORES AMPLIFIER OUTPUT TO GROUND AFTER +1V STEP AT INPUT**

A natural question arises as to whether there are other  $C_{HOLD}$  values that can be used. In one direction, increasing  $C_{HOLD}$  will further reduce the droop and hold step, but lengthen the acquisition time. Since the droop and hold step are already small to begin with, there is no apparent advantage to increasing  $C_{HOLD}$ .

In the other direction, decreasing  $C_{HOLD}$  would increase the droop and hold step but shorten the acquisition time. There is, however, a caveat to reducing  $C_{HOLD}$ : too small a  $C_{HOLD}$  would cause the autozero loop to oscillate. The reason is that when the S/H boost circuit turns on, the input stage  $g_m$  increases drastically and the circuit becomes nonlinear. A sufficiently large  $C_{HOLD}$  must be used to suppress the non-linearity and force the loop to settle. For example, it has been found that a  $C_{HOLD}$  of 470pF results in 1V<sub>P-P</sub> oscillation around 10MHz at the CFA output.


The minimum recommended value for  $C_{HOLD}$  is 2.2nF. With this value the loop remains stable over the entire operating temperature range (-40°C to +85°C). The greatest instability occurs at low temperatures, where we observe from the performance curves that the S/H  $g_m$ 's, and hence the GBWP, are at their maximum. If the operating range is restricted to room temperature or above, then 1.5nF is sufficient to keep the loop stable. At this value of  $C_{HOLD}$  the acquisition time reduces to about 1.5μs.

**Video Performance and Application**

Although the EL4093 is intended for high speed video applications such as SVGA, it also offers excellent performance for NTSC, with 0.04% dG and 0.02° dP at 3.58MHz. Some application considerations, however, are required for handling NTSC signals.


Referring back to Figure 2, recall that typically, the autozero interval lies in the back porch portion of video containing the colorburst pulse. When the S/H compares the video to the reference voltage during this period, the colorburst (40 IRE<sub>P-P</sub>) triggers the S/H boost circuit and prevents the autozero loop from settling.

A remedy for this situation is to attenuate the colorburst before applying it to the S/H input. Figure 6 below shows a 3.58MHz chroma trap which would notch out the colorburst while preserving the video DC level.




**FIGURE 6. COLORBURST TRAP FOR NTSC APPLICATIONS**

One may be tempted to use a RC lowpass filter to suppress the colorburst, as shown in Figure 7 below. This technique, however, poses several problems. First, to obtain enough attenuation, we need to set the pole frequency 10 to 20 times lower than 3.58MHz. This pole, being close to the auto zero loop pole, would destabilize the system and cause the loop to oscillate.



**FIGURE 7. CAUTION: LOWPASS FILTER DOES NOT WORK IN NTSC APPLICATIONS**

Although we can cancel this pole by introducing a zero, the RC network introduces a time delay between the CFA output and the S/H input. This has undesirable effects in some NTSC applications, as Figure 8 illustrates. There is only 0.6μs from the rising edge of sync to the colorburst. If we are autozeroing over the back porch, the autozero period would begin somewhere in this 0.6μs interval. Since the edge of sync is now delayed by the RC network, autozero begins before the video back porch reaches its final value. Consequently, the autozero loop performs a correction on every line and never settles.



**FIGURE 8. LOWPASS FILTER DELAYS INPUT TO SAMPLE AND HOLD**

If the video does not contain any AC components during the autozero level (e.g. RGB video), then the above networks are not needed and the CFA output can be connected directly to the S/H input.

**Power Dissipation**

The EL4093 current feedback amplifier has an absolute maximum of ±30mA output current drive. This is slightly more than the current required to drive ±2V into 75Ω. To see how much the junction temperature is raised in this worst case, we refer to the equations below:

$$T_{JMAX} = T_{MAX} + (\theta_{JA} \cdot PD_{MAX})$$

where:

$T_{MAX}$  = Maximum Ambient Temperature

$\theta_{JA}$  = Thermal Resistance of the Package

$PD_{MAX}$  = Maximum Power Dissipation of the CFA and S/H amplifier in the Package

$PD_{MAX}$  for either the CFA or the S/H amplifier can be calculated as follows:

$$PD_{MAX} = (2 \cdot V_S \cdot I_{SMAX}) + (V_S - V_{OUTMAX}) \cdot (V_{OUTMAX} / R_L)$$

where:

$V_S$  = Supply Voltage

$I_{SMAX}$  = Maximum Supply Current of Amplifier

$V_{OUTMAX}$  = Maximum Output Voltage of Application

$R_L$  = Load Resistance

For the EL4093, the maximum supply current is 11.5mA on  $V_S = \pm 5V$ . Assume that in the worst case, the CFA output swings ±2V into 75Ω. Since the S/H has a current output, we assume that it is at maximum current swing (±5.5mA) but at a mid-rail output voltage (0V). With the above assumptions,  $PD_{MAX}$  for the EL4093 is 223mW, and using the thermal resistance of a narrow SO package (120°C/W), this yields a temperature increase of 27°C. Since the maximum ambient temperature is 85°C, the resulting junction temperature of 112°C is still below the maximum.

Please note that this in addition to metal migration problems.

© Copyright Intersil Americas LLC 2003. All Rights Reserved.

All trademarks and registered trademarks are the property of their respective owners.

For additional products, see [www.intersil.com/en/products.html](http://www.intersil.com/en/products.html)

Intersil products are manufactured, assembled and tested utilizing ISO9001 quality systems as noted in the quality certifications found at [www.intersil.com/en/support/qualandreliability.html](http://www.intersil.com/en/support/qualandreliability.html)

*Intersil products are sold by description only. Intersil may modify the circuit design and/or specifications of products at any time without notice, provided that such modification does not, in Intersil's sole judgment, affect the form, fit or function of the product. Accordingly, the reader is cautioned to verify that datasheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View EL4093CSZ on WIN SOURCE](#)

 [Intersil Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management