



**THE DATASHEET OF
GBJL2001-BP**





Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

GBJL20005 THRU GBJL2010

20 Amp Glass Passivated Bridge Rectifier 50 to 1000 Volts


Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Rating to 1000V PRV
- Low forward voltage drop, high current capability.
- Ideal for printed circuit board
- Halogen free available upon request by adding suffix "-HF"

Maximum Ratings

- UL Recognized File # E165989
- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Mounting torque: 5in-lbs.

MCC Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
GBJL20005	GBJL20005	50V	35V	50V
GBJL2001	GBJL2001	100V	70V	100V
GBJL2002	GBJL2002	200V	140V	200V
GBJL2004	GBJL2004	400V	280V	400V
GBJL2006	GBJL2006	600V	420V	600V
GBJL2008	GBJL2008	800V	560V	800V
GBJL2010	GBJL2010	1000V	700V	1000V




Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	20 A	$T_C = 100^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	240A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V_F	1.05V	$I_{FM} = 10.0 \text{ A}$ $T_J = 25^\circ\text{C}$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	10 μA 500uA	$T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$
Typical thermal resistance	$R_{\theta JC}$	0.8°C/W	
Typical Junction Capacitance	C_J	60 pF	Measured at 1.0MHz, $V_R=4.0\text{V}$

*Pulse Test: Pulse Width 300 μsec , Duty Cycle 1%






Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7.

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	1.067	1.091	27.10	27.70	
B	.551	.575	14.00	14.60	
C	.570	.610	14.50	15.50	
D	.071 typ		1.80 typ		
E	.339	.354	8.60	9.00	
F	.071	.087	1.80	2.20	
G	.120	.134	3.00	3.40	
H	.110	.126	2.80	3.20	
J	.098	.114	2.50	2.90	
K	.012	.028	0.30	0.70	
L	.098	.114	2.50	2.90	
M	.035	.043	0.90	1.10	
N	.390	.400	9.80	10.20	
O	.290	.300	7.30	7.70	
P	.079	.094	2.00	2.40	
R	.150	.157	3.60	4.00	



www.mccsemi.com

**RATING AND CHARACTERISTIC CURVES
GBJL20005 thru GBJL2010**





Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-BP	Bulk: 2.2K/Ctn

Note : Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View GBJL2001-BP on WIN SOURCE](#)
- ⊖ [Micro Commercial Co](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management