



**THE DATASHEET OF
MAX6174BASA+**



MAX6173–MAX6177

High-Precision Voltage References with Temperature Sensor

General Description

The MAX6173–MAX6177 are low-noise, high-precision voltage references. The devices feature a proprietary temperature-coefficient curvature-correction circuit and laser-trimmed thin-film resistors that result in a very low 3ppm/°C temperature coefficient and excellent $\pm 0.06\%$ initial accuracy. The MAX6173–MAX6177 provide a TEMP output where the output voltage is proportional to the die temperature, making the devices suitable for a wide variety of temperature-sensing applications. The devices also provide a TRIM input, allowing fine trimming of the output voltage with a resistive divider network. Low temperature drift and low noise make the devices ideal for use with high-resolution A/D or D/A converters.

The MAX6173–MAX6177 provide accurate preset +2.5V, +3.3V, +4.096V, +5.0V, and +10V reference voltages and accept input voltages up to +40V. The devices draw 320 μ A (typ) of supply current and source 30mA or sink 2mA of load current. The MAX6173–MAX6177 use band-gap technology for low-noise performance and excellent accuracy. The MAX6173–MAX6177 do not require an output bypass capacitor for stability, and are stable with capacitive loads up to 100 μ F. Eliminating the output bypass capacitor saves valuable board area in space-critical applications.

The MAX6173–MAX6177 are available in an 8-pin SO package and operate over the automotive (-40°C to +125°C) temperature range.

Applications


- ADCs
- DACs
- Digital Voltmeters
- Automotive
- Voltage Regulators
- Threshold Detectors

Pin Configuration and Ordering Information appears at end of data sheet.

Benefits and Features

- Wide ($V_{OUT} + 2V$) to +40V Supply Voltage Range
- Excellent Temperature Stability: 3ppm/°C (max)
- Tight Initial Accuracy: 0.05% (max)
- Low Noise: 3.8 μ V_{P-P} (typ at 2.5V Output)
- Sources up to 30mA Output Current
- Low Supply Current: 450 μ A (max at +25°C)
- Linear Temperature Transducer Voltage Output
- +2.5V, +3.3V, +4.096V, +5.0V, or +10V Output Voltages
- Wide Operating Temperature Range: -40°C to +125°C
- No External Capacitors Required for Stability
- Short-Circuit Protected
- AEC-Q100 Qualified (Refer to Ordering Info Section for I/V parts)

Typical Operating Circuit



Absolute Maximum Ratings

| | | | |
|---|-----------------------------------|---|-----------------|
| IN to GND..... | -0.3V to +42V | Operating Temperature Range..... | -40°C to +125°C |
| OUT, TRIM, TEMP to GND | -0.3V to (V _{IN} + 0.3V) | Junction Temperature..... | +150°C |
| Output Short-Circuit to GND | 5s | Storage Temperature Range..... | -65°C to +150°C |
| Continuous Power Dissipation (T _A = +70°C) (Note1) | | Lead Temperature (soldering, 10s) | +300°C |
| 8-Pin SO (derate 7.6mW/°C above +70°C)..... | 606mW | Soldering Temperature (reflow)..... | +260°C |

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Package Thermal Characteristics (Note 1)

8 SO

| PACKAGE CODE | S8+4 |
|---|-------------------------|
| Outline Number | 21-0041 |
| Land Pattern Number | 90-0096 |
| Thermal Resistance, Single-Layer Board | |
| Junction to Ambient - θ_{JA} | 170 |
| Junction to Case - θ_{JC} | 40 |
| Thermal Resistance, Multi-Layer Board | |
| Junction to Ambient - θ_{JA} | 132°C/W |
| Junction to Case - θ_{JC} | 38°C/W |

8 SO

| PACKAGE CODE | S8+22 |
|---|-------------------------|
| Outline Number | 21-0041 |
| Land Pattern Number | 90-0096 |
| Thermal Resistance, Single-Layer Board | |
| Junction to Ambient - θ_{JA} | 170°C/W |
| Junction to Case - θ_{JC} | 40°C/W |
| Thermal Resistance, Multi-Layer Board | |
| Junction to Ambient - θ_{JA} | 132°C/W |
| Junction to Case - θ_{JC} | 38°C/W |

For the latest package outline information and land patterns (footprints), go to www.maximintegrated.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

Package thermal resistances were obtained using the method described in JEDEC specification JESD51-7, using a four-layer board. For detailed information on package thermal considerations, refer to www.maximintegrated.com/thermal-tutorial.

Electrical Characteristics—MAX6173 (V_{OUT} = 2.5V)(V_{IN} = +5V, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS | |
|---|--------------------------------------|--|----------------------------------|--------|------|-------------------|--------|
| OUTPUT | | | | | | | |
| Output Voltage | V _{OUT} | No load, T _A = +25°C | MAX6173A (0.06%) | 2.4985 | 2.5 | 2.5015 | V |
| | | | MAX6173B (0.1%) | 2.4975 | 2.5 | 2.5025 | |
| Output Adjustment Range | ΔV _{TRIM} | R _{POT} = 10kΩ | ±3 | ±6 | | % | |
| Output-Voltage Temperature Coefficient (Note 3) | TCV _{OUT} | T _A = -40°C to +125°C | MAX6173AASA | | 1.5 | 3 | ppm/°C |
| | | | MAX6173BASA | | 3 | 10 | |
| Line Regulation (Note 4) | ΔV _{OUT} /ΔV _{IN} | 4.5V ≤ V _{IN} ≤ 40V | T _A = +25°C | | 0.6 | 5 | ppm/V |
| | | | T _A = -40°C to +125°C | | 0.8 | 10 | |
| Load Regulation (Note 4) | ΔV _{OUT} /ΔI _{OUT} | Sourcing: 0 ≤ I _{OUT} ≤ 10mA | T _A = +25°C | | 2 | 10 | ppm/mA |
| | | | T _A = -40°C to +125°C | | 2 | 15 | |
| | | Sinking: -0.6mA ≤ I _{OUT} ≤ 0 | T _A = +25°C | | 50 | 500 | |
| | | | T _A = -40°C to +125°C | | 90 | 900 | |
| Output Short-Circuit Current | I _{SC} | OUT shorted to GND | | 60 | | mA | |
| | | OUT shorted to IN | | 3 | | | |
| Temperature Hysteresis (Note 5) | ΔV _{OUT} /cycle | | | 120 | | ppm | |
| Long-Term Stability | ΔV _{OUT} /time | 1000 hours at T _A = +25°C | | 50 | | ppm | |
| DYNAMIC | | | | | | | |
| Noise Voltage | e _{OUT} | f = 0.1Hz to 10Hz | | 3.8 | | μV _{P-P} | |
| | | f = 10Hz to 1kHz | | 6.8 | | μV _{RMS} | |
| Turn-On Settling Time | t _R | To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF | | 150 | | μs | |
| INPUT | | | | | | | |
| Supply Voltage Range | V _{IN} | Guaranteed by line regulation test | 4.5 | | 40.0 | V | |
| Quiescent Supply Current | I _{IN} | No load | T _A = +25°C | | 300 | 450 | μA |
| | | | T _A = -40°C to +125°C | | | 600 | |
| TEMP OUTPUT | | | | | | | |
| TEMP Output Voltage | V _{TEMP} | | | 570 | | mV | |
| TEMP Temperature Coefficient | TC _{TEMP} | | | 1.9 | | mV/°C | |

Electrical Characteristics—MAX6177 (V_{OUT} = 3.3V)(V_{IN} = +10V, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS | |
|---|--------------------------------------|--|----------------------------------|--------|------|-------------------|--------|
| OUTPUT | | | | | | | |
| Output Voltage | V _{OUT} | No load, T _A = +25°C | MAX6177A (0.06%) | 3.2980 | 3.3 | 3.3020 | V |
| | | | MAX6177B (0.1%) | 3.2967 | 3.3 | 3.3033 | |
| Output Adjustment Range | ΔV _{TRIM} | R _{POT} = 10kΩ | ±3 | ±6 | | % | |
| Output-Voltage Temperature Coefficient (Note 3) | TCV _{OUT} | T _A = -40°C to +125°C | MAX6177AASA | | 1.5 | 3 | ppm/°C |
| | | | MAX6177BASA | | 3 | 10 | |
| Line Regulation (Note 4) | ΔV _{OUT} /ΔV _{IN} | 5.3V ≤ V _{IN} ≤ 40V | T _A = +25°C | | 0.6 | 5 | ppm/V |
| | | | T _A = -40°C to +125°C | | 0.8 | 10 | |
| Load Regulation (Note 4) | ΔV _{OUT} /ΔI _{OUT} | Sourcing: 0 ≤ I _{OUT} ≤ 10mA | T _A = +25°C | | 2 | 10 | ppm/mA |
| | | | T _A = -40°C to +125°C | | 2 | 15 | |
| | | Sinking: -0.6mA ≤ I _{OUT} ≤ 0 | T _A = +25°C | | 50 | 500 | |
| | | | T _A = -40°C to +125°C | | 90 | 900 | |
| Output Short-Circuit Current | I _{SC} | OUT shorted to GND | | 60 | | mA | |
| | | OUT shorted to IN | | 3 | | | |
| Temperature Hysteresis (Note 5) | ΔV _{OUT} /cycle | | | 120 | | ppm | |
| Long-Term Stability | ΔV _{OUT} /time | 1000 hours at T _A = +25°C | | 50 | | ppm | |
| DYNAMIC | | | | | | | |
| Noise Voltage | e _{OUT} | f = 0.1Hz to 10Hz | | 5 | | μV _{P-P} | |
| | | f = 10Hz to 1kHz | | 9.3 | | μV _{RMS} | |
| Turn-On Settling Time | t _R | To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF | | 180 | | μs | |
| INPUT | | | | | | | |
| Supply Voltage Range | V _{IN} | Guaranteed by line regulation test | 5.3 | | 40.0 | V | |
| Quiescent Supply Current | I _{IN} | No load | T _A = +25°C | | 320 | 500 | μA |
| | | | T _A = -40°C to +125°C | | | 650 | |
| TEMP OUTPUT | | | | | | | |
| TEMP Output Voltage | V _{TEMP} | | | 630 | | mV | |
| TEMP Temperature Coefficient | TC _{TEMP} | | | 2.1 | | mV/°C | |

Electrical Characteristics—MAX6174 (V_{OUT} = 4.096V)(V_{IN} = +10V, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS | | |
|---|--------------------------------------|--|---|----------------------------------|-------|-------------------|--------|-----|
| OUTPUT | | | | | | | | |
| Output Voltage | V _{OUT} | No load, T _A = +25°C | MAX6174A (0.06%) | 4.0935 | 4.096 | 4.0985 | V | |
| | | | MAX6174B (0.1%) | 4.0919 | 4.096 | 4.1001 | | |
| Output Adjustment Range | ΔV _{TRIM} | R _{POT} = 10kΩ | ±3 | ±6 | | % | | |
| Output-Voltage Temperature Coefficient (Note 3) | TCV _{OUT} | T _A = -40°C to +125°C | MAX6174AASA | | 1.5 | 3 | ppm/°C | |
| | | | MAX6174BASA | | 3 | 10 | | |
| Line Regulation (Note 4) | ΔV _{OUT} /ΔV _{IN} | 6.1V ≤ V _{IN} ≤ 40V | T _A = +25°C | | 0.6 | 5 | ppm/V | |
| | | | T _A = -40°C to +125°C | | 0.8 | 10 | | |
| Load Regulation (Note 4) | ΔV _{OUT} /ΔI _{OUT} | Sourcing: 0 ≤ I _{OUT} ≤ 10mA | T _A = +25°C | | 2 | 10 | ppm/mA | |
| | | | T _A = -40°C to +125°C | | 2 | 15 | | |
| | | | Sinking: -0.6mA ≤ I _{OUT} ≤ 0 | T _A = +25°C | | 50 | | 500 |
| | | | | T _A = -40°C to +125°C | | 90 | | 900 |
| Output Short-Circuit Current | I _{SC} | OUT shorted to GND | | 60 | | mA | | |
| | | OUT shorted to IN | | 3 | | | | |
| Temperature Hysteresis (Note 5) | ΔV _{OUT} /cycle | | | 120 | | ppm | | |
| Long-Term Stability | ΔV _{OUT} /time | 1000 hours at T _A = +25°C | | 50 | | ppm | | |
| DYNAMIC | | | | | | | | |
| Noise Voltage | e _{OUT} | f = 0.1Hz to 10Hz | | 7 | | μV _{P-P} | | |
| | | f = 10Hz to 1kHz | | 11.5 | | μV _{RMS} | | |
| Turn-On Settling Time | t _R | To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF | | 200 | | μs | | |
| INPUT | | | | | | | | |
| Supply Voltage Range | V _{IN} | Guaranteed by line regulation test | 6.1 | | 40.0 | V | | |
| Quiescent Supply Current | I _{IN} | No load | T _A = +25°C | | 320 | 500 | μA | |
| | | | T _A = -40°C to +125°C | | | 650 | | |
| TEMP OUTPUT | | | | | | | | |
| TEMP Output Voltage | V _{TEMP} | T _A = +25°C | 475 | 630 | 785 | mV | | |
| | | T _A = -40°C to +125°C | 300 | | 1130 | | | |
| TEMP Temperature Coefficient | TC _{TEMP} | | | 2.1 | | mV/°C | | |

Electrical Characteristics—MAX6175 ($V_{OUT} = 5.0V$) $(V_{IN} = +15V, T_A = -40^{\circ}C$ to $+125^{\circ}C$, unless otherwise noted. Typical values are at $T_A = +25^{\circ}C$.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS | |
|---|---|---|---|---------|------|------------------|---|
| OUTPUT | | | | | | | |
| Output Voltage | V_{OUT} | No load, $T_A = +25^{\circ}C$ | MAX6175A (0.06%) | 4.9970 | 5.0 | 5.0030 | V |
| | | | MAX6175B (0.1%) | 4.9950 | 5.0 | 5.0050 | |
| Output Adjustment Range | ΔV_{TRIM} | $R_{POT} = 10k\Omega$ | ± 3 | ± 6 | | % | |
| Output-Voltage Temperature Coefficient (Note 3) | TCV_{OUT} | $T_A = -40^{\circ}C$ to $+125^{\circ}C$ | MAX6175AASA | 1.5 | 3 | ppm/ $^{\circ}C$ | |
| | | | MAX6175BASA | 3 | 10 | | |
| Line Regulation (Note 4) | $\frac{\Delta V_{OUT}}{\Delta V_{IN}}$ | $7V \leq V_{IN} \leq 40V$ | $T_A = +25^{\circ}C$ | 0.6 | 5 | ppm/V | |
| | | | $T_A = -40^{\circ}C$ to $+125^{\circ}C$ | 0.8 | 10 | | |
| Load Regulation (Note 4) | $\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$ | Sourcing: $0 \leq I_{OUT} \leq 10mA$ | $T_A = +25^{\circ}C$ | 2 | 10 | ppm/mA | |
| | | | $T_A = -40^{\circ}C$ to $+125^{\circ}C$ | 2 | 15 | | |
| | | Sinking: $-0.6mA \leq I_{OUT} \leq 0$ | $T_A = +25^{\circ}C$ | 50 | 500 | | |
| | | | $T_A = -40^{\circ}C$ to $+125^{\circ}C$ | 90 | 900 | | |
| Output Short-Circuit Current | I_{SC} | OUT shorted to GND | | 60 | | mA | |
| | | OUT shorted to IN | | 3 | | | |
| Temperature Hysteresis (Note 5) | $\frac{\Delta V_{OUT}}{\text{cycle}}$ | | | 120 | | ppm | |
| Long-Term Stability | $\frac{\Delta V_{OUT}}{\text{time}}$ | 1000 hours at $T_A = +25^{\circ}C$ | | 50 | | ppm | |
| DYNAMIC | | | | | | | |
| Noise Voltage | e_{OUT} | $f = 0.1Hz$ to $10Hz$ | | 9 | | μV_{P-P} | |
| | | $f = 10Hz$ to $1kHz$ | | 14.5 | | μV_{RMS} | |
| Turn-On Settling Time | t_R | To $V_{OUT} = 0.1\%$ of final value, $C_{OUT} = 50pF$ | | 230 | | μs | |
| INPUT | | | | | | | |
| Supply Voltage Range | V_{IN} | Guaranteed by line regulation test | 7.0 | | 40.0 | V | |
| Quiescent Supply Current | I_{IN} | No load | $T_A = +25^{\circ}C$ | 320 | 550 | μA | |
| | | | $T_A = -40^{\circ}C$ to $+125^{\circ}C$ | | 700 | | |
| TEMP OUTPUT | | | | | | | |
| TEMP Output Voltage | V_{TEMP} | $T_A = +25^{\circ}C$ | 475 | 630 | 785 | mV | |
| | | $T_A = -40^{\circ}C$ to $+125^{\circ}C$ | 300 | | 1130 | | |
| TEMP Temperature Coefficient | TC_{TEMP} | | | 2.1 | | mV/ $^{\circ}C$ | |










ELECTRICAL CHARACTERISTICS—MAX6176 (V_{OUT} = 10V)(V_{IN} = +15V, T_A = -40°C to +125°C, unless otherwise noted. Typical values are at T_A = +25°C.) (Note 2)

| PARAMETER | SYMBOL | CONDITIONS | | MIN | TYP | MAX | UNITS | |
|---|--------------------------------------|--|---|----------------------------------|------|---------|-------------------|-----|
| OUTPUT | | | | | | | | |
| Output Voltage | V _{OUT} | No load, T _A = +25°C | MAX6176A (0.05%) | 9.9950 | 10.0 | 10.0050 | V | |
| | | | MAX6176B (0.1%) | 9.9900 | 10.0 | 10.0100 | | |
| Output Adjustment Range | ΔV _{TRIM} | R _{POT} = 10kΩ | | ±3 | ±6 | | % | |
| Output-Voltage Temperature Coefficient (Note 3) | TCV _{OUT} | T _A = -40°C to +125°C | MAX6176AASA | | 1.5 | 3 | ppm/°C | |
| | | | MAX6176BASA | | 3 | 10 | | |
| Line Regulation (Note 4) | ΔV _{OUT} /ΔV _{IN} | 12V ≤ V _{IN} ≤ 40V | T _A = +25°C | | 0.6 | 5 | ppm/V | |
| | | | T _A = -40°C to +125°C | | 0.8 | 10 | | |
| Load Regulation (Note 4) | ΔV _{OUT} /ΔI _{OUT} | Sourcing: 0 ≤ I _{OUT} ≤ 10mA | T _A = +25°C | | 2 | 10 | ppm/mA | |
| | | | T _A = -40°C to +125°C | | 2 | 15 | | |
| | | | Sinking: -0.6mA ≤ I _{OUT} ≤ 0 | T _A = +25°C | | 50 | | 500 |
| | | | | T _A = -40°C to +125°C | | 90 | | 900 |
| Output Short-Circuit Current | I _{SC} | OUT shorted to GND | | | 60 | | mA | |
| | | OUT shorted to IN | | | 3 | | | |
| Temperature Hysteresis (Note 5) | ΔV _{OUT} /cycle | | | | 120 | | ppm | |
| Long-Term Stability | ΔV _{OUT} /time | 1000 hours at T _A = +25°C | | | 50 | | ppm | |
| DYNAMIC | | | | | | | | |
| Noise Voltage | e _{OUT} | f = 0.1Hz to 10Hz | | | 18 | | μV _{P-P} | |
| | | f = 10Hz to 1kHz | | | 29 | | μV _{RMS} | |
| Turn-On Settling Time | t _R | To V _{OUT} = 0.1% of final value, C _{OUT} = 50pF | | | 400 | | μs | |
| INPUT | | | | | | | | |
| Supply Voltage Range | V _{IN} | Guaranteed by line regulation test | | 12.0 | | 40.0 | V | |
| Quiescent Supply Current | I _{IN} | No load | T _A = +25°C | | 340 | 550 | μA | |
| | | | T _A = -40°C to +125°C | | | 700 | | |
| TEMP OUTPUT | | | | | | | | |
| TEMP Output Voltage | V _{TEMP} | | | | 630 | | mV | |
| TEMP Temperature Coefficient | TC _{TEMP} | | | | 2.1 | | mV/°C | |

Note 2: All devices are 100% production tested at T_A = +25°C and guaranteed by design over T_A = T_{MIN} to T_{MAX}, as specified.**Note 3:** Temperature coefficient is defined as ΔV_{OUT} divided by the temperature range.**Note 4:** Line and load regulation specifications do not include the effects of self-heating.**Note 5:** Thermal hysteresis is defined as the change in +25°C output voltage before and after cycling the device from T_{MAX} to T_{MIN}.










Typical Operating Characteristics

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)












Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)












Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)










Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)









Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)









Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)









Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)







Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)



Typical Operating Characteristics (continued)

($V_{IN} = +5V$ for $V_{OUT} = +2.5V$, $V_{IN} = +15V$ for $V_{OUT} = 4.096V$ and $V_{OUT} = +10V$, $I_{OUT} = 0$, $T_A = +25^\circ C$, unless otherwise noted.)



Pin Description

| PIN | NAME | FUNCTION |
|------|------|--|
| 1, 8 | I.C. | Internally Connected. Do not connect externally. |
| 2 | IN | Positive Power-Supply Input |
| 3 | TEMP | Temperature Proportional Output Voltage. TEMP generates an output voltage proportional to the die temperature. |
| 4 | GND | Ground |
| 5 | TRIM | Output Voltage Trim. Connect TRIM to the center of a voltage-divider between OUT and GND for trimming. Leave unconnected to use the preset output voltage. |
| 6 | OUT | Output Voltage |
| 7 | N.C. | No Connection. Not internally connected. |

Detailed Description

The MAX6173–MAX6177 precision voltage references provide accurate preset +2.5V, +3.3V, +4.096V, +5.0V, and +10V reference voltages from up to +40V input voltages. These devices feature a proprietary temperature-coefficient curvature-correction circuit and laser-trimmed thin-film resistors that result in a very low 3ppm/°C temperature coefficient and excellent 0.05% initial accuracy. The MAX6173–MAX6177 draw 340µA of supply current and source 30mA or sink 2mA of load current.

Trimming the Output Voltage

Trim the factory-preset output voltage on the MAX6173–MAX6177 by placing a resistive divider network between OUT, TRIM, and GND.

Use the following formula to calculate the change in output voltage from its preset value:

$$\Delta V_{OUT} = 2 \times (V_{TRIM} - V_{TRIM (open)}) \times k$$

where:

$$V_{TRIM} = 0V \text{ to } V_{OUT}$$

$$V_{TRIM (open)} = V_{OUT} \text{ (nominal)}/2 \text{ (typ)}$$

$$k = \pm 6\% \text{ (typ)}$$

For example, use a 50kΩ potentiometer (such as the MAX5436) between OUT, TRIM, and GND with the potentiometer wiper connected to TRIM (see Figure 2). As the TRIM voltage changes from V_{OUT} to GND, the output voltage changes accordingly. Set R2 to 1MΩ or less. Currents through resistors R1 and R2 add to the quiescent supply current.

Temp Output

The MAX6173–MAX6177 provide a temperature output proportional to die temperature. TEMP can be calculated from the following formula:

$$TEMP (V) = T_J (\text{°K}) \times n$$

where T_J = the die temperature,

n = the temperature multiplier,

$$n = \frac{V_{TEMP}(\text{at } T_J = T_0)}{T_0} \cong 1.9\text{mV}/\text{°K}$$

T_A = the ambient temperature.

Self-heating affects the die temperature and conversely, the TEMP output. The TEMP equation assumes the output is not loaded. If device power dissipation is negligible, then $T_J \approx T_A$.

Applications Information

Bypassing/Output Capacitance

For the best line-transient performance, decouple the input with a 0.1µF ceramic capacitor as shown in the *Typical Operating Circuit*. Place the capacitor as close to IN as possible. When transient performance is less important, no capacitor is necessary.

The MAX6173–MAX6177 do not require an output capacitor for stability and are stable with capacitive loads up to 100µF. In applications where the load or the supply can experience step changes, a larger output capacitor reduces the amount of overshoot (undershoot) and improves the circuit’s transient response. Place output capacitors as close to the devices as possible for best performance.

Supply Current

The MAX6173–MAX6177 consume 320µA (typ) of quiescent supply current. This improved efficiency reduces power dissipation and extends battery life.

Thermal Hysteresis

Thermal hysteresis is the change in the output voltage at $T_A = +25^\circ\text{C}$ before and after the device is cycled over its entire operating temperature range. Hysteresis is caused by differential package stress appearing across the band-gap core transistors. The typical thermal hysteresis value is 120ppm.

Turn-On Time

The MAX6173–MAX6177 typically turn on and settle to within 0.1% of the preset output voltage in 150µs (2.5V output). The turn-on time can increase up to 150µs with the device operating with a 1µF load.

Short-Circuited Outputs

The MAX6173–MAX6177 feature a short-circuit-protected output. Internal circuitry limits the output current to 60mA when short circuiting the output to ground. The output current is limited to 3mA when short circuiting the output to the input.

Temperature Coefficient vs. Operating Temperature Range for a 1 LSB Maximum Error

In a data converter application, the reference voltage of the converter must stay within a certain limit to keep the error in the data converter smaller than the resolution limit through the operating temperature range. Figure 1 shows the maximum allowable reference-voltage temperature coefficient to keep the conversion error to less than 1 LSB, as a function of the operating temperature range ($T_{MAX} - T_{MIN}$) with the converter resolution as a parameter. The graph assumes the reference-voltage temperature coefficient as the only parameter affecting accuracy.

In reality, the absolute static accuracy of a data converter is dependent on the combination of many parameters such as integral nonlinearity, differential nonlinearity, offset error, gain error, as well as voltage-reference changes.




Figure 1. Temperature Coefficient vs. Operating Temperature Range for a 1 LSB Maximum Error





Figure 2. Applications Circuit Using the MAX5436 Potentiometer

Pin Configuration



Chip Information

PROCESS: BiCMOS

Package Information

For the latest package outline information and land patterns (footprints), go to www.maximintegrated.com/packages. Note that a “+”, “#”, or “.” in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

| PACKAGE TYPE | PACKAGE CODE | OUTLINE NO. | LAND PATTERN NO. |
|--------------|--------------|-------------------------|-------------------------|
| 8 SO | S8+4 | 21-0041 | 90-0096 |
| 8 SO | S8+22 | 21-0041 | 90-0096 |

Ordering Information/Selector Guide

| PART | TEMP RANGE | PIN-PACKAGE | OUTPUT VOLTAGE (V) | TEMPERATURE COEFFICIENT (ppm/°C) -40°C TO +125°C | INITIAL ACCURACY (%) |
|----------------------|-----------------|-------------|--------------------|--|----------------------|
| MAX6173 AASA+ | -40°C to +125°C | 8 SO | 2.500 | 3 | 0.06 |
| MAX6173BASA+ | -40°C to +125°C | 8 SO | 2.500 | 10 | 0.10 |
| MAX6173BASA/V+T | -40°C to +125°C | 8 SO | 2.500 | 3 | 0.06 |
| MAX6174 AASA+ | -40°C to +125°C | 8 SO | 4.096 | 3 | 0.06 |
| MAX6174BASA+ | -40°C to +125°C | 8 SO | 4.096 | 10 | 0.10 |
| MAX6174BASA/V+ | -40°C to +125°C | 8 SO | 4.096 | 10 | 0.10 |
| MAX6174BASA/V+T | -40°C to +125°C | 8 SO | 4.096 | 10 | 0.10 |
| MAX6175 AASA+ | -40°C to +125°C | 8 SO | 5.000 | 3 | 0.06 |
| MAX6175BASA+ | -40°C to +125°C | 8 SO | 5.000 | 10 | 0.10 |
| MAX6175BASA/V+ | -40°C to +125°C | 8 SO | 5.000 | 10 | 0.10 |
| MAX6176 AASA+ | -40°C to +125°C | 8 SO | 10.000 | 3 | 0.05 |
| MAX6176BASA+ | -40°C to +125°C | 8 SO | 10.000 | 10 | 0.10 |
| MAX6177 AASA+ | -40°C to +125°C | 8 SO | 3.300 | 3 | 0.06 |
| MAX6177BASA+ | -40°C to +125°C | 8 SO | 3.300 | 10 | 0.10 |

+Denotes a lead(Pb)-free/RoHS-compliant package.

/V denotes an automotive qualified part

Revision History

| REVISION NUMBER | REVISION DATE | DESCRIPTION | PAGES CHANGED |
|-----------------|---------------|---|---------------|
| 0 | 6/04 | Initial release | — |
| 1 | 2/11 | Added automotive grade part, lead-free information, and soldering temperature | 1, 2 |
| 2 | 3/14 | Updated package code in <i>Package Information</i> | 14 |
| 3 | 6/14 | Updated <i>Ordering Information</i> , <i>Electrical Characteristics</i> , and <i>Typical Operating Characteristics</i> | 1, 4, 5, 8 |
| 4 | 9/14 | Updated <i>Typical Operating Characteristics</i> | 7–14 |
| 5 | 9/14 | Updated <i>Typical Operating Characteristics</i> | 7–15 |
| 6 | 12/17 | Added AEC statement to <i>Benefits and Features</i> section | 1 |
| 7 | 3/18 | Updated <i>Ordering Information</i> table | 18 |
| 8 | 3/18 | Updated <i>Absolute Maximum Ratings</i> section and <i>Electrical Characteristics</i> table | 2–6 |
| 9 | 3/18 | Updated <i>Absolute Maximum Ratings</i> section | 2 |
| 10 | 10/18 | Update <i>Applications</i> , <i>Package Thermal Characteristics</i> , <i>Package Information</i> , and <i>Ordering Information/Selector Guide</i> | 1, 2, 18 |
| 11 | 4/19 | Updated <i>General Description</i> section | 1 |

For pricing, delivery, and ordering information, please visit Maxim Integrated's online storefront at <https://www.maximintegrated.com/en/storefront/storefront.html>.

Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the *Electrical Characteristics* table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View MAX6174BASA+ on WIN SOURCE](#)

 [Maxim Integrated](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management