



RECOMMENDED HOLE LAYOUT FOR .070/1.78
VIEWED FROM COMPONENT

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE
$\nabla = 0$	4 PLACES ± .005	IN/MM
$\nabla = 0$	3 PLACES ± .015	DRAWN BY GEP DATE 1994/07/25
$\nabla = 0$	2 PLACES ± 0.38	CHECKED BY RJF DATE 1994/07/25
$\nabla = 0$	1 PLACE ± 0.50	APPROVED BY RJF DATE 1994/07/25
	ANGULAR ± 1/2°	MATERIAL NO. 1994/07/25

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS
SEE CHARTS
THIS DRAWING CONTAINS INCORPORATED AND S

REV	DESCRIPTION
M	EC NO: UCP2012-1560 DRW: NANGUYEN 2012/01/05 CHKD: JBELL 2012/01/05 APP: FSMITH 2012/02/02

SEE SHT. 1 FOR SINGLE ROW

DUAL ROW PART NUMBERS WITH MATTE TIN PLATING

WITH PEGS

PLATING:	I (SEE NOTE 2)		PLATING:	I (SEE NOTE 2)	
DRAINS:	WITHOUT DRAIN HOLES	WITHOUT DRAIN HOLES	DRAINS:	WITH DRAIN HOLES	DRAINS:
PEGS:	WITH PEGS	WITH PEGS	PEGS:	WITH PEGS	PEGS:
MAT'L:	94V-2 [NATURAL]	94V-0 [NATURAL]	MAT'L:	94V-2 [NATURAL]	MAT'L:
PACKAGING:	PK-5566-001	PK-5566-001	PACKAGING:	PK-5566-001	PACKAGING:
ITEM NO.	CKTS	ITEM NO.	ITEM NO.	CKTS	CKTS
44472-0250	2	44472-0251	44472-0252	2	2
44472-0450	4	44472-0451	44472-0452	4	4
44472-0650	6	44472-0651	44472-0652	6	6
44472-0850	8	44472-0851	44472-0852	8	8
44472-1050	10	44472-1051	44472-1052	10	10
44472-1250	12	44472-1251	44472-1252	12	12
44472-1450	14	44472-1451	44472-1452	14	14
44472-1650	16	44472-1651	44472-1652	16	16
44472-1850	18	44472-1851	44472-1852	18	18
44472-2050	20	44472-2051	44472-2052	20	20
44472-2250	22	44472-2251	44472-2252	22	22
44472-2450	24	44472-2451	44472-2452	24	24

G

WITHOUT PEGS

PLATING:	I (SEE NOTE 2)		PLATING:	I (SEE NOTE 2)	
DRAINS:	WITHOUT DRAIN HOLES	WITHOUT DRAIN HOLES	DRAINS:	WITH DRAIN HOLES	DRAINS:
PEGS:	WITHOUT PEGS	WITHOUT PEGS	PEGS:	WITHOUT PEGS	PEGS:
MAT'L:	94V-2 [NATURAL]	94V-0 [NATURAL]	MAT'L:	94V-2 [NATURAL]	MAT'L:
PACKAGING:	PK-5566-001	PK-5566-001	PACKAGING:	PK-5566-001	PACKAGING:
ITEM NO.	HOUSING NO.	ITEM NO.	ITEM NO.	CKTS	CKTS
44472-0254	2	44472-0255	44472-0256	2	2
44472-0454	4	44472-0455	44472-0456	4	4
44472-0654	6	44472-0655	44472-0656	6	6
44472-0854	8	44472-0855	44472-0856	8	8
44472-1054	10	44472-1055	44472-1056	10	10
44472-1254	12	44472-1255	44472-1256	12	12
44472-1454	14	44472-1455	44472-1456	14	14
44472-1654	16	44472-1655	44472-1656	16	16
44472-1854	18	44472-1855	44472-1856	18	18
44472-2054	20	44472-2055	44472-2056	20	20
44472-2254	22	44472-2255	44472-2256	22	22
44472-2454	24	44472-2455	44472-2456	24	24

C

* ITEMS PRECEDED BY AN "X" ARE NOT AVAILABLE.

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE
= 0 = 0 = 0	mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± 0.15 2 PLACES ± 0.38 ± .020 1 PLACE ± 0.50 ± --- ANGULAR ± 1/2°	DRAWN BY DATE GEP 1994/07/25 CHECKED BY DATE RJF 1994/07/25 APPROVED BY DATE RJF 1994/07/25 MATERIAL NO. 1994/07/25
DESCRIPTION	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS SEE CHARTS THIS DRAWING CONTAINS INCORPORATED AND SI	

REV	DESCRIPTION	DATE
M	EC NO: UCP2012-1560 DRWMANGUYEN 2012/01/05	2012/01/05
	CHKD:JBELL 2012/01/05	2012/01/05
	APR:FSMITH 2012/02/02	2012/02/02

DUAL ROW PART NUMBERS WITH SELECT GOLD PLATING

J

WITH PEGS		2 (SEE NOTE 2)		2 (SEE NOTE 2)		PLATING:	
PLATING:	WITHOUT DRAIN HOLES	WITH PEGS	WITHOUT DRAIN HOLES	WITH DRAIN HOLES	WITH PEGS	DRAINS:	WITH DRAIN HOLES
PEGS:	WITH PEGS	WITHOUT PEGS	WITH PEGS	WITHOUT PEGS	DRAINS:	WITH PEGS	WITHOUT PEGS
MAT'L:	94V-2 [NATURAL]	94V-0 [NATURAL]	94V-2 [NATURAL]	94V-2 [NATURAL]	MAT'L:	94V-2 [NATURAL]	94V-2 [NATURAL]
PACKAGING:	PK-5566-001	PK-5566-001	PK-5566-001	PK-5566-001	PACKAGING:	PK-5566-001	PK-5566-001
ITEM NO.	CKTS	ITEM NO.	CKTS	ITEM NO.	CKTS	ITEM NO.	CKTS
X	44472-0260	2	X	44472-0261	2	44472-0262	2
X	44472-0460	4	X	44472-0461	4	44472-0462	4
X	44472-0660	6	X	44472-0661	6	44472-0662	6
X	44472-0860	8	X	44472-0861	8	44472-0862	8
X	44472-1060	10	X	44472-1061	10	44472-1062	10
X	44472-1260	12	X	44472-1261	12	44472-1262	12
X	44472-1460	14	X	44472-1461	14	44472-1462	14
X	44472-1660	16	X	44472-1661	16	44472-1662	16
X	44472-1860	18	X	44472-1861	18	44472-1862	18
X	44472-2060	20	X	44472-2061	20	44472-2062	20
X	44472-2260	22	X	44472-2261	22	44472-2262	22
X	44472-2460	24	X	44472-2461	24	44472-2462	24

H

G

F

WITHOUT PEGS		2 (SEE NOTE 2)		2 (SEE NOTE 2)		PLATING:	
PLATING:	WITHOUT DRAIN HOLES	WITHOUT PEGS	WITHOUT DRAIN HOLES	WITHOUT PEGS	WITHOUT PEGS	DRAINS:	WITHOUT PEGS
PEGS:	WITHOUT PEGS	WITHOUT PEGS	WITHOUT PEGS	WITHOUT PEGS	WITHOUT PEGS	DRAINS:	WITHOUT PEGS
MAT'L:	94V-2 [NATURAL]	94V-0 [NATURAL]	94V-2 [NATURAL]	94V-0 [NATURAL]	WITHOUT PEGS	DRAINS:	WITHOUT PEGS
PACKAGING:	PK-5566-001	PK-5566-001	PK-5566-001	PK-5566-001	WITHOUT PEGS	DRAINS:	WITHOUT PEGS
ITEM NO.	CKTS	ITEM NO.	CKTS	ITEM NO.	WITHOUT PEGS	DRAINS:	WITHOUT PEGS
X	44472-0264	2	X	44472-0265	2	44472-0266	2
X	44472-0464	4	X	44472-0465	4	44472-0466	4
X	44472-0664	6	X	44472-0665	6	44472-0666	6
X	44472-0864	8	X	44472-0865	8	44472-0866	8
X	44472-1064	10	X	44472-1065	10	44472-1066	10
X	44472-1264	12	X	44472-1265	12	44472-1266	12
X	44472-1464	14	X	44472-1465	14	44472-1466	14
X	44472-1664	16	X	44472-1665	16	44472-1666	16
X	44472-1864	18	X	44472-1865	18	44472-1866	18
X	44472-2064	20	X	44472-2065	20	44472-2066	20
X	44472-2264	22	X	44472-2265	22	44472-2266	22
X	44472-2464	24	X	44472-2465	24	44472-2466	24

E

D

C

* ITEMS PRECEDED BY A 'X' ARE NOT AVAILABLE.

B

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE
	4 PLACES ± .005	IN/MM
	3 PLACES ± .015	DRAWN BY GEP
	2 PLACES ± 0.38	CHECKED BY RJF
	1 PLACE ± 0.50	APPROVED BY RJF
	ANGULAR ± 1/2°	DATE 1994/07/25
		DATE 1994/07/25

A

EC NO: UCP2012-1560	DRW: MANGUYEN	2012/01/05
CHKD: JBEL	2012/01/05	
APP: FSMITH	2012/02/02	
DESCRIPTION		
REV		

tb_frames_C.P.AM.T
Rev. F 2009/06/18

SEE CHARTS
DRAFT WHERE APPLICABLE
MUST REMAIN WITHIN DIMENSIONS

THIS DRAWING CONTAINS INCORPORATED AND S

J

WITH PEGS	
PLATING: I (SEE NOTE 2)	
DRAINS: WITH DRAIN HOLES	
PEGS: WITH PEGS	
MAT'L: 94V-2 [NATURAL]	
PACKAGING: PK-5566-001	
ITEM NO.	CKTS
X 44472-0270	2
X 44472-0470	4
X 44472-0670	6
X 44472-0870	8
X 44472-1070	10
X 44472-1270	12
X 44472-1470	14
X 44472-1670	16
X 44472-1870	18
X 44472-2070	20
X 44472-2270	22
X 44472-2470	24

F

E

D

C

* ITEMS PRECEDED BY "X" ARE NOT AVAILABLE.

B

EC NO: UCP2012-1560 SEE SHEET 1 DRWMANNAGUYEN 2012/01/05 CHKD:JBELL 2012/01/05 APPR:FSMITH 2012/02/02 DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE
		mm	IN/MM
		4 PLACES ± .015	DRAWN BY GEP
		3 PLACES ± .020	CHECKED BY RJF
		1 PLACE ± 0.38	APPROVED BY RJF
		ANGULAR ±1/2°	DATE 1994/07/25
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DATE 1994/07/25
		MATERIAL NO. SEE CHART	
		SIZE THIS DRAWING CONTAINED AND INCORPORATED AND SI	

A

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 444720654 on WIN SOURCE](#)

 [Molex, LLC Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management