Product Configuration System

Programmable Series Oscillators

SG-8002 **JA** **32.0000M** **-** **P** **H** **C** **L0**

Model Number

Package Type
DB: Plastic 19.8x6.36mm (SG-51 Type)
DC: Plastic 13.7x6.6mm (SG-531 Type)
JA: Plastic 14x8.65mm (SG-615 Type)
JC: Plastic 10.5x5mm (SG-636 Type)
JF: Plastic 5x7mm (SG-645 Type)
CA: Ceramic 5x7mm (SG-710 Type)
LB: NPO 5x3.2mm (SG-550 Type)
CE : Ceramic 3.2x2.5mm (SG-310 Type)
LA: NPO 3.2x2.5mm (SG-350 Type)

Output Frequency
1.0 ~ 125MHz:
M: Unit in MHz

Function
P: OE
S: ST

Power Supply (Vdd) Duty Level
H: 5.0V, CMOS (50% Vdd)
T: 5.0V, TTL (1.4V)
C: 3.3V, CMOS (50% Vdd)

Frequency Stability / Op Temp
B: +/-50ppm -20° ~ +70°C
C: +/-100ppm -20° ~ +70°C
M: +/-100ppm -40° ~ +85°C

Packaging
Tape and Reel
(except DB & I
L0: 1000pcs pe
L3: 250pcs per
B: Bulk

Stick (DB Only
S: 25pcs/stick
Stick (DC Only
S: 35pcs/stick

EPSON
EPSON ELECTRONICS AMERICA, INC.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View SG-8002CA-PCB on WIN SOURCE
- Epson Company Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management