



**THE DATASHEET OF
CHF8838CNF500L**





Features

- DC to 3.0 GHz
- Flanged model
- Low VSWR
- Aluminium Nitride ceramic

Applications

- High power RF transmission

CHF8838CNF Series 150 W Power RF Flanged Chip Termination


General Specifications

Substrate.....ALN
 Resistive Film.....Thick Film
 TabAg
 Tab Attachment
Brazed with epoxy encapsulation
 Mounting FlangeCu plated with Ni
 Resistance.....50 Ω
 Tolerance.....±5 %
 Packaging60 pcs./tray


Absolute Ratings

Power.....150 W
 Frequency3.0 GHz
 VSWR.....1.2 Maximum

Characteristic Curve



Product Dimensions



Reliable Electronic Solutions

Asia-Pacific:

Tel: +886-2 2562-4117
 Fax: +886-2 2562-4116

Europe:

Tel: +41-41 768 5555
 Fax: +41-41 768 5510


The Americas:

Tel: +1-951 781-5500
 Fax: +1-951 781-5700

www.bourns.com



How To Order

CHF 8838 C N F 500 L







Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View CHF8838CNF500L on WIN SOURCE](#)
-  [Bourns Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management