



Characteristics:

- Allows thorough cleaning of ESD sensitive assemblies without the danger of high charges generated by conventional brushes
- Conductive carbon loaded polypropylene handle
- Permanent static dissipative bristles, made of Nylon 6.12, superior grade, high quality Nylon filament
- Yellow bristles, 0.4 mm in diameter
- Highly resilient, durable and abrasion resistant
- For cleaning ESD sensitive assemblies
- Hot stamped with ESD protective symbol
- RTT Resistance: 1×10^9 to $<1 \times 10^{11}$ ohms tested per modified ANSI/ESD S4.1



35686 35687 35688 36093 36094



35689 36095 36097

Item	Handle Type	Overall Length	Overall Width	Bristle Length	Bristle Width	Bristle Height
35686	Flat	5-3/16" (148 mm)	1-1/16" (27 mm)	3/4" (19 mm)	7/8" (22 mm)	3/16" (5 mm)
35687	Flat	6-1/4" (159 mm)	2-1/8" (54 mm)	13/16" (21 mm)	2" (51 mm)	3/16" (5 mm)
35688	Long	6" (152 mm)	1/2" (13 mm)	9/16" (14 mm)	1-1/4" (32 mm)	1/4" (6 mm)
35689	Curved	4" (102 mm)	2-3/4" (70 mm)	1" (24 mm)	3" (76 mm)	1-1/4" (32 mm)
36093	Flat	5-1/8" (130 mm)	10/16" (16 mm)	11/16" (17 mm)	7/16" (11 mm)	1/4" (6 mm)
36094	Flat	5-3/4" (146 mm)	7/8" (22 mm)	3/4" (19 mm)	3/4" (19 mm)	3/16" (5 mm)
36095	Flat	6-1/4" (159 mm)	1-5/8" (41 mm)	13/16" (21 mm)	1-7/8" (48 mm)	3/16" (5 mm)
36097	Long	7" (178 mm)	1/2" (13 mm)	3/4" (19 mm)	2-5/16" (59 mm)	3/8" (10 mm)

Dimensions are taken from the bottom of the brush to the top of the bristles.

Designed to fulfill ANSI/ESD S20.20 requirement to ground all conductors at ESD workstation.

ESD Handbook TR20.20 Table 1 lists under Typical Static Electricity Sources "Brushes (camel/pig hair and synthetic bristles)."

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." (TR 20.20 section 2.4)

Unless otherwise noted, tolerance is $\pm 10\%$.
Specifications and procedures subject to change without notice.
Made in Israel

DISSIPATIVE BRUSHES

3651 WALNUT AVE., CHINO, CA 91710
PHONE: (909) 627-2453
WEBSITE: MendaPump.com



**DRAWING
NUMBER**
35686

DATE:
August
2018

MENDA

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View 36093 on WIN SOURCE](#)
-  [MENDA/EasyBraid Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management