





**THE DATASHEET OF  
CDRH6D38NP-7R4NC**



# SMD Power Inductor CDRH6D38



## Description

- Ferrite drum core construction.
- Magnetically shielded.
- L × W × H: 7.0 × 7.0 × 4.0 mm Max.
- Product weight: 0.6g(Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.

## Environmental Data

- Operating temperature range: -40°C ~ +100°C (including coil's self temperature rise)
- Storage temperature range: -40°C ~ +100°C
- Solder reflow temperature: 260 °C peak.


## Packaging

- Carrier tape and reel packaging
- 13" diameter reel
- 1000pcs per reel



## Applications

- Ideally used in Game machine, HDD, Notebook PC, Projector, PDA, etc as DC-DC converter inductors.


## Dimension - [mm]



## Land pattern and Schematics - [mm]



(3.3μH~15μH)



(18μH~100μH)

# SMD Power Inductor

## CDRH6D38




### Electrical Characteristics

Part Name	Stamp	Inductance ( $\mu\text{H}$ ) [ within ] ※1	D.C.R.( $\Omega$ ) Max. (Typ.) (at 20°C)	Rated Current (A) ※2
CDRH6D38NP-3R3NC	3R3	3.3 $\pm$ 30%	20m (15m)	3.50
CDRH6D38NP-5R0NC	5R0	5.0 $\pm$ 30%	24m (18m)	2.90
CDRH6D38NP-6R2NC	6R2	6.2 $\pm$ 30%	27m (20m)	2.50
CDRH6D38NP-7R4NC	7R4	7.4 $\pm$ 30%	31m (23m)	2.30
CDRH6D38NP-8R7NC	8R7	8.7 $\pm$ 30%	34m (25m)	2.20
CDRH6D38NP-100NC	100	10 $\pm$ 30%	38m (28m)	2.00
CDRH6D38NP-120NC	120	12 $\pm$ 30%	53m (39m)	1.70
CDRH6D38NP-150NC	150	15 $\pm$ 30%	57m (42m)	1.60
CDRH6D38NP-180NC	180	18 $\pm$ 30%	92m (68m)	1.50
CDRH6D38NP-220NC	220	22 $\pm$ 30%	96m (71m)	1.30
CDRH6D38NP-270NC	270	27 $\pm$ 30%	109m (81m)	1.20
CDRH6D38NP-330NC	330	33 $\pm$ 30%	124m (92m)	1.10
CDRH6D38NP-390NC	390	39 $\pm$ 30%	138m(102m)	1.00
CDRH6D38NP-470NC	470	47 $\pm$ 30%	155m(115m)	0.95
CDRH6D38NP-560NC	560	56 $\pm$ 30%	202m(150m)	0.85
CDRH6D38NP-680NC	680	68 $\pm$ 30%	234m(173m)	0.75
CDRH6D38NP-820NC	820	82 $\pm$ 30%	324m(240m)	0.70
CDRH6D38NP-101NC	101	100 $\pm$ 30%	358m(265m)	0.65

※1. Inductance measuring condition: at 100kHz.


※2. Rated current: The DC current at which the inductance decreases to 65% of it's nominal value or when  $\Delta t=30^\circ\text{C}$ , whichever is lower ( $T_a=20^\circ\text{C}$ ).

# SMD Power Inductor CDRH6D38



## Saturation Current & Temperature Rise Graph

— L (20°C) — L (105°C) —  $\Delta T$




# SMD Power Inductor CDRH6D38




## Saturation Current & Temperature Rise Graph

— L (20°C) — L (105°C) —  $\Delta T$




## Solder Reflow Condition

Heat Endurance



Temperature Chart



Please refer to the sales offices on our website - <http://www.sumida.com>

### Hong Kong

Tel.+852-2880-6781  
FAX.+852-2565-9600  
[sales@hk.sumida.com](mailto:sales@hk.sumida.com)

### Saitama(Japan)

Tel.+81-48-691-7300  
FAX.+81-48-691-7340  
[sales@jp.sumida.com](mailto:sales@jp.sumida.com)

### Chicago

Tel.+1-847-545-6700  
FAX. +1-847-545-6720  
[sales@us.sumida.com](mailto:sales@us.sumida.com)

### Shanghai

Tel.+86-21-5836-3299  
FAX.+86-21-5836-3266  
[shanghai.sales@cn.sumida.com](mailto:shanghai.sales@cn.sumida.com)

### Seoul

Tel.+82-2-6237-0777  
FAX.+82-2-6237-0778  
[sales@kr.sumida.com](mailto:sales@kr.sumida.com)

### Obernzell

Tel.+49-8591-937-0  
FAX. +49-8591-937-103  
[contact@eu.sumida.com](mailto:contact@eu.sumida.com)

### Shenzhen

Tel.+86-755-8291-0228  
FAX.+86-755-8291-0338  
[shenzhen.sales@cn.sumida.com](mailto:shenzhen.sales@cn.sumida.com)

### Singapore

Tel.+65-6296-3388  
FAX.+65-6841-4426  
[sales@sg.sumida.com](mailto:sales@sg.sumida.com)

### Neumarkt

Tel.+49-9181-4509-110  
FAX. +49-9181-4509-310  
[infocomp@eu.sumida.com](mailto:infocomp@eu.sumida.com)

### Taipei

Tel.+886-2-8751-2737  
FAX.+886-2-8751-2738  
[sales@tw.sumida.com](mailto:sales@tw.sumida.com)

### San Jose

Tel.+1-408-321-9660  
FAX.+1-408-321-9308  
[sales@us.sumida.com](mailto:sales@us.sumida.com)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View CDRH6D38NP-7R4NC on WIN SOURCE](#)
- ⊖ [Sumida America Components Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management