

ES3 SERIES: Board to Cable Type

Internal I/O for LED Lighting

Product Release



General Specifications

- 1.65mm mounting height
- Voltage rating: AC/DC 200V
- Current rating: 2A per contact
- Number of contacts: 2
- Operating temperature: -40°C to +105°C
- Applicable Wire Size : AWG #22 to 26
- PCB thickness: 1.6mm max

Target Application

- Indoor and outdoor LED lighting fixtures



Features

The ES3 series is a board to cable connector for power supply in various LED lighting devices.

- Mechanical lock is included for secure mating in high vibration and shock environments.
- The bottom mating design conceals most of the connector body under the LED board.
- The receptacle insulator is made of white LCP for heat and light resistance.
- Available in embossed tape packaging compatible with SMT mounting.

Enclosed you will find a Component Product Information guide and JACS for the series.

For further details and promotional samples, please contact Marketing Resources



Technology to Inspire Innovation

MB-11-56-10
October 2011

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View ES3B002WF1R1000](#) on WIN SOURCE

 [JAE Electronics](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management