



**THE DATASHEET OF  
GM5BW96382A**



# Selection Guide



Status: April 2010

## [High-luminosity white chip LEDs for lighting applications]



High brightness and luminous intensity, industry-leading performance levels, compact packages:  
Sharp's high-luminosity white chip LEDs bring clear benefits in a wide variety of lighting applications.  
The sizes and performance details of these LEDs are listed in the tables below.

### [Standard package]


#### NEW

Package type size	Type number	Outline dimensions (LxWxD) in mm	Colour range/wavelength [x, y]	Colour temperature [K]	CRI TYP. [Ra]	Luminous flux Iv [lm]	Luminous intensity Iv (typ.) [mcd]	V <sub>F</sub> [V]	I <sub>F</sub> [mA]	T <sub>opr</sub> [°C]
  3228 (PLCC 2)  	GM5SAE27POA	3.2x2.8x1.9	(0.458, 0.410) warm white	2,700	85	4.9	2,000	3.2	20	-30 to +85
	GM5SAE30POA	3.2x2.8x1.9	(0.434, 0.404) warm white	3,000	85	5.0	1,900	3.2	20	-30 to +85
	GM5SAE35POA	3.2x2.8x1.9	(0.407, 0.392) natural white	3,500	83	5.0	2,100	3.2	20	-30 to +85
	GM5SAE40POA	3.2x2.8x1.9	(0.382, 0.380) natural white	4,000	83	5.3	2,100	3.2	20	-30 to +85
	GM5SAE45POA	3.2x2.8x1.9	(0.361, 0.366) pure white	4,500	83	5.5	2,200	3.2	20	-30 to +85
	GM5SAE50POA	3.2x2.8x1.9	(0.345, 0.355) pure white	5,000	83	5.5	2,200	3.2	20	-30 to +85
	GM5SAE57POA	3.2x2.8x1.9	(0.329, 0.342) pure white	5,700	80	5.5	2,200	3.2	20	-30 to +85
	GM5SAE65POA	3.2x2.8x1.9	(0.312, 0.328) cool white	6,500	80	5.5	2,200	3.2	20	-30 to +85


According to energy star requirements concerning CRI and colour temperature

Package type size	Type number	Outline dimensions (LxWxD) in mm	Colour range/wavelength [x, y]	Colour temperature [K]	CRI TYP. [Ra]	Luminous flux Iv [lm]	Luminous intensity Iv (typ.) [mcd]	V <sub>F</sub> [V]	I <sub>F</sub> [mA]	T <sub>opr</sub> [°C]
  3228 (PLCC 2)  	GM5BN96385A	3.2x2.8x1.9	(0.34, 0.35) pure white	5,200	90	3.5	1,400	3.2	20	-30 to +100
	GM5BW96382A	3.2x2.8x1.9	(0.31, 0.31) cool white	6,800		5.0	2,000	3.2	20	-30 to +100
	GM5BW96385A	3.2x2.8x1.9	(0.34, 0.36) pure white	5,200		5.5	2,300	3.2	20	-30 to +100
	GM5BW96387A	3.2x2.8x1.9	(0.29, 0.28) cool white	10,000	60	5.0	2,000	3.2	20	-30 to +100


## [3-chip package]

Package type size	Type number	Outline dimensions (LxWxD) in mm	Colour range/ wavelength [x, y]	Colour temperature [K]	CRI (typ.) [Ra]	Luminous flux lv [lm]	Luminous intensity lv (typ.) [mcd]	V <sub>F</sub> [V]	I <sub>F</sub> [mA]	T <sub>opr</sub> [°C]
 3228 (PLCC 4)	GM5BW97330A	3.2x2.8x1.9 3 chip	(0.338, 0.356) pure white	5,300	62	17.0	6,400	3.2	20	-30 to +100
	GM5BW97331A	3.2x2.8x1.9 3 chip	(0.335, 0.344) pure white	5,300	62	17.0	6,400	3.2	20	-30 to +100
	GM5BW97332A	3.2x2.8x1.9 3 chip	(0.312, 0.311) cool white	6,700		15.0	5,800	3.2	20	-30 to +100
	GM5BW97333A	3.2x2.8x1.9 3 chip	(0.283, 0.262) ultra-cool white	11,500		12.0	5,100	3.2	20	-30 to +100


## [Thin package]


Package type size	Type number	Outline dimensions (LxWxD) in mm	Colour range/ wavelength [x, y]	Colour temperature [K]	Luminous intensity lv (typ.) [mcd]	V <sub>F</sub> [V]	I <sub>F</sub> [mA]	T <sub>opr</sub> [°C]
 3228	GM5BW93330A	3.2x2.8x0.9	(0.31, 0.31) cool white	6,850	5,400	3.4	25	-30 to +85


## [Ultra small package]

Package type size	Type number	Outline dimensions (LxWxD) in mm	Colour range/ wavelength [x, y]	Colour temperature [K]	Luminous intensity lv (typ.) [mcd]	V <sub>F</sub> [V]	I <sub>F</sub> [mA]	T <sub>opr</sub> [°C]
 1608	GM1BW20300A	1.6x0.8x0.2	(0,27, 0,24) warm white	2,200	50	2.9	5	-20 to +80

## [Side shoot package]

Package type size	Type number	Outline dimensions (LxWxD) in mm	Colour range/ wavelength [x, y]	Colour temperature [K]	Luminous intensity lv (typ.) [mcd]	V <sub>F</sub> [V]	I <sub>F</sub> [mA]	T <sub>opr</sub> [°C]
 2812	GM4BW853A0A	2.8x1.2x0.8	(0,30, 0,29) cool white	8,000	1,900	3.2	20	-30 to +85
	GM4BW853B0A	2.8x1.2x0.8	(0,30, 0,29) cool white	8,000	2,200	3.2	20	-30 to +85

Package type size	Type number	Outline dimensions (LxWxD) in mm	Colour range/ wavelength [x, y]	Colour temperature [K]	Luminous intensity lv (typ.) [mcd]	V <sub>F</sub> [V]	I <sub>F</sub> [mA]	T <sub>opr</sub> [°C]
	GM4BW653A0A	3.85x1.0x0.6	(0,30, 0,29) cool white	8,000	1,900	3.2	20	-30 to +85
	GM4BW653B0A	3.85x1.0x0.6	(0,30, 0,29) cool white	8,000	2,200	3.2	20	-30 to +85
	GM4BN653C0A	3.85x1.0x0.6	(0,29, 0,28) cool white Hi NTSC	9,400	1,700	3.2	20	-30 to +85

Package type size	Type number	Outline dimensions (LxWxD) in mm	Colour range/ wavelength [x, y]	Colour temperature [K]	Luminous intensity lv (typ.) [mcd]	V <sub>F</sub> [V]	I <sub>F</sub> [mA]	T <sub>opr</sub> [°C]
	GM4BW53340A	3.85x1.0x0.5	(0,30, 0,29) cool white	8,000	1,800	3.2	20	-30 to +85

Subject to alterations and modifications.  
For complete product information please refer to the product specifications.

# SHARP

Sharp Microelectronics Europe a division of Sharp Electronics (Europe) GmbH  
Sonninstraße 3 | 20097 Hamburg | Germany | Tel.: +49-18 05-07 35 07\* | Fax: +49-40-23 76 22 32 | www.sharpsme.com

\*Calls cost € 0.14 per minute from German landlines and no more than € 0.42 per minute from the German mobile network.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View GM5BW96382A](#) on WIN SOURCE
-  [Sharp Microelectronics](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management