THE DATASHEET OF

L206

www.win-source.net 0086-755-83957316

Fluke accessory selection guide

Find the right accessories to make your meter work for you

FLUKE®

		10/11/12/12B	110/111/112	114/115/116/117	20/70 Series	27	70/73 III	175/177	179	80 Series III/83V	87/89 IV	87V	187/189	45	39/41B	43B	90 Series	120 Series	190 Series	50S/50D	51/52/53/54 II	61/65	63/66/68	321/322	330 Series	705/707	712/713	714	715	716/717	718	725/726	741/743	744	787/789	T3/T5	1587	1577	561	574/576	FoodPro Plus	62
Current	i200			†	•	•	73	•	•	•	•	•	•	•			•	•	•																3		•	•				
	i200s	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•														•	•	•		•	•				
	i400			†	•	•	73	•	•	•	•	•	•	•																				3		•	•				
	i400s	4	4	4	4	4	4	4	4	4	4	4	4	4	•	•	•	•	•													4	4	4		4	4				
	80i-600A			†	•	•	73	•	•	•	•	•	•	•																				•		•	•				
	i1000s	4	4	4	4	4	4	4	4	4	4	4	4	4	•	•	•	•	•													4	4	4		4	4				
	i2000 flex	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•													•	•	•		•	•				
	i3000s flex	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•													•	•	•		•	•				
	i3000s	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•													3	3	•		•	•				
	i410	•		•	•	•	•	•	•	•	•	•	•	•		5	5	5	5													3	3	•		•	•				
	i1010	•		•	•	•	•	•	•	•	•	•	•	•		5	5	5	5													3	3	•		•	•				
	i30/i30s				•										•	•	•	•	•															•		•	•				
Temperature	80AK			116					•		•	•	•																							•	•				
	80BK			116					•		•	•	•																							•					
	All 80PK Probes	1	1	Δ	1*		1	1	2	1	2	2	2	1		1	1	1	1	•	•							•	1			•	•	•	1		2	2	•	•		
	80PJ-1/80PJ-9																			•	•							•				•	•	•								
	80PT-25																				•							•				•	•	•								
	80TK	•	•		•	•	•	•		•				•		•	•	•	•										•						•							
	80T-150U	•	•		•	•	•	•					•	•		•	•	•	•										•						•							
	80PJ-EXT																			•	•							•				•	•	•								
	80PK-EXT	1	1	2	1	1	1	1	2	1	2	2	2	1		1	1	1	1	•	•							•	1			•	•	•	1		2					
	80PT-EXT																				•							•				•	•	•								
	80CK-M	1	1	2	1	1	1	1	2	1	2	2	2	1		1	1	1	1	•	•							•	1			•	•	•	1		2					
	80CJM																			•	•							•				•	•	•								
	80PR-60																						66/68																			
Cases	C50	•	•	•																•		65																				
	C520																																			•						
	C550/C1600	The C550 and C1600 are large enough to hold accessories and multiple test tools (see page 70)																																								
	C12A	•	•	•																						•																
	C23	•	•	•																		•		•																		
	C25				•	•	•	•	•	•	•	•	•							•	•	•		•				•	•	•		•			•		•	•				
	C33																							•	•		•									•						
	C43									•	•	•	•		•	•		•														•	•	•								
	C90		•	•	•		•	•	•											•	•	•																				
	C125		•	•	•	•	•	•	•	•	•	•	•					•									•	•	•	•	•	•			•		•	•				
	C789														•	•		•													•		•	•	•								
	C20					•				•	•	•	•																			•			789							
	C101	•	•	•	•	•	•	•	•	•	•	•	•					•		•	•	•	•	•	•	•	•	•	•	•	•	•			•	•	•	•				
	C510							•	•											•	•																					
Holsters	C10	•*		•*																						•	•															
	C70Y						•													•																						
	H80M									•	•	•															•	•	•	•					787							
	H3																								•																	
	H5																																			•		•				
	H6																				•		•																•			•
	TPak		•	•			•	•	•	83V	•	•	•								•											•			789		•	•				
	C570																																							•		
Test Leads	Standard Test Lead Input	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U	U					U	U	U			U	U	U	U	U	U	U		U	U				
	TL220	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					•	•	•			•	•	•	•	•	•	•		•	•				
	TL223	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					•	•	•			•	•	•	•	•	•	•		•	•				
	TL225	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					•	•	•			•	•	•	•	•	•	•		•	•				
	TL238	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					•	•	•			•	•	•	•	•	•	•		•	•				
	TL80A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					•	•	•			•	•	•	•	•	•	•		•	•				
	TL81A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					•	•	•			•	•	•	•	•	•	•		•	•				
	TL71	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					•	•	•			•	•	•	•	•	•	•		•	•				
	TL76	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•					•	•	•			•	•	•	•	•	•	•		•	•				
Specialty	FlukeView Forms Software										•	•	•	•							•**														789							
	PV350 (pressure)	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•							•			•				•	•	•		•	•				
	FOM (fiber optic)	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•							•			•				•	•	•							
	CO-210	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•							•			•				•	•	•							
	80K-6, 80K-15, 80K-40	dc	dc	dc	•	•	•	•	•	•	•	•	•	dc																					•							
	AN5 Cable																																							•		
	FP Probe																																								•	

(1) Requires 80TK (2) Requires 80AK (3) Limited low level ac capability – see page 40 (4) Requires PM9081/001 Adapter (5) Requires PM9082/001 adapter †115, 117 only Δ116 only – requires 80AK

U A universal accessory. Works with most brands of meters. For detailed Current Clamp specifications see pages 58 and 59. *included with the 12B and 16 **53, 54 only

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View L206 on WIN SOURCE
- Fluke Electronics Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management