

WRIST STRAP:

- A. Stamped 4mm (nominal) stud. To fit 4mm (nominal) spring loaded medical snap socket.
- B. Easy to open plastic clasp secures elastic material in place, and allows the user to easily adjust the wrist band size. Maintains electrical continuity even when open.
- C. Non-allergenic stainless steel base plate, provides excellent skin contact, for superior grounding.
- D. Insulating cap, thermoplastic.
- E. Soft elastic band.

Band Circumference:
 Min: 3" 76mm
 Max: 15" 381mm
 Width: 0.75" 19mm

GROUND CORD:

- F. Barrel type banana plug. Fits industry standard banana jack 4.22mm (nominal).
- G. Metallized, high flex tinsel, black jacket.
- H. Alligator clip included.
- I. Spring loaded snap socket.
- J. One megohm, resistor, molded within snap assembly, limits current for operator safety.

The color of the band material may vary.

Item	Description
23311	Wrist Strap, Economy, Adjustable, 12 ft Cord, 4mm
23312	Wrist Strap, Economy, Adjustable, 6 ft Cord, 4mm

Specifications and procedures subject to change without notice

Wrist Strap, Adjustable, Economy

ESD SYSTEMS.com


ESD SYSTEMS.COM
 432 NORTHBORO ROAD CENTRAL
 MARLBORO, MA 01752 USA
 TEL. (508) 485-7390 FAX (508) 480-0257

DRAWING NUMBER
 TD-23311

DATE
 May
 2010

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 23312 on WIN SOURCE](#)

 [Desco Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management