



**THE DATASHEET OF  
BZD27C100P-M3-08**



## Zener Diodes with Surge Current Specification



### FEATURES

- Silicon planar Zener diodes
- Low profile surface-mount package
- Zener and surge current specification
- Low leakage current
- Excellent stability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Meets JESD 201 class 2 whisker test
- ESD capability according to AEC-Q101: human body model: > 8 kV machine model: > 800 V
- Wave and reflow solderable
- AEC-Q101 qualified
- Base P/N-M3 - halogen-free, RoHS-compliant, and commercial grade
- Base P/N-HM3 - halogen-free, RoHS-compliant, and automotive grade (available on request)
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



PRIMARY CHARACTERISTICS		
PARAMETER	VALUE	UNIT
V <sub>Z</sub> range nom.	3.6 to 200	V
Test current I <sub>ZT</sub>	5 to 100	mA
V <sub>BR</sub>	7 to 188	V
V <sub>WM</sub>	6.2 to 160	V
P <sub>PPM</sub>	150	W
T <sub>J</sub> max.	175	°C
V <sub>Z</sub> specification	Pulse current	
Int. construction	Single	
Polarity	Uni-directional	

ORDERING INFORMATION			
DEVICE NAME	ORDERING CODE	TAPED UNITS PER REEL	MINIMUM ORDER QUANTITY
BZD27-M Series	BZD27C3V6P-M3-08 to BZD27C200P-M3-08	3000 per 7" reel (8mm tape)	30 000/box
	BZD27C3V6P-M3-18 to BZD27C200P-M3-18	10 000 per 13" reel (8 mm tape)	50 000/box

PACKAGE					
PACKAGE NAME	WEIGHT	MOLDING COMPOUND FLAMMABILITY RATING	MOISTURE SENSITIVITY LEVEL	WHISKER TEST ACC. JESD 201	SOLDERING CONDITIONS
DO-219AB (SMF)	15 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	Class 2	Peak temperature max. 260 °C

ABSOLUTE MAXIMUM RATINGS (T <sub>amb</sub> = 25 °C, unless otherwise specified)					
PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT	
Power dissipation	T <sub>L</sub> = 105 °C	P <sub>tot</sub>	2300	mW	
	T <sub>A</sub> = 30 °C <sup>(1)</sup>	P <sub>tot</sub>	800	mW	
Non repetitive peak surge power dissipation <sup>(2)</sup>	100 μs square pulse	P <sub>ZSM</sub>	300	W	
	10/1000 μs waveform	P <sub>RSM</sub>	150	W	
Junction to lead		R <sub>thJL</sub>	30	K/W	
Junction to ambient air	Mounted on epoxy-glass PCB with 3 mm x 3 mm Cu pads (≥ 40 μm thick)	R <sub>thJA</sub>	180	K/W	
Junction temperature		T <sub>J</sub>	175	°C	
Storage temperature range		T <sub>stg</sub>	-65 to +175	°C	
Operating temperature range		T <sub>op</sub>	-65 to +175	°C	

### Notes

- <sup>(1)</sup> Mounted on epoxy-glass PCB with 3 mm x 3 mm Cu pads (≥ 40 μm thick)  
<sup>(2)</sup> T<sub>J</sub> = 25 °C prior to surge



<b>ELECTRICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)											
PART NUMBER	MARKING CODE	ZENER VOLTAGE RANGE <sup>(1)</sup>			TEST CURRENT	REVERSE CURRENT		DYNAMIC RESISTANCE		TEMPERATURE COEFFICIENT	
		V <sub>Z</sub> at I <sub>ZT1</sub>			I <sub>ZT1</sub>	I <sub>R</sub> at V <sub>R</sub>		Z <sub>Z</sub> at I <sub>ZT1</sub>		$\alpha_{VZ}$ at I <sub>ZT1</sub>	
		V			mA	$\mu\text{A}$	V	$\Omega$		%/ $^{\circ}\text{C}$	
		MIN.	NOM.	MAX.		MAX.		TYP.	MAX.	MIN.	MAX.
BZD27C3V6P-M	N0	3.4	3.6	3.8	100	100	1	4	8	-0.14	-0.04
BZD27C3V9P-M	N1	3.7	3.9	4.1	100	50	1	4	8	-0.14	-0.04
BZD27C4V3P-M	N2	4	4.3	4.6	100	25	1	4	7	-0.12	-0.02
BZD27C4V7P-M	N3	4.4	4.7	5	100	10	1	3	7	-0.1	0
BZD27C5V1P-M	N4	4.8	5.1	5.4	100	5	1	3	6	-0.08	0.02
BZD27C5V6P-M	N5	5.2	5.6	6	100	10	2	2	4	-0.04	0.04
BZD27C6V2P-M	N6	5.8	6.2	6.6	100	5	2	2	3	-0.01	0.06
BZD27C6V8P-M	N7	6.4	6.8	7.2	100	10	3	1	3	0	0.07
BZD27C7V5P-M	N8	7	7.5	7.9	100	50	3	1	2	0	0.07
BZD27C8V2P-M	N9	7.7	8.2	8.7	100	10	3	1	2	0.03	0.08
BZD27C9V1P-M	O0	8.5	9.1	9.6	50	10	5	2	4	0.03	0.08
BZD27C10P-M	O1	9.4	10	10.6	50	7	7.5	2	4	0.05	0.09
BZD27C11P-M	O2	10.4	11	11.6	50	4	8.2	4	7	0.05	0.1
BZD27C12P-M	O3	11.4	12	12.7	50	3	9.1	4	7	0.05	0.1
BZD27C13P-M	O4	12.4	13	14.1	50	2	10	5	10	0.05	0.1
BZD27C15P-M	O5	13.8	15	15.6	50	1	11	5	10	0.05	0.1
BZD27C16P-M	O6	15.3	16	17.1	25	1	12	6	15	0.06	0.11
BZD27C18P-M	O7	16.8	18	19.1	25	1	13	6	15	0.06	0.11
BZD27C20P-M	O8	18.8	20	21.2	25	1	15	6	15	0.06	0.11
BZD27C22P-M	O9	20.8	22	23.3	25	1	16	6	15	0.06	0.11
BZD27C24P-M	P0	22.8	24	25.6	25	1	18	7	15	0.06	0.11
BZD27C27P-M	P1	25.1	27	28.9	25	1	20	7	15	0.06	0.11
BZD27C30P-M	P2	28	30	32	25	1	22	8	15	0.06	0.11
BZD27C33P-M	P3	31	33	35	25	1	24	8	15	0.06	0.11
BZD27C36P-M	P4	34	36	38	10	1	27	21	40	0.06	0.11
BZD27C39P-M	P5	37	39	41	10	1	30	21	40	0.06	0.11
BZD27C43P-M	P6	40	43	46	10	1	33	24	45	0.07	0.12
BZD27C47P-M	P7	44	47	50	10	1	36	24	45	0.07	0.12
BZD27C51P-M	P8	48	51	54	10	1	39	25	60	0.07	0.12
BZD27C56P-M	P9	52	56	60	10	1	43	25	60	0.07	0.12
BZD27C62P-M	Q0	58	62	66	10	1	47	25	80	0.08	0.13
BZD27C68P-M	Q1	64	68	72	10	1	51	25	80	0.08	0.13
BZD27C75P-M	Q2	70	75	79	10	1	56	30	100	0.08	0.13
BZD27C82P-M	Q3	77	82	87	10	1	62	30	100	0.08	0.13
BZD27C91P-M	Q4	85	91	96	5	1	68	60	200	0.08	0.13
BZD27C100P-M	Q5	94	100	106	5	1	75	60	200	0.09	0.13
BZD27C110P-M	Q6	104	110	116	5	1	82	80	250	0.09	0.13
BZD27C120P-M	Q7	114	120	127	5	1	91	80	250	0.09	0.13
BZD27C130P-M	Q8	124	130	141	5	1	100	110	300	0.09	0.13
BZD27C150P-M	Q9	138	150	156	5	1	110	130	300	0.09	0.13
BZD27C160P-M	R0	153	160	171	5	1	120	150	350	0.09	0.13
BZD27C180P-M	R1	168	180	191	5	1	130	180	400	0.09	0.13
BZD27C200P-M	R2	188	200	212	5	1	150	200	500	0.09	0.13

**Notes**

- Electrical characteristics when used as regulator diodes
- Maximum  $V_F = 1.2\text{ V}$ , at  $I_F = 0.2\text{ A}$
- (1) Pulse test:  $t_p \leq 5\text{ ms}$



<b>ELECTRICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)											
PART NUMBER	MARKING CODE	ZENER VOLTAGE RANGE			TEST CURRENT	REVERSE CURRENT		CLAMPING VOLTAGE		TEMPERATURE COEFFICIENT	
		$V_Z$ at $I_{ZT1}$			$I_{ZT1}$	$I_R$ at $V_R$		$V_C$ at $I_{RSM}^{(1)}$		$\alpha_{VZ}$ at $I_{ZT1}$	
		V			mA	$\mu\text{A}$	V	V	A	%/ $^{\circ}\text{C}$	
		MIN.	NOM.	MAX.		MAX.		MAX.		MIN.	MAX.
BZD27C7V5P-M	N8	7	7.5	7.9	100	1500	6.2	11.3	13.3	0	0.07
BZD27C8V2P-M	N9	7.7	8.2	8.7	100	1200	6.8	12.3	12.2	0.03	0.08
BZD27C9V1P-M	O0	8.5	9.1	9.6	50	100	7.5	13.3	11.3	0.03	0.08
BZD27C10P-M	O1	9.4	10	10.6	50	20	8.2	14.8	10.1	0.05	0.09
BZD27C11P-M	O2	10.4	11	11.6	50	5	9.1	15.7	9.6	0.05	0.1
BZD27C12P-M	O3	11.4	12	12.7	50	5	10	17	8.8	0.05	0.1
BZD27C13P-M	O4	12.4	13	14.1	50	5	11	18.9	7.9	0.05	0.1
BZD27C15P-M	O5	13.8	15	15.6	50	5	12	20.9	7.2	0.05	0.1
BZD27C16P-M	O6	15.3	16	17.1	25	5	13	22.9	6.6	0.06	0.11
BZD27C18P-M	O7	16.8	18	19.1	25	5	15	25.6	5.9	0.06	0.11
BZD27C20P-M	O8	18.8	20	21.2	25	5	16	28.4	5.3	0.06	0.11
BZD27C22P-M	O9	20.8	22	23.3	25	5	18	31	4.8	0.06	0.11
BZD27C24P-M	P0	22.8	24	25.6	25	5	20	33.8	4.4	0.06	0.11
BZD27C27P-M	P1	25.1	27	28.9	25	5	22	38.1	3.9	0.06	0.11
BZD27C30P-M	P2	28	30	32	25	5	24	42.2	3.6	0.06	0.11
BZD27C33P-M	P3	31	33	35	25	5	27	46.2	3.2	0.06	0.11
BZD27C36P-M	P4	34	36	38	10	5	30	50.1	3	0.06	0.11
BZD27C39P-M	P5	37	39	41	10	5	33	54.1	2.8	0.06	0.11
BZD27C43P-M	P6	40	43	46	10	5	36	60.7	2.5	0.07	0.12
BZD27C47P-M	P7	44	47	50	10	5	39	65.5	2.3	0.07	0.12
BZD27C51P-M	P8	48	51	54	10	5	43	70.8	2.1	0.07	0.12
BZD27C56P-M	P9	52	56	60	10	5	47	78.6	1.9	0.07	0.12
BZD27C62P-M	Q0	58	62	66	10	5	51	86.5	1.7	0.08	0.13
BZD27C68P-M	Q1	64	68	72	10	5	56	94.4	1.6	0.08	0.13
BZD27C75P-M	Q2	70	75	79	10	5	62	103.5	1.5	0.08	0.13
BZD27C82P-M	Q3	77	82	87	10	5	68	114	1.3	0.08	0.13
BZD27C91P-M	Q4	85	91	96	5	5	75	126	1.2	0.09	0.13
BZD27C100P-M	Q5	94	100	106	5	5	82	139	1.1	0.09	0.13
BZD27C110P-M	Q6	104	110	116	5	5	91	150	1	0.09	0.13
BZD27C120P-M	Q7	114	120	127	5	5	100	167	0.9	0.09	0.13
BZD27C130P-M	Q8	124	130	141	5	5	110	185	0.81	0.09	0.13
BZD27C150P-M	Q9	138	150	156	5	5	120	205	0.73	0.09	0.13
BZD27C160P-M	R0	153	160	171	5	5	130	224	0.67	0.09	0.13
BZD27C180P-M	R1	168	180	191	5	5	150	252	0.6	0.09	0.13
BZD27C200P-M	R2	188	200	212	5	5	160	278	0.54	0.09	0.13

**Notes**

- Electrical characteristics when used as protection diodes
- (1) Non-repetitive peak reverse current in accordance with "IEC 60-1, section 8" (10/1000  $\mu\text{s}$  pulse); see fig. 4

**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - Forward Current vs. Forward Voltage




Fig. 4 - Non-Repetitive Peak Reverse Current Pulse Definition




Fig. 2 - Typ. Diode Capacitance vs. Reverse Voltage



Fig. 3 - Power Dissipation vs. Ambient Temperature



**PACKAGE DIMENSIONS** in millimeters (inches): **DO219-AB (SMF)**



Foot print recommendation:



Created - Date: 15. February 2005  
Rev. 3 - Date: 13. March 2007  
Document no.:S8-V-3915.01-001 (4)  
17247



**BLISTERTAPE DIMENSIONS FOR SMF** in millimeters



Mat:	A0	B0	K0	W	T	P0	P2	P1	D0	D1	E	F
PS	1.9	4.0	1.5	8.0	0.235	4.0	2.0	4.0	1.5	1	1.75	3.5

Document-No.: S8-V-3717.02-001 (3)  
18513



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View BZD27C100P-M3-08 on WIN SOURCE](#)

 [Vishay Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management