



**THE DATASHEET OF
DF11-12DS-2C**



Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△	6	RE-H-03802	T.A	C.H	'00.07.12	△			
△						△			

APPLICABLE STANDARD	
OPERATING TEMPERATURE RANGE	-30 °C TO 85 °C(NOTE 1)
STORAGE TEMPERATURE RANGE	-10°C TO 60 °C △
RATING VOLTAGE	250V AC △ UL·CSA
30V AC	△
APPLICABLE CONTACT	DF11-22SC * DF11-2428SC *
RATING CURRENT	2 A
2 A	△
APPLICABLE CABLE	UL1061,1007 AWG22~28

SPECIFICATIONS			
ITEM	TEST METHOD	REQUIREMENTS	QT AT
CONSTRUCTION			
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	× ×
MARKING	CONFIRMED VISUALLY.		× ×
ELECTRIC CHARACTERISTICS			
INSULATION RESISTANCE	500V DC.	1000 MΩ MIN.	× -
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASH OVER OR BREAKDOWN.	× -
MECHANICAL CHARACTERISTICS			
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	× -
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75mm AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs.	× -
SHOCK △	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 3 DIRECTION.	② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	× -
ENVIRONMENTAL CHARACTERISTICS			
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→ 5 TO 35→85→ 5 TO 35 °C TIME 30→ 5 TO 15→30→ 5 TO 15min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000M Ω MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	× -
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 500M Ω MIN. △ ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	× -

REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	T.OMA	T.OMA	K.SATO	M.YAMAMOTO	
Unless otherwise specified, refer to MIL-STD-1344.	'90.5.10	'90.5.10	'90.5.10	'90.5.10	

Note QT: Qualification Test AT: Assurance Test ×:Applicable Test

HS HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO.
		DF11-*DS-2C
CODE NO.(OLD)	DRAWING NO.	PEART NO
CL	ELC4-162389-01	CL543-

TO



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View DF11-12DS-2C on WIN SOURCE](#)
-  [Hirose Electric Co Ltd Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management