



**THE DATASHEET OF
IHW30N160R5XKSA1**



Reverse-Conducting IGBT with monolithic body diode

Features


- $V_{CE} = 1600\text{ V}$
- $I_C = 30\text{ A}$
- Powerful monolithic body diode with low forward voltage
- Very tight parameter distribution
- High ruggedness, temperature stable behavior
- Low V_{CEsat}
- Easy parallel switching capability due to positive temperature coefficient in V_{CEsat}
- Low EMI
- Pb-free lead plating; RoHS compliant; halogen free (according IEC 61249-2-21)
- Complete product spectrum and PSpice Models: <http://www.infineon.com/igbt/>

Potential applications


- Induction cooking
- Microwave ovens

Product validation

- Qualified for industrial applications according to the relevant tests of JEDEC47/20/22



Description



Type	Package	Marking
IHW30N160R5	PG-TO247-3	H30SR5

Table of contents

	Description	1
	Features	1
	Potential applications	1
	Product validation	1
	Table of contents	2
1	Package	3
2	IGBT	3
3	Diode	5
4	Characteristics diagrams	6
5	Package outlines	12
6	Testing conditions	13
	Revision history	14
	Disclaimer	15

1 Package

Table 1 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Internal emitter inductance measured 5 mm (0.197 in) from case	L_E			13.0		nH
Storage temperature	T_{stg}		-55		175	°C
Soldering temperature		wave soldering 1.6 mm (0.063 in.) from case for 10 s			260	°C
Mounting torque	M	M3 screw Maximum of mounting process: 3			0.6	Nm
Thermal resistance, junction-ambient	$R_{th(j-a)}$				40	K/W

2 IGBT

Table 2 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Collector-emitter voltage	V_{CE}	$T_{vj} \geq 25\text{ °C}$	1600	V	
DC collector current, limited by T_{vjmax}	I_C		$T_c = 25\text{ °C}$	60	A
			$T_c = 100\text{ °C}$	39	
Pulsed collector current, t_p limited by T_{vjmax}	I_{Cpulse}		90	A	
Non repetitive peak collector current ¹⁾	I_{CSM}		200	A	
Turn-off safe operating area		$V_{CE} = 1600\text{ V}, t_p = 1\text{ }\mu\text{s}, T_{vj} \leq 175\text{ °C}$	90	A	
Gate-emitter voltage	V_{GE}		± 20	V	
Transient gate-emitter voltage	V_{GE}	$t_p \leq 10\text{ }\mu\text{s}, D < 0.01$	± 25	V	
Power dissipation	P_{tot}		$T_c = 25\text{ °C}$	263	W
			$T_c = 100\text{ °C}$	131.5	

1) capacitor charging saturation current limited by $T_{vjmax} < 175\text{ °C}$ and $t_p < 3\text{ }\mu\text{s}$

Table 3 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter breakdown voltage	V_{BRCES}	$I_C = 0.5\text{ mA}, V_{GE} = 0\text{ V}$	1600			V

(table continues...)

Table 3 (continued) Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Collector-emitter saturation voltage	V_{CEsat}	$I_C = 30\text{ A}, V_{GE} = 15\text{ V}$	$T_{vj} = 25\text{ °C}$		1.85	2.15	V
			$T_{vj} = 125\text{ °C}$		2.2		
			$T_{vj} = 175\text{ °C}$		2.4		
Gate-emitter threshold voltage	V_{GETh}	$I_C = 0.75\text{ mA}, V_{CE} = V_{GE}$		4.5	5.1	5.8	V
Zero gate-voltage collector current	I_{CES}	$V_{CE} = 1600\text{ V}, V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ °C}$			100	μA
			$T_{vj} = 175\text{ °C}$		800		
Gate-emitter leakage current	I_{GES}	$V_{CE} = 0\text{ V}, V_{GE} = 20\text{ V}$				100	nA
Transconductance	g_{fs}	$I_C = 30\text{ A}, V_{CE} = 20\text{ V}$			20.5		S
Input capacitance	C_{ies}	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 100\text{ kHz}$			1500		pF
Output capacitance	C_{oes}	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 100\text{ kHz}$			42		pF
Reverse transfer capacitance	C_{res}	$V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 100\text{ kHz}$			38		pF
Gate charge	Q_G	$I_C = 30\text{ A}, V_{GE} = 15\text{ V}, V_{CC} = 1280\text{ V}$			205		nC
Turn-off delay time	t_{doff}	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{Gon} = 10\ \Omega, R_{Goff} = 10\ \Omega, L_\sigma = 175\text{ nH}, C_\sigma = 40\text{ pF}$	$T_{vj} = 25\text{ °C}, I_C = 30\text{ A}$		290		ns
			$T_{vj} = 175\text{ °C}, I_C = 30\text{ A}$		330		
Fall time (inductive load)	t_f	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{Gon} = 10\ \Omega, R_{Goff} = 10\ \Omega, L_\sigma = 175\text{ nH}, C_\sigma = 40\text{ pF}$	$T_{vj} = 25\text{ °C}, I_C = 30\text{ A}$		47		ns
			$T_{vj} = 175\text{ °C}, I_C = 30\text{ A}$		81		
Turn-off energy	E_{off}	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{Gon} = 10\ \Omega, R_{Goff} = 10\ \Omega, L_\sigma = 175\text{ nH}, C_\sigma = 40\text{ pF}$	$T_{vj} = 25\text{ °C}, I_C = 30\text{ A}$		2		mJ
			$T_{vj} = 175\text{ °C}, I_C = 30\text{ A}$		3		
Total switching energy	E_{ts}	$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_{Gon} = 10\ \Omega, R_{Goff} = 10\ \Omega, L_\sigma = 175\text{ nH}, C_\sigma = 40\text{ pF}$	$I_C = 30\text{ A}$		0.35		mJ
			$I_C = 30\text{ A}$		1.27		
Soft turn-off energy	E_{off}	$V_{CC} = 600\text{ V}, dv/dt = 300\text{ V}/\mu\text{s}$	$T_{vj} = 25\text{ °C}$		0.35		mJ
			$T_{vj} = 175\text{ °C}$		1.27		
IGBT thermal resistance, junction to case	R_{thjc}					0.57	K/W
Operating junction temperature	T_{vj}			-40		175	$^{\circ}\text{C}$

Note: Electrical Characteristic, at $T_{vj} = 25^{\circ}\text{C}$, unless otherwise specified.

3 Diode

Table 4 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit	
Repetitive peak reverse voltage	V_{RRM}	$T_{vj} \geq 25^{\circ}\text{C}$	1600	V	
Diode forward current, limited by T_{vjmax}	I_F		$T_c = 25^{\circ}\text{C}$	55	A
			$T_c = 100^{\circ}\text{C}$	36	
Diode pulsed current, limited by T_{vjmax}	I_{Fpulse}		90	A	

Table 5 Characteristic values


Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Diode forward voltage	V_F	$I_F = 30\text{ A}$	$T_{vj} = 25^{\circ}\text{C}$		2	2.3	V
			$T_{vj} = 125^{\circ}\text{C}$		2.4		
			$T_{vj} = 175^{\circ}\text{C}$		2.6		
Diode thermal resistance, junction to case	R_{thjc}				0.57	K/W	
Operating junction temperature	T_{vj}		-40		175	$^{\circ}\text{C}$	

Note: For optimum lifetime and reliability, Infineon recommends operating conditions that do not exceed 80% of the maximum ratings stated in this datasheet.

4 Characteristics diagrams


Reverse bias safe operating area

$I_C = f(V_{CE})$
 $D = 0, T_{vj} \leq 175\text{ °C}, V_{GE} = 15\text{ V}, T_c = 25\text{ °C}$




Power dissipation as a function of case temperature

$P_{tot} = f(T_c)$
 $T_{vj} \leq 175\text{ °C}$




Collector current as a function of heatsink temperature

$I_C = f(T_c)$
 $T_{vj} \leq 175\text{ °C}, V_{GE} \geq 15\text{ V}$




Typical output characteristic

$I_C = f(V_{CE})$
 $T_{vj} = 25\text{ °C}$




Typical output characteristic

$I_C = f(V_{CE})$
 $T_{vj} = 150\text{ °C}$




Typical transfer characteristic

$I_C = f(V_{GE})$
 $V_{CE} = 20\text{ V}$




Typical collector-emitter saturation voltage as a function of junction temperature

$V_{CEsat} = f(T_{vj})$
 $V_{GE} = 15\text{ V}$



Typical switching times as a function of collector current

$t = f(I_C)$
 $V_{CC} = 600\text{ V}, T_{vj} = 175\text{ °C}, V_{GE} = 0/15\text{ V}, R_G = 10\text{ }\Omega$




4 Characteristics diagrams

Typical switching times as a function of gate resistor

$t = f(R_G)$


$I_C = 30 \text{ A}, V_{CC} = 600 \text{ V}, T_{vj} = 175 \text{ }^\circ\text{C}, V_{GE} = 0/15 \text{ V}$



Typical switching times as a function of junction temperature

$t = f(T_{vj})$


$I_C = 30 \text{ A}, V_{CC} = 600 \text{ V}, V_{GE} = 0/15 \text{ V}, R_G = 10 \text{ } \Omega$



Gate-emitter threshold voltage as a function of junction temperature

$V_{GEth} = f(T_{vj})$


$I_C = 0.75 \text{ mA}$



Typical switching energy losses as a function of collector current

$E = f(I_C)$

$V_{CC} = 600 \text{ V}, T_{vj} = 175 \text{ }^\circ\text{C}, V_{GE} = 0/15 \text{ V}, R_G = 10 \text{ } \Omega$




4 Characteristics diagrams

Typical switching energy losses as a function of gate resistor

$E = f(R_G)$


$I_C = 30\text{ A}, V_{CC} = 600\text{ V}, T_{vj} = 175\text{ }^\circ\text{C}, V_{GE} = 0/15\text{ V}$



Typical switching energy losses as a function of junction temperature

$E = f(T_{vj})$


$I_C = 30\text{ A}, V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_G = 10\text{ }\Omega$



Typical switching energy losses as a function of collector emitter voltage

$E = f(V_{CE})$


$I_C = 30\text{ A}, T_{vj} = 175\text{ }^\circ\text{C}, V_{GE} = 0/15\text{ V}, R_G = 10\text{ }\Omega$



Typical resonant switching energy losses as a function of collector current

$E = f(I_C)$


$V_{CC} = 600\text{ V}, V_{GE} = 0/15\text{ V}, R_G = 10\text{ }\Omega$



4 Characteristics diagrams


Typical gate charge

$V_{GE} = f(Q_{GE})$
 $I_C = 30\text{ A}$




Typical capacitance as a function of collector-emitter voltage

$C = f(V_{CE})$
 $f = 1000\text{ kHz}, V_{GE} = 0\text{ V}$




IGBT transient thermal impedance as a function of pulse width

$Z_{th} = f(t_p)$
 $D = t_p/T$




Diode transient thermal impedance as a function of pulse width

$Z_{th} = f(t_p)$
 $D = t_p/T$




Typical diode forward current as a function of forward voltage

$$I_F = f(V_F)$$



Typical diode forward voltage as a function of junction temperature

$$V_F = f(T_{vj})$$



5 Package outlines




Figure 1

6 Testing conditions




Figure 2

Revision history

Document revision	Date of release	Description of changes
V2.1	2018-08-28	Final Data Sheet
V2.2	2019-09-19	additional parameter in maximum ratings table: non repetitive peak collector current
n/a	2020-11-30	Datasheet migrated to a new system with a new layout and new revision number schema: target or preliminary datasheet = 0.xy; final datasheet = 1.xy
1.10	2022-04-05	“Forward bias safe operating area” diagram renamed to “Reverse bias safe operating area” T_{vj} condition in table “Maximum rated values ” of IGBT at “Turn off safe operating area” changed to 175°C

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2022-04-05

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2022 Infineon Technologies AG

All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference

IFX-AAL233-003

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.



WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View IHW30N160R5XKSA1 on WIN SOURCE](#)
-  [Infineon Technologies Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management