



**THE DATASHEET OF  
JAN2N2326S**



## SILICON CONTROLLED RECTIFIER

Qualified per MIL-PRF-19500/276

### Devices

2N2323	2N2324	2N2326	2N2328	
2N2323S	2N2324S	2N2326S	2N2328S	2N2329
2N2323A	2N2324A	2N2326A	2N2328A	2N2329S
2N2323AS	2N2324AS	2N2326AS	2N2328AS	


Qualified  
Level

JAN  
JANTX  
JANTXV

### MAXIMUM RATINGS

Ratings	Sym	2N2323,S/ 2N2323A,S	2N2324,S/ 2N2324A,S	2N2326,S/ 2N2326A,S	2N2328,S/ 2N2328A,S	2N2329,S	Unit	
Reverse Voltage	V <sub>RM</sub>	50	100	200	300	400	Vdc	
Working Peak Reverse Voltage	V <sub>RM</sub>	75	150	300	400	500	Vpk	
Forward Blocking Voltage	V <sub>F BXM</sub>	50 <sup>(3/4)</sup>	100 <sup>(3/4)</sup>	200 <sup>(3/4)</sup>	300 <sup>(3/4)</sup>	400 <sup>(3)</sup>	Vpk	
Average Forward Current <sup>(1)</sup>	I <sub>O</sub>	0.22						Adc
Forward Current Surge Peak <sup>(2)</sup>	I <sub>FSM</sub>	15						Adc
Cathode-Gate Current	V <sub>KGM</sub>	6						Vpk
Operating Temperature	T <sub>OP</sub>	-65 to +125						°C
Storage Junction Temp	T <sub>STG</sub>	-65 to +150						°C

- 1) This average forward current is for an ambient temperature of 80°C and 180 electrical degrees of conduction.
- 2) Surge current is non-recurrent. The rate of rise of peak surge current shall not exceed 40 A during the first 5 μs after switching from the 'off' (blocking) to the 'on' (conducting) state. This is measured from the point where the thyristor voltage has decayed to 90% of its initial blocking value.
- 3) Gate connected to cathode through 1,000 ohm resistor.
- 4) Gate connected to cathode through 2,000 ohm resistor.



\*See appendix A  
for package outline

### ELECTRICAL CHARACTERISTICS

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

#### SUBGROUP 2 TESTING

Reverse Blocking Current				
R <sub>2</sub> = 1 kμ	2N2323 thru 2N2329 2N2323S thru 2N2329S			
R <sub>2</sub> = 2 kμ	2N2323A thru 2N2328A 2N2323AS thru 2N2328AS			
V <sub>R</sub> = 50 Vdc	2N2323, S, A, AS		10	μAdc
V <sub>R</sub> = 100 Vdc	2N2324, S, A, AS			
V <sub>R</sub> = 200 Vdc	2N2326, S, A, AS			
V <sub>R</sub> = 300 Vdc	2N2328, S, A, AS			
V <sub>R</sub> = 400 Vdc	2N2329, S,			



## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View JAN2N2326S on WIN SOURCE](#)
- ⊖ [Microchip Technology Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management