



**THE DATASHEET OF**  
**14004-3**



## Power Terminal Blocks: Barrier & Dead Front

### Series 14002

#### Specifications

**Description:** Barrier terminal block.

**Poles:** 2- to 6-poles.

**Wire Range:** 2 – 14 AWG Cu/8 AWG Al.

#### Ratings:

Volts: — 600Vac/dc

Amps: — 115A

SCCR:— 10kA per  
UL 508A table SB4.1

**Agency Information:** CE, Guide XCFR2, UL E62622; CSA LR15364.

**Torque Ratings\*:** 2-3, 50 lb-in; 4-6, 45 lb-in; 8, 40 lb-in; 10-14, 35 lb-in.

\*Consult factory for torque ratings for CP and Q options.

**Marking:** Marking strip optional, consult factory.

#### Options For Load Side Connector

CP: Sems pressure plate, rated 60A, 600V

Q: Quick-Connect, rated 50A, 600V

To order options, enter letter code in front of Catalog Number: i.e., CP14002-2.



#### Catalog Numbers

Catalog Numbers	Poles	Catalog Numbers	Poles
14002-2	2	14002-5	5
14002-3	3	14002-6	6
14002-4	4		

### Series 14004

#### Specifications

**Description:** Dead front terminal block.

**Poles:** 2 to 12 poles.

**Wire Range:**  
4 – 14 AWG Cu/8 AWG Al.

#### Ratings:

Volts: — 600Vac/dc

Amps: — 90A

SCCR: — 10kA per UL 508A table SB4.1

**Agency Information:** CE, Guide XCFR2, UL E62622; CSA LR15364.

**Marking:** Marking strip optional, consult factory.




#### Catalog Numbers

Catalog Numbers	Poles	Catalog Numbers	Poles
14004-2	2	14004-8	8
14004-3	3	14004-9	9
14004-4	4	14004-10	10
14004-5	5	14004-11	11
14004-6	6	14004-12	12
14004-7	7		

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 14004-3 on WIN SOURCE](#)

 [Eaton Bussmann Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management