



**THE DATASHEET OF
5500UG 005C1000**





Product: [5500UG](#)

Security & Sound, #22-2c, BC, CM

Product Description

Security & Sound Cable, Rated-CM, 2-22 AWG stranded bare copper conductors with polyolefin insulation, PVC jacket

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | Security System, Alarm, Intercom/PA, Single Line Telephone |
|------------------------|--|

Construction Details

Conductor

| Element | No. of Elements | Size | Stranding | Material |
|---------|-----------------|--------|-----------|------------------|
| Pair(s) | 1 | 22 AWG | 7x30 | BC - Bare Copper |

Insulation

| Element | Material | Nom. Thickness | Nom. Insulation Diameter | Color Code |
|---------|--------------------|--------------------|--------------------------|---------------|
| Pair(s) | PP - Polypropylene | 0.007 in (0.18 mm) | 0.042 in (1.1 mm) | Black and Red |

Outer Shield

| Material |
|-----------|
| No Shield |

Outer Jacket

| Material | Nom. Thickness | Nom. Diameter | Ripcord |
|--------------------------|--------------------|---------------|---------|
| PVC - Polyvinyl Chloride | 0.015 in (0.38 mm) | 0.114 in | Yes |

| | |
|-----------------------------------|----------|
| Overall Cable Diameter (Nominal): | 0.114 in |
|-----------------------------------|----------|

Electrical Characteristics

Electricals

| Element | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Max. Current |
|---------|--------------------|-------------------------------|--------------------------------|
| Pair(s) | 16.4 Ohm/1000ft | 20 pF/ft (66 pF/m) | 2.8 Amps per Conductor at 25°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V |

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|----------------|----------------|
| 75°C | -20°C To +75°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-------------------|-------------------|
| 1.14 in (29.0 mm) | 1.14 in |

| | |
|--------------------|--------------------|
| Max. Pull Tension: | 18.2 lbs (8.26 kg) |
|--------------------|--------------------|

| | |
|--------------------|--------------|
| Bulk Cable Weight: | 7 lbs/1000ft |
|--------------------|--------------|

Standards and Compliance

| | |
|----------------------------------|--|
| Environmental Suitability: | Indoor |
| Flammability / Reaction to Fire: | UL1685 UL Loading |
| NEC / UL Compliance: | Article 800, CM |
| CEC / C(UL) Compliance: | CM |
| European Directive Compliance: | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.301 Revision Date: 02-15-2024 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC |
|-----------------|-------------|------------|----------|--------------|
| 5500UG U4FU500 | Beige U4F | UnReel | 500 ft | 612825162933 |
| 5500UG U4FC1000 | Beige U4F | Coil | 1,000 ft | 612825162926 |
| 5500UG 006C500 | Blue, Light | Coil | 500 ft | 612825365839 |
| 5500UG 006U500 | Blue, Light | UnReel | 500 ft | 612825163046 |
| 5500UG 001C500 | Brown | Coil | 500 ft | 612825162957 |
| 5500UG 001C1000 | Brown | Coil | 1,000 ft | 612825162940 |
| 5500UG 008C500 | Gray | Coil | 500 ft | 612825163091 |
| 5500UG 008C1000 | Gray | Coil | 1,000 ft | 612825163084 |
| 5500UG 008U1000 | Gray | UnReel | 1,000 ft | 612825337188 |
| 5500UG 005C500 | Green, Dark | Coil | 500 ft | 612825163022 |
| 5500UG 005U500 | Green, Dark | UnReel | 500 ft | 612825163039 |
| 5500UG 005C1000 | Green, Dark | Coil | 1,000 ft | 612825163015 |
| 5500UG 003C500 | Orange | Coil | 500 ft | 612825162964 |
| 5500UG 003U500 | Orange | UnReel | 500 ft | 612825162971 |
| 5500UG 007C500 | Violet | Coil | 500 ft | 612825163060 |
| 5500UG 007U500 | Violet | UnReel | 500 ft | 612825163077 |
| 5500UG 007C1000 | Violet | Coil | 1,000 ft | 612825163053 |
| 5500UG 009C500 | White | Coil | 500 ft | 612825163114 |
| 5500UG 009C1000 | White | Coil | 1,000 ft | 612825163107 |
| 5500UG 009U1000 | White | UnReel | 1,000 ft | 612825163121 |
| 5500UG 004C500 | Yellow | Coil | 500 ft | 612825162995 |
| 5500UG 004U500 | Yellow | UnReel | 500 ft | 612825163008 |
| 5500UG 004C1000 | Yellow | Coil | 1,000 ft | 612825162988 |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 5500UG 005C1000 on WIN SOURCE](#)

 [Belden Inc. Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management