



**THE DATASHEET OF  
6SL32030BD238SA0**



MLFB-Ordering data

6SL3203-0BD23-8SA0



Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	Connections
------------	-------------

Input	
Number of phases	3 AC
Line voltage	380 ... 480 V

  

Output	
Rated current	39.4 A

Line side	
Version	screw-type terminal
Conductor cross-section	4.00 mm <sup>2</sup>

  

Load side	
Version	shielded lead
Conductor cross-section	4.00 mm <sup>2</sup>
Cable length	0.40 m

Mechanical data
-----------------

Dimensions	
Width	190.0 mm
Height	362.0 mm
Depth	55.0 mm
Degree of protection	IP20 / UL open type
Net weight	2.3 kg

PE connection	
Version	On housing with M4 screw studs

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View 6SL32030BD238SA0 on WIN SOURCE](#)

 [Siemens Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management