



**THE DATASHEET OF
A472K15X7RF5UAAP**



Axial Leaded Multilayer Ceramic Capacitors for Automotive Applications

Class 1 and Class 2, 50 V_{DC}, 100 V_{DC}, 200 V_{DC}



FEATURES

- AEC-Q200 qualified with PPAP available
- High reliability MLCC insert with wet build process
- High operating temperature up to 160 °C
- High capacitance with small size
- Axial mounting style
- Parts compliant with ELV directive
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

 AUTOMOTIVE
GRADE

RoHS
COMPLIANT

APPLICATIONS

- Automotive

| QUICK REFERENCE DATA | | | | | | |
|----------------------------|--------|--------|------|-----------|---------|---------|
| DESCRIPTION | VALUE | | | | | |
| Ceramic class | 1 | | | 2 | | |
| Ceramic dielectric | C0G | | | X7R | | |
| Voltage (V _{DC}) | 50 | 100 | 200 | 50 | 100 | 200 |
| Min. capacitance (pF) | 100 | 100 | 100 | 330 | 330 | 330 |
| Max. capacitance (pF) | 12 000 | 12 000 | 8200 | 1 000 000 | 470 000 | 180 000 |
| Mounting | Axial | | | | | |

MARKING

Marking indicates capacitance value and tolerance in accordance with “EIA 198” and voltage marks.

OPERATING TEMPERATURE RANGE

-55 °C to +160 °C (50 % rated voltage above 150 °C)

TEMPERATURE CHARACTERISTICS

Class 1: C0G

Class 2: X7R

SECTIONAL SPECIFICATIONS

Climatic category (acc. to EN 60058-1)

Class 1 and 2: 55/125/21

APPROVALS

EIA 198

IEC 60384-9

AEC-Q200

DESIGN

- The capacitors consist of a high reliability MLCC
- The lead wires are 0.5 mm and are made of 100 % tinned copper clad steel wire
- Coating is made of yellow colored flame retardant epoxy resin in accordance with UL 94 V-0

CAPACITANCE RANGE

100 pF to 1 μF

TOLERANCE ON CAPACITANCE

± 5 %, ± 10 %, ± 20 %

RATED VOLTAGE

50 V_{DC}, 100 V_{DC}, 200 V_{DC}

TEST VOLTAGE

- 50 V_{DC} and 100 V_{DC}: 250 % of rated voltage
- 200 V_{DC}: 200 % of rated voltage

INSULATION RESISTANCE

100 GΩ or 1000 ΩF whichever is less at rated voltage within 2 min of charging.


DISSIPATION FACTOR

Class 1: 0.1 % max.

(at 1 MHz, 1 V where C ≤ 1000 pF;
at 1 kHz; 1 V where C > 1000 pF)

Class 2: 2.5 % max.


(at 1 kHz, 1 V)

DIMENSIONS (in millimeters)


| SIZE CODE | Lb _{MAX.} | ØD _{MAX.} |
|-----------|--------------------|--------------------|
| 15 | 3.8 | 2.6 |
| 20 | 5.1 | 3.1 |

Note

- The leads are matte tinned FeCu wire

MARKING

MARKING CODE DESCRIPTION

| DDD | XXX | t | V | T |
|---|---|---------------------------------------|------------------------------------|--------------------------|
| Date Code | Capacitance Code | Tolerance Code | Voltage Code | T.C. Code |
| The first digit is the year, the last two digits are the week. For example: 109 = 2011, 9 th week 217 = 2012, 17 th week | Two significant digits followed by one digit for the multiplier as given below. 1 = * 10, 2 = * 100, 3 = * 1000, 4 = * 10 000, 5 = * 100 000 | J = ± 5 % K = ± 10 % M = ± 20 % | 1 = 100 V 2 = 200 V 5 = 50 V | A = C0G (NP0) C = X7R |

ORDERING CODE INFORMATION

| A | 104 | K | 15 | X7R | F | 5 | TAA | P |
|-----------------------|--|---------------------------------------|------------------------------------|------------------------------------|--|-----------------------|--------------------------|---|
| 1 | 2 3 4 | 5 | 6 7 | 8 9 10 | 11 | 12 | 13 14 15 | 16 |
| Product Type | Capacitance (pF) | Capacitance Tolerance | Size Code | TC Code | Rated Voltage | Lead Diameter | Packaging | AEC-Q200 Qualified |
| A = axial leaded MLCC | The first two digits are the significant figures of capacitance and the last digit is a multiplier as follows: 1 = * 10 2 = * 100 3 = * 1000 4 = * 10 000 5 = * 100 000 | J = ± 5 % K = ± 10 % M = ± 20 % | Please refer to relevant datasheet | Please refer to relevant datasheet | F = 50 V _{DC} H = 100 V _{DC} K = 200 V _{DC} | 5 = 0.50 mm ± 0.05 mm | TAA = reel UAA = ammo | P = AEC-Q200 qualified and lead (Pb)-free |



ORDERING CODES

| DIELECTRIC COG | | | |
|----------------|---------------------------------|---------------------------------|---------------------------------|
| CAP. (pF) | 50 V _{DC} | 100 V _{DC} | 200 V _{DC} |
| 100 | A101#15C0GF5###P | A101#15C0GH5###P | A101#15C0GK5###P |
| 120 | A121#15C0GF5###P | A121#15C0GH5###P | A121#15C0GK5###P |
| 150 | A151#15C0GF5###P | A151#15C0GH5###P | A151#15C0GK5###P |
| 180 | A181#15C0GF5###P | A181#15C0GH5###P | A181#15C0GK5###P |
| 220 | A221#15C0GF5###P | A221#15C0GH5###P | A221#15C0GK5###P |
| 270 | A271#15C0GF5###P | A271#15C0GH5###P | A271#15C0GK5###P |
| 330 | A331#15C0GF5###P | A331#15C0GH5###P | A331#15C0GK5###P |
| 390 | A391#15C0GF5###P | A391#15C0GH5###P | A391#15C0GK5###P |
| 470 | A471#15C0GF5###P | A471#15C0GH5###P | A471#15C0GK5###P |
| 560 | A561#15C0GF5###P | A561#15C0GH5###P | A561#15C0GK5###P |
| 680 | A681#15C0GF5###P | A681#15C0GH5###P | A681#15C0GK5###P |
| 820 | A821#15C0GF5###P | A821#15C0GH5###P | A821#15C0GK5###P |
| 1000 | A102#15C0GF5###P | A102#15C0GH5###P | A102#15C0GK5###P |
| 1200 | A122#15C0GF5###P | A122#15C0GH5###P | A122#20C0GK5###P |
| 1500 | A152#15C0GF5###P | A152#15C0GH5###P | A152#20C0GK5###P |
| 1800 | A182#15C0GF5###P | A182#15C0GH5###P | A182#20C0GK5###P |
| 2200 | A222#15C0GF5###P | A222#20C0GH5###P | A222#20C0GK5###P |
| 2700 | A272#15C0GF5###P | A272#20C0GH5###P | A272#20C0GK5###P |
| 3300 | A332#15C0GF5###P | A332#20C0GH5###P | A332#20C0GK5###P |
| 3900 | A392#15C0GF5###P | A392#20C0GH5###P | A392#20C0GK5###P ⁽¹⁾ |
| 4700 | A472#20C0GF5###P | A472#20C0GH5###P | A472#20C0GK5###P ⁽¹⁾ |
| 5600 | A562#20C0GF5###P | A562#20C0GH5###P | A562#20C0GK5###P ⁽¹⁾ |
| 6800 | A682#20C0GF5###P | A682#20C0GH5###P | A682#20C0GK5###P ⁽¹⁾ |
| 8200 | A822#20C0GF5###P | A822#20C0GH5###P | A822#20C0GK5###P ⁽¹⁾ |
| 12 000 | A123#20C0GF5###P ⁽¹⁾ | A123#20C0GH5###P ⁽¹⁾ | - |

Notes

- Lead diameter is 0.5 mm
 - # 5th digit is capacitance tolerance code: ± 5 % = J; ± 10 % = K
 - # 13th, 14th and 15th digits are packaging code: reel = TAA; ammo = UAA
- ⁽¹⁾ Ø D is 4.5 mm max.



| DIELECTRIC X7R | | | |
|----------------|---------------------------------|---------------------------------|---------------------------------|
| CAP. (pF) | 50 V _{DC} | 100 V _{DC} | 200 V _{DC} |
| 330 | A331#15X7RF5###P | A331#15X7RH5###P | A331#15X7RK5###P |
| 390 | A391#15X7RF5###P | A391#15X7RH5###P | A391#15X7RK5###P |
| 470 | A471#15X7RF5###P | A471#15X7RH5###P | A471#15X7RK5###P |
| 560 | A561#15X7RF5###P | A561#15X7RH5###P | A561#15X7RK5###P |
| 680 | A681#15X7RF5###P | A681#15X7RH5###P | A681#15X7RK5###P |
| 820 | A821#15X7RF5###P | A821#15X7RH5###P | A821#15X7RK5###P |
| 1000 | A102#15X7RF5###P | A102#15X7RH5###P | A102#15X7RK5###P |
| 1200 | A122#15X7RF5###P | A122#15X7RH5###P | A122#15X7RK5###P |
| 1500 | A152#15X7RF5###P | A152#15X7RH5###P | A152#15X7RK5###P |
| 1800 | A182#15X7RF5###P | A182#15X7RH5###P | A182#15X7RK5###P |
| 2200 | A222#15X7RF5###P | A222#15X7RH5###P | A222#15X7RK5###P |
| 2700 | A272#15X7RF5###P | A272#15X7RH5###P | A272#15X7RK5###P |
| 3300 | A332#15X7RF5###P | A332#15X7RH5###P | A332#15X7RK5###P |
| 3900 | A392#15X7RF5###P | A392#15X7RH5###P | A392#15X7RK5###P |
| 4700 | A472#15X7RF5###P | A472#15X7RH5###P | A472#15X7RK5###P |
| 5600 | A562#15X7RF5###P | A562#15X7RH5###P | A562#15X7RK5###P |
| 6800 | A682#15X7RF5###P | A682#15X7RH5###P | A682#15X7RK5###P |
| 8200 | A822#15X7RF5###P | A822#15X7RH5###P | A822#15X7RK5###P |
| 10 000 | A103#15X7RF5###P | A103#15X7RH5###P | A103#15X7RK5###P |
| 12 000 | A123#15X7RF5###P | A123#15X7RH5###P | A123#15X7RK5###P |
| 15 000 | A153#15X7RF5###P | A153#15X7RH5###P | A153#15X7RK5###P |
| 18 000 | A183#15X7RF5###P | A183#15X7RH5###P | A183#15X7RK5###P |
| 22 000 | A223#15X7RF5###P | A223#15X7RH5###P | A223#15X7RK5###P |
| 27 000 | A273#15X7RF5###P | A273#15X7RH5###P | A273#15X7RK5###P |
| 33 000 | A333#15X7RF5###P | A333#15X7RH5###P | A333#20X7RK5###P |
| 39 000 | A393#15X7RF5###P | A393#15X7RH5###P | A393#20X7RK5###P |
| 47 000 | A473#15X7RF5###P | A473#15X7RH5###P | A473#20X7RK5###P |
| 56 000 | A563#15X7RF5###P | A563#15X7RH5###P | A563#20X7RK5###P |
| 68 000 | A683#15X7RF5###P | A683#15X7RH5###P | A683#20X7RK5###P |
| 82 000 | A823#15X7RF5###P | A823#15X7RH5###P | A823#20X7RK5###P |
| 100 000 | A104#15X7RF5###P | A104#15X7RH5###P | A104#20X7RK5###P |
| 120 000 | A124#15X7RF5###P | A124#20X7RH5###P | A124#20X7RK5###P |
| 150 000 | A154#20X7RF5###P | A154#20X7RH5###P | A154#20X7RK5###P ⁽¹⁾ |
| 180 000 | A184#20X7RF5###P | A184#20X7RH5###P | A184#20X7RK5###P ⁽¹⁾ |
| 220 000 | A224#20X7RF5###P | A224#20X7RH5###P | - |
| 270 000 | A274#20X7RF5###P | A274#20X7RH5###P | - |
| 330 000 | A334#20X7RF5###P | A334#20X7RH5###P ⁽¹⁾ | - |
| 390 000 | A394#20X7RF5###P | A394#20X7RH5###P ⁽¹⁾ | - |
| 470 000 | A474#20X7RF5###P | A474#20X7RH5###P ⁽¹⁾ | - |
| 560 000 | A564#20X7RF5###P ⁽¹⁾ | - | - |
| 680 000 | A684#20X7RF5###P ⁽¹⁾ | - | - |
| 820 000 | A824#20X7RF5###P ⁽¹⁾ | - | - |
| 1 000 000 | A105#20X7RF5###P ⁽¹⁾ | - | - |

Notes

- Lead diameter is 0.5 mm
 - # 5th digit is capacitance tolerance code: ± 10 % = K; ± 20 % = M
 - # 13th, 14th and 15th digits are packaging code: reel = TAA; ammo = UAA
- ⁽¹⁾ Ø D is 4.5 mm max.



TAPING AND PACKAGING

LABELLING

Each reel is provided with a label showing the following details:

manufacturer, A style, capacitance, tolerance, batch number, quantity of components, rated voltage, dielectric.


On special request other designations can be shown.

For example:



| PACKAGING QUANTITIES AND BOX DIMENSIONS | | | |
|---|--|-----------------------------------|-------------------------------|
| PACKAGING | SIZE CODE | SMALLEST PACKAGING QUANTITY (SPQ) | BOX DIMENSIONS L x W x H (mm) |
| Tape on reel | 15, 20 | 7000 | 370 x 370 x 90 |
| | Ordering code marked with ⁽¹⁾ | 5000 | |
| Ammopack | 15, 20 | 4000 | 265 x 85 x 95 |
| | Ordering code marked with ⁽¹⁾ | 2000 | |

CAPACITORS ON BANDOLIER FOR DIPPED AXIAL



| PARAMETER | SYMBOL | DIMENSIONS | |
|--|------------------|------------|---------------|
| | | mm | INCH |
| Inside tape spacing | B ⁽¹⁾ | 52.4 ± 1.5 | 2.062 ± 0.059 |
| Center to tape spacing | C | ± 0.8 | ± 0.031 |
| Cumulative pitch, 6 consecutive components | P | ± 1.5 | ± 0.059 |
| Components pitch | A | 5.0 ± 0.5 | 0.197 ± 0.015 |
| Lead bend | M | < 1.2 | < 0.047 |
| Exposed adhesive | S | < 0.51 | > 0.020 |
| Tape width | T | 6.35 | 0.250 |
| Lead sandwich | H | > 3.96 | > 0.156 |

Note

⁽¹⁾ Inside tape spacing 26.0 mm + 1.51 mm/- 0.0 mm is available on request

REEL DATA


A maximum of 0.5 % of the total number of capacitors per reel may be missing.

A maximum of 1 consecutive vacant positions is followed by 6 consecutive components.

Tape begins and ends with a minimum of 4 empty positions (180 mm tape).

Maximum of 5 splicers per reel.

REEL



| REEL DIMENSIONS | | |
|-----------------|----------------|------------|
| | | |
| REEL SIZE | | (mm) |
| A | Outer diameter | 355.6 max. |
| L | Hole diameter | 28 ± 1 |
| K | Core diameter | 90 |
| H ₁ | Internal width | 69.9 ± 1.5 |

AMMOPACK DATA

A maximum of 0.5 % of the total number of capacitors per pack may be missing.


A maximum of 1 consecutive vacant positions is followed by 6 consecutive components.

Tape begins and ends with a minimum of 4 empty positions (180 mm tape).

Maximum of 5 splicers per pack.

The cumulative pitch tolerance over 20 consecutive units is not to exceed ± 1.0 mm.

AMMOPACK



| RELATED DOCUMENTS | |
|---------------------|--|
| General Information | www.vishay.com/doc?45214 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

⊖ [View A472K15X7RF5UAAP](#) on WIN SOURCE

⊖ [Vishay](#) Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management