



**THE DATASHEET OF  
AOTF15B65M3**



### General Description

- Latest AlphaGBT (αIGBT) technology
- 650V Breakdown voltage
- Very fast and soft recovery freewheeling diode
- High efficient turn-on di/dt controllability
- Low  $V_{CE(sat)}$  enables high efficiencies
- Low turn-off switching loss and softness
- Very good EMI behavior
- High short-circuit ruggedness

### Applications


- Motor drives
- Sewing machines
- Home appliances
- Fan, pumps, vacuum cleaner
- Other hard switching applications

### Product Summary


$V_{CE}$	650V
$I_C$ ( $T_C=100^\circ\text{C}$ )	15A
$V_{CE(sat)}$ ( $T_J=25^\circ\text{C}$ )	1.95V



TO-220F



AOTF15B65M3



Orderable Part Number	Package Type	Form	Minimum Order Quantity
AOTF15B65M3	TO220F	Tube	1000

### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	AOTF15B65M3	Units
Collector-Emitter Voltage	$V_{CE}$	650	V
Gate-Emitter Voltage	$V_{GE}$	$\pm 30$	V
Continuous Collector Current	$I_C$	$T_C=25^\circ\text{C}$	30 <sup>(2)</sup>
		$T_C=100^\circ\text{C}$	15 <sup>(2)</sup>
Pulsed Collector Current, Limited by $T_{Jmax}$	$I_{CM}$	45	A
Turn off SOA, $V_{CE} \leq 650\text{V}$ , Limited by $T_{Jmax}$	$I_{LM}$	45	A
Continuous Diode Forward Current	$I_F$	$T_C=25^\circ\text{C}$	20 <sup>(2)</sup>
		$T_C=100^\circ\text{C}$	10 <sup>(2)</sup>
Diode Pulsed Current, Limited by $T_{Jmax}$	$I_{FM}$	30	A
Short circuit withstanding time $t_{SC}$ $V_{GE}=15\text{V}$ , $V_{CC} \leq 400\text{V}$ , $T_J \leq 150^\circ\text{C}$	$t_{SC}$	5	$\mu\text{s}$
Power Dissipation	$P_D$	$T_C=25^\circ\text{C}$	30
		$T_C=100^\circ\text{C}$	12
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	$^\circ\text{C}$
Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds	$T_L$	300	$^\circ\text{C}$

### Thermal Characteristics

Parameter	Symbol	AOTF15B65M3	Units
Maximum Junction-to-Ambient	$R_{\theta JA}$	65	$^\circ\text{C/W}$
Maximum IGBT Junction-to-Case	$R_{\theta JC}$	4.2	$^\circ\text{C/W}$
Maximum Diode Junction-to-Case	$R_{\theta JC}$	7	$^\circ\text{C/W}$

1) Allowed number of short circuits: <1000; time between short circuits: >1s.

2) TO220F  $I_C$  follows TO220/TO263.


**Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units	
<b>STATIC PARAMETERS</b>							
BV <sub>CES</sub>	Collector-Emitter Breakdown Voltage	I <sub>C</sub> =1mA, V <sub>GE</sub> =0V, T <sub>J</sub> =25°C	650	-	-	V	
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	V <sub>GE</sub> =15V, I <sub>C</sub> =15A	T <sub>J</sub> =25°C	-	1.95	2.5	V
			T <sub>J</sub> =125°C	-	2.46	-	
			T <sub>J</sub> =150°C	-	2.61	-	
V <sub>F</sub>	Diode Forward Voltage	V <sub>GE</sub> =0V, I <sub>F</sub> =10A	T <sub>J</sub> =25°C	-	1.9	2.4	V
			T <sub>J</sub> =125°C	-	1.96	-	
			T <sub>J</sub> =150°C	-	1.95	-	
V <sub>GE(th)</sub>	Gate-Emitter Threshold Voltage	V <sub>CE</sub> =5V, I <sub>C</sub> =1mA	-	5.1	-	V	
I <sub>CES</sub>	Zero Gate Voltage Collector Current	V <sub>CE</sub> =650V, V <sub>GE</sub> =0V	T <sub>J</sub> =25°C	-	-	10	μA
			T <sub>J</sub> =125°C	-	-	100	
			T <sub>J</sub> =150°C	-	-	500	
I <sub>GES</sub>	Gate-Emitter leakage current	V <sub>CE</sub> =0V, V <sub>GE</sub> =±30V	-	-	±100	nA	
g <sub>FS</sub>	Forward Transconductance	V <sub>CE</sub> =20V, I <sub>C</sub> =15A	-	9	-	S	
<b>DYNAMIC PARAMETERS</b>							
C <sub>ies</sub>	Input Capacitance	V <sub>GE</sub> =0V, V <sub>CC</sub> =25V, f=1MHz	-	655	-	pF	
C <sub>oes</sub>	Output Capacitance		-	68	-	pF	
C <sub>res</sub>	Reverse Transfer Capacitance		-	25	-	pF	
Q <sub>g</sub>	Total Gate Charge	V <sub>GE</sub> =15V, V <sub>CC</sub> =520V, I <sub>C</sub> =15A	-	25.4	-	nC	
Q <sub>ge</sub>	Gate to Emitter Charge		-	7.5	-	nC	
Q <sub>gc</sub>	Gate to Collector Charge		-	11	-	nC	
I <sub>C(SC)</sub>	Short circuit collector current	V <sub>GE</sub> =15V, V <sub>CC</sub> =400V, t <sub>sc</sub> ≤5μs, T <sub>J</sub> ≤150°C	-	70	-	A	
R <sub>g</sub>	Gate resistance	V <sub>GE</sub> =0V, V <sub>CC</sub> =0V, f=1MHz	-	5.8	-	Ω	
<b>SWITCHING PARAMETERS, (Load Inductive, T<sub>J</sub>=25°C)</b>							
t <sub>D(on)</sub>	Turn-On DelayTime	T <sub>J</sub> =25°C V <sub>GE</sub> =15V, V <sub>CC</sub> =400V, I <sub>C</sub> =15A, R <sub>G</sub> =20Ω	-	10	-	ns	
t <sub>r</sub>	Turn-On Rise Time		-	17	-	ns	
t <sub>D(off)</sub>	Turn-Off Delay Time		-	68	-	ns	
t <sub>f</sub>	Turn-Off Fall Time		-	16	-	ns	
E <sub>on</sub>	Turn-On Energy		-	0.28	-	mJ	
E <sub>off</sub>	Turn-Off Energy		-	0.19	-	mJ	
E <sub>total</sub>	Total Switching Energy		-	0.47	-	mJ	
t <sub>rr</sub>	Diode Reverse Recovery Time		-	263	-	ns	
Q <sub>rr</sub>	Diode Reverse Recovery Charge		I <sub>F</sub> =10A, di/dt=200A/μs, V <sub>CC</sub> =400V	-	0.4	-	μC
I <sub>rm</sub>	Diode Peak Reverse Recovery Current		-	3.8	-	A	
<b>SWITCHING PARAMETERS, (Load Inductive, T<sub>J</sub>=150°C)</b>							
t <sub>D(on)</sub>	Turn-On DelayTime	T <sub>J</sub> =150°C V <sub>GE</sub> =15V, V <sub>CC</sub> =400V, I <sub>C</sub> =15A, R <sub>G</sub> =20Ω	-	9	-	ns	
t <sub>r</sub>	Turn-On Rise Time		-	18	-	ns	
t <sub>D(off)</sub>	Turn-Off Delay Time		-	80	-	ns	
t <sub>f</sub>	Turn-Off Fall Time		-	28	-	ns	
E <sub>on</sub>	Turn-On Energy		-	0.3	-	mJ	
E <sub>off</sub>	Turn-Off Energy		-	0.31	-	mJ	
E <sub>total</sub>	Total Switching Energy		-	0.61	-	mJ	
t <sub>rr</sub>	Diode Reverse Recovery Time		-	262	-	ns	
Q <sub>rr</sub>	Diode Reverse Recovery Charge		I <sub>F</sub> =10A, di/dt=200A/μs, V <sub>CC</sub> =400V	-	0.6	-	μC
I <sub>rm</sub>	Diode Peak Reverse Recovery Current		-	4.5	-	A	


APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO MAKE CHANGES TO PRODUCT SPECIFICATIONS WITHOUT NOTICE. IT IS THE RESPONSIBILITY OF THE CUSTOMER TO EVALUATE SUITABILITY OF THE PRODUCT FOR THEIR INTENDED APPLICATION. CUSTOMER SHALL COMPLY WITH APPLICABLE LEGAL REQUIREMENTS, INCLUDING ALL APPLICABLE EXPORT CONTROL RULES, REGULATIONS AND LIMITATIONS.

AOS' products are provided subject to AOS' terms and conditions of sale which are set forth at:  
[http://www.aosmd.com/terms\\_and\\_conditions\\_of\\_sale](http://www.aosmd.com/terms_and_conditions_of_sale)


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




**Figure 1: Output Characteristic**  
( $T_j=25^\circ\text{C}$ )




**Figure 2: Output Characteristic**  
( $T_j=150^\circ\text{C}$ )




**Figure 3: Transfer Characteristic**



**Figure 4: Diode Characteristic**




**Figure 5: Collector-Emitter Saturation Voltage vs. Junction Temperature**




**Figure 6: Diode Forward voltage vs. Junction Temperature**


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




**Figure 7: Gate-Charge Characteristics**




**Figure 8: Capacitance Characteristic**




**Figure 9: Forward Bias Safe Operating Area**  
( $T_C=25^\circ\text{C}$ ,  $V_{GE}=15\text{V}$ )



**Figure 10: Power Dissipation as a Function of Case**




**Figure 11: Current De-rating**




**Figure 12: Diode Reverse Leakage Current vs. Junction Temperature**


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




**Figure 13: Switching Time vs.  $I_C$**   
( $T_J=150^\circ\text{C}$ ,  $V_{GE}=15\text{V}$ ,  $V_{CE}=400\text{V}$ ,  $R_g=20\Omega$ )



**Figure 14: Switching Time vs.  $R_g$**   
( $T_J=150^\circ\text{C}$ ,  $V_{GE}=15\text{V}$ ,  $V_{CE}=400\text{V}$ ,  $I_C=15\text{A}$ )




**Figure 15: Switching Time vs.  $T_J$**   
( $V_{GE}=15\text{V}$ ,  $V_{CE}=400\text{V}$ ,  $I_C=15\text{A}$ ,  $R_g=20\Omega$ )




**Figure 16:  $V_{GE(\text{TH})}$  vs.  $T_J$**


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




**Figure 17: Switching Loss vs.  $I_C$**   
( $T_j=150^\circ\text{C}$ ,  $V_{GE}=15\text{V}$ ,  $V_{CE}=400\text{V}$ ,  $R_g=20\Omega$ )



**Figure 18: Switching Loss vs.  $R_g$**   
( $T_j=150^\circ\text{C}$ ,  $V_{GE}=15\text{V}$ ,  $V_{CE}=400\text{V}$ ,  $I_C=15\text{A}$ )




**Figure 19: Switching Loss vs.  $T_j$**   
( $V_{GE}=15\text{V}$ ,  $V_{CE}=400\text{V}$ ,  $I_C=15\text{A}$ ,  $R_g=20\Omega$ )




**Figure 20: Switching Loss vs.  $V_{CE}$**   
( $T_j=150^\circ\text{C}$ ,  $V_{GE}=15\text{V}$ ,  $I_C=15\text{A}$ ,  $R_g=20\Omega$ )


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




**Figure 21: Diode Reverse Recovery Charge and Peak Current vs. Conduction Current**  
( $V_{GE}=15V, V_{CE}=400V, di/dt=200A/\mu s$ )



**Figure 22: Diode Reverse Recovery Time and Softness Factor vs. Conduction Current**  
( $V_{GE}=15V, V_{CE}=400V, di/dt=200A/\mu s$ )




**Figure 23: Diode Reverse Recovery Charge and Peak Current vs. di/dt**  
( $V_{GE}=15V, V_{CE}=400V, I_F=10A$ )




**Figure 24: Diode Reverse Recovery Time and Softness Factor vs. di/dt**  
( $V_{GE}=15V, V_{CE}=400V, I_F=10A$ )

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**



**Figure 25: Normalized Maximum Transient Thermal Impedance for IGBT**



**Figure 26: Normalized Maximum Transient Thermal Impedance for Diode**




Figure A: Gate Charge Test Circuit & Waveforms




Figure B: Inductive Switching Test Circuit & Waveforms




Figure C: Diode Recovery Test Circuit & Waveforms

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View AOTF15B65M3 on WIN SOURCE](#)
- [Alpha & Omega Semiconductor Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management