



**THE DATASHEET OF  
HM2103NLT**






NOTES: UNLESS OTHERWISE SPECIFIED

NOTICE:	THIS IS A RoHS COMPLIANT COMPONENT/PRODUCT. ALL ENGINEERING CHANGES MUST HAVE PRIOR APPROVAL BY THE DESIGN CENTER.
RoHS	


1. SOLDERABILITY: CONFORMS TO ANSI/J-STD-002, IPC/EIA J-STD-003A.
2. OPERATING TEMPERATURE: -40°C TO +125°C
3. STORAGE TEMPERATURE: -50°C TO +125°C
4. JEDEC MOISTURE: LEVEL 1.
5. AEC-Q200 QUALIFIED
6. TO ORDER TAPE & REEL PACKAGING ADD A "T" SUFFIX TO THE PART NUMBER (ie. HM2103NL BECOMES HM2103NLT)
7. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES. TOLERANCES ARE:

DECIMALS

.XX ±.01  
.XXX ±.005





SUGGES



© Copyright, 2017, Pulse Electronics Corp. All rights reserved. Pulse confidential & proprietary. (09/13/17)

PRODUCT DESCRIPTION	TLA DRAWING	PS DRAWING	SHEET	PART
TRANSFORMER/CMC,4.3kVDC ISO,SGL,SMT	HM2103NL-10	PS-01528.001-A	1 OF 2	HM21

E-MAIL: PRODINFONETWORK@PULSEELECTRONICS.COM(US), ASIA@PULSEELECTRONICS.COM(Asia) PHONE: USA:858 674 8100, GERMANY:49 7032 78060, SINGAPORE:65 6287 8998, SH



SCHEMATIC

ELECTRICAL CHARACTERISTICS AT +25°C UNLESS

PARAMETER	SPECIFICATION
QUALIFICATION	PER AEC-Q200
DESIGN CONSTRUCTION	FUNCTIONAL IN
CREEPAGE DISTANCE	> 5mm
OPERATING TEMPERATURE	-40°C TO 125°C
TURNS RATIO	1.00 ± 0.02
POLARITY	PER SCHEMATIC
DC RESISTANCE	TRANSFORMER SIDE 0.45 OHMS MAX
INDUCTANCE (OCL) AT 100 kHz, 100 mV (-40°C TO +125°C)	150 uH MIN, 45 uH MAX
LEAKAGE INDUCTANCE	0.50 uH MAX @ 100 kHz
INSERTION LOSS	0.25 dB MAX @ 100 kHz
RETURN LOSS (Z OUT = 100 OHM ±1%)	20 dB MIN @ 100 kHz
COMMON MODE REJECTION RATIO	1-10 MHz -35 dB MIN
INPUT - OUTPUT ISOLATION	4300 VDC FOR 1 MIN WITH 1.0 mA MAX OF 100 kHz PULSES
INSULATION RESISTANCE	400 MEGAOHMS MIN
WORKING VOLTAGE	1000 VDC FOR 1 MIN

© Copyright, 2017, Pulse Electronics Corp. All rights reserved. Pulse confidential & proprietary. (09/13/17)

PRODUCT DESCRIPTION	TLA DRAWING	PS DRAWING	SHEET	PART
TRANSFORMER/CMC,4.3kVDC ISO,SGL,SMT	HM2103NL-10	PS-01528.001-A	2 OF 2	HM2103NL-10

E-MAIL: PRODINFO@PULSEELECTRONICS.COM(US), ASIA@PULSEELECTRONICS.COM(Asia)

PHONE: USA:858 674 8100, GERMANY:49 7032 78060, SINGAPORE:65 6287 8998, SHANGHAI:86 21 5101 9999

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View HM2103NLT on WIN SOURCE](#)

 [Pulse Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management