



# THE DATASHEET OF TPSMD22A



## TPSMD Series



### Agency Approvals

| AGENCY | AGENCY FILE NUMBER |
|--------|--------------------|
|        | E230531            |


### Maximum Ratings and Thermal Characteristics (T<sub>A</sub>=25°C unless otherwise noted)

| Parameter  | Symbol                            | Value      | Unit |
|--|-----------------------------------|------------|------|
| Peak Pulse Power Dissipation by 10/1000µs Waveform (Fig.2)(Note 1), (Note 2) | P <sub>PPM</sub>                  | 3000       | W    |
| Power Dissipation on Infinite Heat Sink at T <sub>A</sub> =50°C              | P <sub>M(AV)</sub>                | 6.5        | W    |
| Peak Forward Surge Current, 8.3ms Single Half Sine Wave (Note 3)             | I <sub>FSM</sub>                  | 300        | A    |
| Maximum Instantaneous Forward Voltage at 100A for Unidirectional Only        | V <sub>F</sub>                    | 3.5        | V    |
| Operating Junction and Storage Temperature Range                             | T <sub>J</sub> , T <sub>STG</sub> | -65 to 150 | °C   |
| Typical Thermal Resistance Junction to Lead                                  | R <sub>wJL</sub>                  | 15         | °C/W |
| Typical Thermal Resistance Junction to Ambient                               | R <sub>wJA</sub>                  | 75         | °C/W |

**Notes:**

1. Non-repetitive current pulse per Fig. 4 and derated above T<sub>A</sub> = 25°C per Fig. 3.
2. Mounted on copper pad area of 0.31x0.31" (8.0 x 8.0mm) to each terminal.
3. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional component only, duty cycle=4 per minute maximum.

### Functional Diagram



### Description

The TPSMD series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.


### Features

- Hi reliability application and automotive grade AEC-Q101 qualified
- SMT for minimal board footprint
- Low profile package
- Typical failure mode is short from over-specified voltage or current
- Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c
- IEC-61000-4-2 ESD 30kV(Air), 30kV (Contact)
- EFT protection of data lines in accordance with IEC 61000-4-4
- Built-in strain relief
- V<sub>BR</sub> @T<sub>J</sub> = V<sub>BR</sub> @25°C x (1 + α T x (T<sub>J</sub> - 25)) (α T: Temperature Coefficient)
- Glass passivated chip junction
- 3000W peak pulse power capability at 10/1000µs waveform, repetition rate (duty cycles):0.01%
- Fast response time: typically less than 1.0ps from 0V to V<sub>BR</sub> min
- Excellent clamping capability
- Low incremental surge resistance
- Typical I<sub>R</sub> ≤ 2µA for V<sub>R</sub> > 10V
- High temperature soldering guaranteed: 260°C/10 seconds at terminals
- UL Recognized compound meeting flammability rating V-0.
- Meet MSL level1, per J-STD-020, high temperature soldering guaranteed.
- Matte tin lead-free plated
- Halogen free and RoHS compliant
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/JEDEC J-STD-609A.01)



### Applications

TVS Components are ideal for the protection of I/O Interfaces, V<sub>CC</sub> bus and other vulnerable circuits used in Telecom, Computer, Industrial and Consumer electronic applications.

## Electrical Characteristics

| Part Number (Uni) | Part Number (Bi) | Marking |      | Reverse Stand off Voltage $V_R$ (Volts) | Breakdown Voltage $V_{BR}$ (Volts) @ $I_T$ |        | Test Current $I_T$ (mA) | Maximum Clamping Voltage $V_C$ @ $I_{CP}$ (V) | Maximum Peak Pulse Current $I_{PP}$ (A) | Maximum Reverse Leakage $I_R$ @ $V_R$ ( $\mu$ A) | Agency Approval  |
|-------------------|------------------|---------|------|---|--|--------|-------------------------|---|---|--|---|
|                   |                  | UNI     | BI   |   | MIN  | MAX    |                         |   |   |  |   |
| TPSMD10A          | TPSMD10CA        | PDXA    | DDXA | 10.0                                    | 11.10                                      | 12.30  | 1                       | 17.0  | 176.5                                   | 5  | X   |
| TPSMD11A          | TPSMD11CA        | PDZA    | DDZA | 11.0                                    | 12.20                                      | 13.50  | 1                       | 18.2  | 164.8                                   | 2  | X   |
| TPSMD12A          | TPSMD12CA        | PEEA    | DEEA | 12.0                                    | 13.30                                      | 14.70  | 1                       | 19.9  | 150.8                                   | 2  | X   |
| TPSMD13A          | TPSMD13CA        | PEGA    | DEGA | 13.0                                    | 14.40                                      | 15.90  | 1                       | 21.5  | 139.5                                   | 2  | X   |
| TPSMD14A          | TPSMD14CA        | PEKA    | DEKA | 14.0                                    | 15.60                                      | 17.20  | 1                       | 23.2  | 129.3                                   | 2  | X   |
| TPSMD15A          | TPSMD15CA        | PEMA    | DEMA | 15.0                                    | 16.70                                      | 18.50  | 1                       | 24.4  | 123.0                                   | 2  | X   |
| TPSMD16A          | TPSMD16CA        | PEPA    | DEPA | 16.0                                    | 17.80                                      | 19.70  | 1                       | 26.0  | 115.4                                   | 2  | X   |
| TPSMD17A          | TPSMD17CA        | PERA    | DERA | 17.0                                    | 18.90                                      | 20.90  | 1                       | 27.6  | 108.7                                   | 2  | X   |
| TPSMD18A          | TPSMD18CA        | PETA    | DETA | 18.0                                    | 20.00                                      | 22.10  | 1                       | 29.2  | 102.7                                   | 2  | X   |
| TPSMD20A          | TPSMD20CA        | PEVA    | DEVA | 20.0                                    | 22.20                                      | 24.50  | 1                       | 32.4  | 92.6                                    | 2  | X   |
| TPSMD22A          | TPSMD22CA        | PEXA    | DEXA | 22.0                                    | 24.40                                      | 26.90  | 1                       | 35.5  | 84.5                                    | 2  | X   |
| TPSMD24A          | TPSMD24CA        | PEZA    | DEZA | 24.0                                    | 26.70                                      | 29.50  | 1                       | 38.9  | 77.1                                    | 2  | X   |
| TPSMD26A          | TPSMD26CA        | PFEA    | DFEA | 26.0                                    | 28.90                                      | 31.90  | 1                       | 42.1  | 71.3                                    | 2  | X   |
| TPSMD28A          | TPSMD28CA        | PFGA    | DFGA | 28.0                                    | 31.10                                      | 34.40  | 1                       | 45.4  | 66.1                                    | 2  | X   |
| TPSMD30A          | TPSMD30CA        | PFKA    | DFKA | 30.0                                    | 33.30                                      | 36.80  | 1                       | 48.4  | 62.0                                    | 2  | X   |
| TPSMD33A          | TPSMD33CA        | PFMA    | DFMA | 33.0                                    | 36.70                                      | 40.60  | 1                       | 53.3  | 56.3                                    | 2  | X   |
| TPSMD36A          | TPSMD36CA        | PFPA    | DFPA | 36.0                                    | 40.00                                      | 44.20  | 1                       | 58.1  | 51.6                                    | 2  | X   |
| TPSMD40A          | TPSMD40CA        | PFRA    | DFRA | 40.0                                    | 44.40                                      | 49.10  | 1                       | 64.5  | 46.5                                    | 2  | X   |
| TPSMD43A          | TPSMD43CA        | PFTA    | DFTA | 43.0                                    | 47.80                                      | 52.80  | 1                       | 69.4  | 43.2                                    | 2  | X   |
| TPSMD45A          | TPSMD45CA        | PFVA    | DFVA | 45.0                                    | 50.00                                      | 55.30  | 1                       | 72.7  | 41.3                                    | 2  | X   |
| TPSMD48A          | TPSMD48CA        | PFXA    | DFXA | 48.0                                    | 53.30                                      | 58.90  | 1                       | 77.4  | 38.8                                    | 2  | X   |
| TPSMD51A          | TPSMD51CA        | PFZA    | DFZA | 51.0                                    | 56.70                                      | 62.70  | 1                       | 82.4  | 36.4                                    | 2  | X   |
| TPSMD54A          | TPSMD54CA        | RGEA    | DGEA | 54.0                                    | 60.00                                      | 66.30  | 1                       | 87.1  | 34.4                                    | 2  | X   |
| TPSMD58A          | TPSMD58CA        | PGGA    | DGGA | 58.0                                    | 64.40                                      | 71.20  | 1                       | 93.6  | 32.1                                    | 2  | X   |
| TPSMD60A          | TPSMD60CA        | PGKA    | DGKA | 60.0                                    | 66.70                                      | 73.70  | 1                       | 96.8  | 31.0                                    | 2  | X   |
| TPSMD64A          | TPSMD64CA        | PGMA    | DGMA | 64.0                                    | 71.10                                      | 78.60  | 1                       | 103.0   | 29.1                                    | 2  | X   |
| TPSMD70A          | TPSMD70CA        | PGPA    | DGPA | 70.0                                    | 77.80                                      | 86.00  | 1                       | 113.0   | 26.5                                    | 2  | X   |
| TPSMD75A          | TPSMD75CA        | PGRA    | DGRA | 75.0                                    | 83.30                                      | 92.10  | 1                       | 121.0   | 24.8                                    | 2  | X   |
| TPSMD78A          | TPSMD78CA        | PGTA    | DGTA | 78.0                                    | 86.70                                      | 95.80  | 1                       | 126.0   | 23.8                                    | 2  | X   |
| TPSMD85A          | TPSMD85CA        | PGVA    | DGVA | 85.0                                    | 94.40                                      | 104.00 | 1                       | 137.0   | 21.9                                    | 2  | X   |


**I-V Curve Characteristics**




- $P_{PPM}$  Peak Pulse Power Dissipation** – Max power dissipation
- $V_R$  Stand-off Voltage** – Maximum voltage that can be applied to the TVS without operation
- $V_{BR}$  Breakdown Voltage** – Maximum voltage that flows through the TVS at a specified test current ( $I_T$ )
- $V_C$  Clamping Voltage** – Peak voltage measured across the TVS at a specified  $I_{ppm}$  (peak impulse current)
- $I_R$  Reverse Leakage Current** – Current measured at  $V_R$
- $V_F$  Forward Voltage Drop for Uni-directional**

**Ratings and Characteristic Curves** ( $T_A=25^\circ\text{C}$  unless otherwise noted)

**Figure 1 - TVS Transients Clamping Waveform**




**Figure 2 - Peak Pulse Power Rating**




continues on next page.

**Ratings and Characteristic Curves** ( $T_J=25^\circ\text{C}$  unless otherwise noted) (Continued)


**Figure 3 - Peak Pulse Power Derating Curve**




**Figure 4 - Pulse Waveform**




**Figure 5 - Typical Junction Capacitance**



**Figure 6 - Steady State Power Derating Curve**




**Figure 7 - Maximum Non-Repetitive Peak Forward Surge Current Uni-Directional only**



### Soldering Parameters

|  |                                    |                  |
|--|------------------------------------|------------------|
| Reflow Condition                                       | Lead-free assembly                 |                  |
| Pre Heat   | - Temperature Min ( $T_{s(min)}$ ) | 150°C            |
|  | - Temperature Max ( $T_{s(max)}$ ) | 200°C            |
|  | - Time (min to max) ( $t_s$ )      | 60 – 120 secs    |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak) | 3°C/second max                     |                  |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   | 3°C/second max                     |                  |
| Reflow   | - Temperature ( $T_L$ ) (Liquidus) | 217°C            |
|  | - Time (min to max) ( $t_s$ )      | 60 – 150 seconds |
| Peak Temperature ( $T_p$ )                             | 260 <sup>+0/-5</sup> °C            |                  |
| Time within 5°C of actual peak Temperature ( $t_p$ )   | 30 seconds max                     |                  |
| Ramp-down Rate   | 6°C/second max                     |                  |
| Time 25°C to peak Temperature ( $T_p$ )                | 8 minutes max.                     |                  |
| Do not exceed  | 260°C                              |                  |




### Physical Specifications

|                 |   |
|-----------------|---|
| <b>Weight</b>   | 0.007 ounce, 0.21 grams   |
| <b>Case</b>     | JEDEC DO214AB. Molded plastic body over glass passivated junction |
| <b>Polarity</b> | Color band denotes positive end (cathode) except Bidirectional.   |
| <b>Terminal</b> | Matte Tin-plated leads, Solderable per JESD22-B102                |

### Environmental Specifications


|                            |                          |
|----------------------------|--------------------------|
| <b>High Temp. Storage</b>  | JESD22-A103              |
| <b>HTRB</b>                | JESD22-A108              |
| <b>Temperature Cycling</b> | JESD22-A104              |
| <b>MSL</b>                 | JEDEC-J-STD-020, Level 1 |
| <b>H3TRB</b>               | JESD22-A101              |
| <b>RSH</b>                 | JESD22-A111              |

### Dimensions




| Dimensions | Inches |       | Millimeters |       |
|------------|--------|-------|-------------|-------|
|            | Min    | Max   | Min         | Max   |
| A          | 0.114  | 0.126 | 2.900       | 3.200 |
| B          | 0.260  | 0.280 | 6.600       | 7.110 |
| C          | 0.220  | 0.245 | 5.590       | 6.220 |
| D          | 0.079  | 0.103 | 2.060       | 2.620 |
| E          | 0.030  | 0.060 | 0.760       | 1.520 |
| F          | -      | 0.008 | -           | 0.203 |
| G          | 0.305  | 0.320 | 7.750       | 8.130 |
| H          | 0.006  | 0.012 | 0.152       | 0.305 |
| I          | 0.129  | -     | 3.300       | -     |
| J          | 0.094  | -     | 2.400       | -     |
| K          | -      | 0.165 | -           | 4.200 |
| L          | 0.094  | -     | 2.400       | -     |

**Part Numbering System**




**Part Marking System**



**Packaging Options**

| Part number   | Component Package | Quantity | Packaging Option                 | Packaging Specification |
|---------------|-------------------|----------|----------------------------------|-------------------------|
| TPSMDxxxXX    | DO-214AB          | 3000     | Tape & Reel - 16mm tape/13" reel | EIA STD RS-481          |
| TPSMDxxxXX-T7 | DO-214AB          | 500      | Tape & Reel - 16mm tape /7" reel | EIA STD RS-481          |

**Tape and Reel Specification**



**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View TPSMD22A on WIN SOURCE](#)

 [Littelfuse Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management