




# THE DATASHEET OF RS1JFA



# Surface Mount Fast Recovery Rectifiers

## 0.8 A, 50 V - 1000 V




### RS1AFA, NRVHPRS1AFA Series

#### Features

- Glass Passivated Chip Junction
- Fast Switching for High Efficiency
- High Surge Capacity
- Low Forward Voltage: 1.3 V Maximum
- UL Flammability 94V-0 Classification
- MSL 1 per J-STD-020
- RoHS Compliant / Green Molding Compound
- Industrial Device Qualified per AEC-Q101 Standards
- NRVHP Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable

\*See authorized use policy



**SOD-123FA**  
**CASE 425AB**

(Color Band Denotes Cathode)

#### ORDERING INFORMATION

| Part Number | Top Mark | Package   | Packing Method† |
|-------------|----------|-----------|-----------------|
| RS1AFA      | RAL      | SOD-123FA | Tape and Reel   |
| RS1BFA      | RBL      | SOD-123FA | Tape and Reel   |
| RS1DFA      | RDL      | SOD-123FA | Tape and Reel   |
| RS1GFA      | RGL      | SOD-123FA | Tape and Reel   |
| RS1JFA      | RJL      | SOD-123FA | Tape and Reel   |
| RS1KFA      | RKL      | SOD-123FA | Tape and Reel   |
| RS1MFA      | RML      | SOD-123FA | Tape and Reel   |
| NRVHPRS1AFA | RAL      | SOD-123FA | Tape and Reel   |
| NRVHPRS1BFA | RBL      | SOD-123FA | Tape and Reel   |
| NRVHPRS1DFA | RDL      | SOD-123FA | Tape and Reel   |
| NRVHPRS1GFA | RGL      | SOD-123FA | Tape and Reel   |
| NRVHPRS1JFA | RJL      | SOD-123FA | Tape and Reel   |
| NRVHPRS1KFA | RKL      | SOD-123FA | Tape and Reel   |
| NRVHPRS1MFA | RML      | SOD-123FA | Tape and Reel   |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

## RS1AFA, NRVHPRS1AFA Series

**Table 1. ABSOLUTE MAXIMUM RATINGS** Values are at  $T_A = 25^\circ\text{C}$  unless otherwise noted.

| Symbol      | Parameter   | Value       |         |         |         |         |         |         | Unit             |
|-------------|---|-------------|---------|---------|---------|---------|---------|---------|------------------|
|             |   | RS1 AFA     | RS1 BFA | RS1 DFA | RS1 GFA | RS1 JFA | RS1 KFA | RS1 MFA |                  |
| $V_{RRM}$   | Repetitive Peak Reverse Voltage   | 50          | 100     | 200     | 400     | 600     | 800     | 1000    | V                |
| $V_{RMS}$   | RMS Reverse Voltage   | 35          | 70      | 140     | 280     | 420     | 560     | 700     | V                |
| $V_R$       | DC Blocking Voltage   | 50          | 100     | 200     | 400     | 600     | 800     | 1000    | V                |
| $I_{F(AV)}$ | Average Forward Rectified Current   | 0.8         |         |         |         |         |         |         | A                |
| $I_{FSM}$   | Peak Forward Surge Current: 8.3 ms Single Half Sine-Wave Superimposed on Rated Load | 30          |         |         |         |         |         |         | A                |
| $T_J$       | Operating Junction Temperature Range  | -55 to +150 |         |         |         |         |         |         | $^\circ\text{C}$ |
| $T_{STG}$   | Storage Temperature Range   | -55 to +150 |         |         |         |         |         |         | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

**Table 2. THERMAL CHARACTERISTICS** (Note 1)

| Symbol          | Parameter   | Value | Unit                      |
|-----------------|---|-------|---------------------------|
| $\Psi_{JL}$     | Typical Thermal Characteristics, Junction-to-Lead | 32    | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Typical Thermal Resistance, Junction-to-Ambient   | 105   | $^\circ\text{C}/\text{W}$ |

1. Device mounted on 5 mm x 5 mm Cu pad PCB.

**Table 3. ELECTRICAL CHARACTERISTICS** Values are at  $T_A = 25^\circ\text{C}$  unless otherwise noted.

| Symbol   | Parameter                              | Conditions  | Min                    | Typ | Max | Unit          |
|----------|--|---|------------------------|-----|-----|---------------|
| $V_F$    | Instantaneous Forward Voltage (Note 2) | $I_F = 0.8 \text{ A}$   |                        |     | 1.3 | V             |
| $I_R$    | Reverse Current at Rated $V_R$         | $T_J = 25^\circ\text{C}$  |                        |     | 5   | $\mu\text{A}$ |
|          |  | $T_J = 125^\circ\text{C}$   |                        |     | 50  |               |
| $C_J$    | Junction Capacitance                   | $V_R = 4 \text{ V}, f = 1 \text{ MHz}$                                      |                        | 10  |     | pF            |
| $T_{rr}$ | Reverse Recovery Time                  | $I_F = 0.5 \text{ A},$<br>$I_R = 1 \text{ A},$<br>$I_{rr} = 0.25 \text{ A}$ | RS1AFA, RS1BFA, RS1DFA |     | 150 | ns            |
|          |  |   | RS1GFA, RS1JFA         |     | 250 |               |
|          |  |   | RS1KFA, RS1MFA         |     | 500 |               |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Pulse test with  $PW = 300 \mu\text{s}$ , 1% duty cycle

# RS1AFA, NRVHPRS1AFA Series

## TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. Forward Current Derating Curve




Figure 2. Typical Reverse Characteristics




Figure 3. Maximum Non-Repetitive Forward Surge Current




Figure 4. Typical Instantaneous Forward Characteristics




Figure 5. Typical Junction Capacitance






Figure 6. Reverse Recovery Time Characteristic and Test Circuit Diagram

**MECHANICAL CASE OUTLINE**  
**PACKAGE DIMENSIONS**




**SOD-123FA**  
**CASE 425AB**  
**ISSUE A**


DATE 11 AUG 2022



TOP VIEW



FRONT VIEW




BOTTOM VIEW

NOTES:

1. NO INDUSTRY STANDARD APPLIES TO THIS PACKAGE.
2. ALL DIMENSIONS ARE IN MILLIMETERS.
3. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND THE BAR PROTRUSIONS.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 1.23        | 1.33 | 1.43 |
| b   | 0.80        | 1.00 | 1.20 |
| c   | 0.16        | 0.23 | 0.30 |
| D   | 2.70        | 2.80 | 2.90 |
| D1  | 3.40        | 3.60 | 3.80 |
| E   | 1.70        | 1.80 | 1.90 |
| He  | 2.45        | ---  | 2.60 |
| L   | 0.35        | 0.60 | 0.85 |



**RECOMMENDED MOUNTING FOOTPRINT\***

\* For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERM/D.

|                         |                    |  |
|-------------------------|--------------------|--|
| <b>DOCUMENT NUMBER:</b> | <b>98AON13722G</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOD-123FA</b>   | <b>PAGE 1 OF 1</b>   |

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:



Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View RS1JFA](#) on WIN SOURCE
-  [ON Semiconductor](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management