



CONTACT ORIENTATION ON ROLL

NOTES : (UNLESS OTHERWISE SPECIFIED)


- 1. MATERIAL :**
 - 1.1. CONTACT BODY : COPPER ALLOY.
 - 1.2. OUTER SPRING : STAINLESS STEEL
- 2. SPECIFICATIONS :**
 - 2.1 CURRENT RATING : 13A MAX.
 - 2.2 TERMINATION TYPE : CRIMPING.
 - 2.3 WIRE RANGE : 20~22AWG.
 - 2.4 WIRE INSULATION DIA(MAX) : Ø3.2mm.
- 3. ROHS COMPLIANT.**
- 4. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.**
- 5. AVAILABLE TOOLS :**
 - 5.1 HAND CRIMPER : MFX-3954.
 - 5.2 CRIMP APPLICATOR : MFX-3957.
 - 5.3 EXTRACTION TOOL : QXRT16.



SECTION A-A



SECTION B-B





REV	ECO	RE
B1	-	

P/N	CONTACT PLATING(MATING AREA)
SS20M1T	TIN PLATING OVER NICKEL.
SS20M1F	GOLD FLASH PLATING OVER NICKEL.
SS20M1G10	10μ" GOLD PLATING OVER NICKEL.
SS20M1G15	15μ" GOLD PLATING OVER NICKEL.
SS20M1G30	30μ" GOLD PLATING OVER NICKEL.

QUANTITY	PART NUMBER	MATERIAL
UNLESS OTHERWISE SPECIFIED		SIGNATURES: DAA
1) All dimensions are in metric (mm).		DATE: ARROW
2) Tolerances are as follows:		UNIT: μm
2-PL DEC ±0.15		CHECKED: #1/64
3-PL DEC ±0.08		ANGLE: 45°
3) Note reference =		ENGINEER:
MATERIAL SPECIFICATIONS:		APPROVAL:
PROCESS SPECIFICATIONS:		CUSTOMER:
NEXT ASSY:		THIS DRAWING IS SUPPLIED FOR REFERENCE ONLY. IT IS NOT TO BE USED FOR SPECIFICATIONS AND PERFORMANCE. THE PROPERTY RIGHTS IN THIS DRAWING ARE RESERVED. REPRODUCTION OR TRANSMISSION OF THIS DRAWING WITHOUT THE WRITTEN PERMISSION OF THE DRAWING ISSUING DEPARTMENT IS STRICTLY PROHIBITED. MANUFACTURING VARIATIONS.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View SS20M1F on WIN SOURCE](#)
-  [Amphenol Sine Systems Corp Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management