



# THE DATASHEET OF SEK-SPS30



**SPS 30**

## **Particulate Matter Sensor**

For HVAC and air quality applications



**SENSIRION**

# SPS30 Particulate Matter Sensor

The MCERTS-certified SPS30 particulate matter (PM) sensor marks a technological breakthrough in optical PM sensors. Its measurement principle is based on laser scattering and makes use of Sensirion's innovative contamination-resistance technology. This technology, together with high-quality and long-lasting components, enables precise measurements from the device's first operation and throughout its lifetime of more than ten years.

## Applications

The SPS3x has been designed for use in various applications and devices, such as:

- Air purifiers
- HVAC equipment
- Demand-controlled ventilation systems
- Air conditioners
- Air quality and environmental monitors
- Smart home and IoT devices

## Technology and benefits

Technology	Benefits
Proprietary contamination-resistance technology and long-lasting components	Lifetime of more than eight years while operating continuously for 24 hours/day. No need for cleaning and/or maintenance, thus avoiding problems related to sensor drift or malfunction.
Laser-based scattering principle and advanced algorithms	Accurate measurements for different types of dust and other particles.
Accurate high-resolution particle size binning	Enables new use cases and device-specific actions based on detected particle composition.
Small, ultra-slim package	Easy to integrate into devices where size and space are limited.
Fully calibrated digital output. UART and I <sup>2</sup> C interfaces	Simple interfacing and read-out.

## Sensor Specifications



Particulate Matter Sensor Specifications	
Mass concentration accuracy <sup>1</sup>	± 10 µg/m <sup>3</sup> @ 0 to 100 µg/m <sup>3</sup> ± 10% @ 100 to 1,000 µg/m <sup>3</sup>
Mass concentration range	0 to 1,000 µg/m <sup>3</sup>
Mass concentration resolution	1 µg/m <sup>3</sup>
Particle detection size range <sup>2</sup>	Mass concentration: PM1.0, PM2.5, PM4 and PM10 Number concentration: PM0.5, PM1.0, PM2.5, PM4 and PM10
Lower limit of detection	0.3 µm
Minimum sampling interval	1 s (continuous mode)
Lifetime	> 8 years operating continuously 24h/day
Dimensions	40.6 x 40.6 x 12.2 mm <sup>3</sup>
Operating temperature range	-10 to +60 °C
Storage temperature range	-40 to +70 °C
Electrical Specifications	
Interface	UART, I <sup>2</sup> C
Supply voltage	4.5 – 5.5 V
Average supply current @ 1 Hz measurement rate	< 60 mA

<sup>1</sup> Specified for PM2.5 at 25 °C using potassium chloride salt particles and the TSI DustTrak™ DRX Aerosol Monitor 8533 as a reference.

<sup>2</sup> PM<sub>x</sub> defines particles with a size smaller than "x" micrometers (e.g., PM2.5 = particles smaller than 2.5 µm).

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View SEK-SPS30 on WIN SOURCE](#)
-  [Sensirion AG Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management