



**THE DATASHEET OF
C2012X5R1A106KT000E**



C.3216.X7R.1H.105.K.160.

| Series Name | |
|-------------|----------------------|
| Description | |
| C | General Purpose |
| CKC | Array |
| CKG | MEGACAP |
| CLL | Ultra Low Inductance |

| Case Size Code | | | |
|----------------|------|-----|-----|
| C | CKC | CKG | CLL |
| 0.40 x 0.20 | 0402 | | |
| 0.50 x 1.00 | 0510 | | |
| 0.60 x 0.30 | 0603 | | |
| 0.80 x 1.60 | 0816 | | |
| 0.90 x 0.60 | N27 | | |
| 1.00 x 0.50 | 1005 | | |
| 1.25 x 2.00 | 1220 | | |
| 1.37 x 1.00 | M25 | | |
| 1.60 x 0.80 | 1608 | C1A | |
| 1.60 x 3.20 | 1632 | | |
| 2.00 x 1.25 | 2012 | L22 | E1A |
| | | L44 | |
| 3.20 x 1.60 | 3216 | A43 | G1A |
| 3.20 x 2.50 | 3225 | | |
| 3.80 x 2.90 | | 32K | |
| 4.50 x 2.00 | 4520 | | |
| 4.50 x 3.20 | 4532 | | |
| | | 45K | |
| | | 45N | |
| 5.70 x 5.00 | 5750 | | |
| 6.50 x 5.50 | | 57K | |
| | | 57N | |
| 7.50 x 6.30 | 7563 | | |

| Temperature Characteristics | |
|-----------------------------|---|
| Temperature | Temperature Coefficient or Capacitance Change |
| CH | -25°C to +85°C 0±60ppm/°C |
| C0G | -55°C to +125°C 0±30ppm/°C |
| NP0 | -55°C to +150°C 0±30ppm/°C |
| JB | -25°C to +85°C ±10% |
| X5R | -55°C to +85°C ±15% |
| X6S | -55°C to +105°C ±22% |
| X7R | -55°C to +125°C ±15% |
| X7S | -55°C to +125°C ±22% |
| X7T | -55°C to +125°C +22, -33% |
| X8R | -55°C to +150°C ±15% |

| Capacitance Tolerance | |
|-----------------------|----------|
| Description | |
| B | ±0.10 pF |
| C | ±0.25 pF |
| D | ±0.50 pF |
| F | ±1% |
| G | ±2% |
| J | ±5% |
| K | ±10% |
| M | ±20% |

| Thickness Code | |
|----------------|---------|
| Description | |
| 020 | 0.20 mm |
| 030 | 0.30 mm |
| 045 | 0.45 mm |
| 050 | 0.50 mm |
| 055 | 0.55 mm |
| 060 | 0.60 mm |
| 070 | 0.70 mm |
| 080 | 0.80 mm |
| 085 | 0.85 mm |
| 100 | 1.00 mm |
| 110 | 1.10 mm |
| 115 | 1.15 mm |
| 125 | 1.25 mm |
| 130 | 1.30 mm |
| 160 | 1.60 mm |
| 200 | 2.00 mm |
| 230 | 2.30 mm |
| 250 | 2.50 mm |
| 280 | 2.80 mm |
| 290 | 2.90 mm |
| 320 | 3.20 mm |
| 335 | 3.35 mm |
| 500 | 5.00 mm |

| Rated Voltage Code | | | | | | |
|--------------------|------|------|------|----|------|------|
| A | C | D | E | F | G | H |
| 0 | | | | 4V | | |
| 1 | 10V | 16V | 25V | | 50V | |
| 2 | 100V | 200V | 250V | | 630V | 450V |
| 3 | 1KV | 2KV | 3KV | | | |

| Nominal Capacitance | |
|---------------------|--|
|---------------------|--|

The capacitance is expressed in three digit codes as follows:
 The first and second digits identify the first and second significant digits of the nominal capacitance.
 The third digit identifies the multiplier (power of ten) of the nominal capacitance.
 Ex. 0R2 = 0.2pF; 103 = 10,000pF; 105 = 1,000,000pF

CGA.5.L.3.X7R.1H.105.K.16

| Series Name | |
|-------------|------------------------|
| Description | |
| CGA | Automotive Grade |
| CGJ | High Reliability Grade |
| CEU | Serial Design |

| Case Size Code | | |
|----------------|-----|-----|
| CGA | CGJ | CEU |
| 0.60 x 0.30 | 1 | |
| 1.00 x 0.50 | 2 | 2 |
| 1.60 x 0.80 | 3 | 3 |
| 2.00 x 1.25 | 4 | 4 |
| 3.20 x 1.60 | 5 | 5 |
| 3.20 x 2.50 | 6 | |
| 4.50 x 2.00 | 7 | |
| 4.50 x 3.20 | 8 | |
| 5.70 x 5.00 | 9 | |

| Thickness Code | |
|----------------|---------|
| Description | |
| A | 0.30 mm |
| B | 0.50 mm |
| C | 0.60 mm |
| E | 0.80 mm |
| F | 0.85 mm |
| G | 1.10 mm |
| H | 1.15 mm |
| J | 1.25 mm |
| K | 1.30 mm |
| L | 1.60 mm |
| M | 2.00 mm |
| N | 2.30 mm |
| P | 2.50 mm |
| Q | 2.80 mm |
| R | 3.20 mm |

| Capacitance Tolerance | |
|-----------------------|-----------|
| Description | |
| C | ± 0.25 pF |
| D | ± 0.50 pF |
| F | ± 1% |
| J | ± 5% |
| K | ± 10% |
| M | ± 20% |

Nominal Capacitance

The capacitance is expressed in three digit code (pF). The first and second digits identify the first two digits of the capacitance. The third digit identifies the decimal point.
 Ex. 0R2 = 0.2pF; 103 = 10,000pF; 105 = 1,000,000pF

| Life Test Condition or Function Identification Code | |
|---|---------------------|
| Description | |
| 1 | 1.0 x Rated Voltage |
| 2 | 2.0 x Rated Voltage |
| 3 | 1.5 x Rated Voltage |
| 4 | 1.2 x Rated Voltage |
| A | ESD Protection |

| Temperature Characteristics | | |
|-----------------------------|---|------------|
| Temperature | Temperature Coefficient or Capacitance Change | |
| C0G | -55°C to +125°C | 0±30ppm/°C |
| NP0 | -55°C to +150°C | 0±30ppm/°C |
| X5R | -55°C to +85°C | ±15% |
| X6S | -55°C to +105°C | ±22% |
| X7R | -55°C to +125°C | ±15% |
| X7S | -55°C to +125°C | ±22% |
| X7T | -55°C to +125°C | +22, -33% |
| X8R | -55°C to +150°C | ±15% |

| Rated Voltage Code | | | | | | |
|--------------------|------|------|------|------|------|-----|
| A | C | D | E | F | H | J |
| 0 | | | | | | 6.3 |
| 1 | 10V | 16V | 25V | 50V | | |
| 2 | 100V | 200V | 250V | 500V | 630V | |
| 3 | 1KV | 2KV | 2KV | 3KV | | |

CGB.3.C.1.X5R.0J.106.M.06

| Series Name | |
|-------------|-------------|
| Description | Low Profile |
| CGB | |

| Case Size Code | |
|----------------|-------------|
| CGB | Description |
| 1 | 0.60 x 0.30 |
| 2 | 1.00 x 0.50 |
| 3 | 1.60 x 0.80 |
| 4 | 2.00 x 1.25 |

| Thickness Code | |
|----------------|--------------|
| Description | Thickness |
| T | 0.22 mm max. |
| A | 0.33 mm max. |
| S | 0.50 mm max. |
| B | 0.55 mm max. |
| C | 0.65 mm max. |

| Capacitance Tolerance | |
|-----------------------|-----------|
| Description | Tolerance |
| K | ±10% |
| M | ±20% |

Nominal Capacitance

The capacitance is expressed in three digit codes (pF). The first and second digits identify the first of the capacitance. The third digit identifies the decimal point.
 Ex. 0R2 = 0.2pF; 103 = 10,000pF; 105 = 1,000,000pF

| Life Test Condition | |
|---------------------|---------------------|
| Description | Condition |
| 1 | 1.0 x Rated Voltage |
| 3 | 1.5 x Rated Voltage |

| Temperature Characteristics | |
|-----------------------------|----------------------|
| Temperature | Tolerance |
| JB | -25°C to +85°C ±10% |
| X5R | -55°C to +85°C ±15% |
| X6S | -55°C to +105°C ±22% |
| X7R | -55°C to +125°C ±15% |
| X7S | -55°C to +125°C ±22% |

| Rated Voltage Code | |
|--------------------|---------|
| Code | Voltage |
| 0 | 4V |
| 1 | 6.3V |
| A | 10V |
| C | 16V |
| E | 25V |

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View C2012X5R1A106KT000E on WIN SOURCE](#)
- ⊖ [TDK Corporation Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management