



**THE DATASHEET OF  
CT-3001/CCP**





CT-3001/CCP • CT-3001/CCPINT • CT-3001/CCPUK  
 • CT-3001/CCPAUS • CT-3001/CCPTO  
 MULTI-USE (CRIMP • CUT • PUNCH) TOOL

This tool meets requirements of Safety for Hand Held, Motor-Operated Electric Tools specification UL 60745-1 and CSA C22.2 No 60745-1. Tool is listed under CSA file number 268531.

**NOTES, UNLESS OTHERWISE SPECIFIED:**

The CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK, CT-3001/CCPAUS and CT-3001/CCPTO Battery Operated Multi-Use Tools are designed to crimp and cut:

- Crimps Panduit Copper and Aluminum compression connectors using Panduit Crimping Dies. Go to [www.panduit.com](http://www.panduit.com) for more information.
- Cuts Aluminum and Copper code conductor cable up to 1" [25mm].
- Cuts Aluminum and Mild Steel Threaded Rod; M5 to M12, and 1/4 to 1/2 UNC Thread.
- Punch Capacity of 2" (50 mm) conduit size in 10 Gauge (3.41 mm) mild steel with standard Greenlee punches and Panduit Punch Drive Adapter.

**The CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK and CT-3001/CCPAUS Tools include:**

Qty.	Description / Item								
1	Battery Operated Hydraulic Multi-Use (Crimp, Cut) Tool								
2	Rechargeable Battery (Makita Lithium-Ion 18VDC, 3Ah)								
1	<table border="0" style="width: 100%; text-align: center;"> <tr> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Plug Type A (North America)</td> <td>Plug Type C (International)</td> <td>Plug Type G (UK)</td> <td>Plug Type I (Australia)</td> </tr> </table> Makita Battery Charger – Regional (reference images above for regional plug type)					Plug Type A (North America)	Plug Type C (International)	Plug Type G (UK)	Plug Type I (Australia)
Plug Type A (North America)	Plug Type C (International)	Plug Type G (UK)	Plug Type I (Australia)						
1	Tool Case								
1	Set of "UAW" Die Adapters								

**The CT-3001/CCPTO Tool includes:**

Qty.	Description / Item
1	Battery Operated Hydraulic Multi-use (Crimp, Cut, Punch) Tool
1	Set of "UAW" Die Adapters

**Technical Information:**

Tool Weight (including battery)	7.1 lbs. (3.2 kg)
Dimensions (including battery)	17.5" L x 4.6" H x 3.0" W [444 L x 116 H x 75 W] mm
Crimping Force	6.7 tons (60 kN)

Tools are to be used with Panduit crimp dies, cable cutters, threaded rod cutters, and punch drive adapters are sold separately. Go to [www.panduit.com](http://www.panduit.com) for more information.

"UAM" adapter for cable cutting applications is sold separately.

A copy of operation manual and accessory information can be found at: [www.panduit.com](http://www.panduit.com).

Dimensions in [brackets] are in millimeters. All dimensions are for reference only.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	<b>CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK, CT-3001/CCPAUS and CT-3001/CCPTO</b>				CUSTOMER DRAWING	
00	7-25-16	BKA	ACC	JADE	DRAWING RELEASED	010819	ITEM REVISION NAME: 00084SLG_DC/00				<b>PANDUIT</b>	
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± --- (.xxx) ± --- (.xx) ± --- ANGLES ± ---				MATERIAL: -----	
							THIRD ANGLE PROJECTION				DRAWING NUMBER: 00084SLG_DC	
							DRAWN BY: BKA	DATE: 7-21-16	CHK ACC	SCALE NONE	SHT 1 OF 1	SIZE <b>B</b>

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View CT-3001/CCP on WIN SOURCE](#)

 [Panduit Corp Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management