




**THE DATASHEET OF  
HSEC8-160-01-S-DV-A**



# GENERATE<sup>®</sup>

## HIGH-SPEED EDGE CARD SYSTEMS


0.60 mm, 0.80 mm and 1.00 mm PITCH




### FEATURES & BENEFITS

- Maximum Design Flexibility
- Up to 64 Gbps PAM4 performance
- PCI Express<sup>®</sup> 3.0, 4.0, 5.0 and 6.0
- Edge Rate<sup>®</sup> contacts optimized for signal integrity performance and high-cycle life
- Up to 200 positions available
- Vertical, right-angle, edge mount, pass-through orientations
- Power/signal combo, press-fit tails, rugged weld tabs, locks and latches
- Mating cable assemblies available


**EDGE  
RATE<sup>®</sup>**  
CONTACT



Rugged tucked beam technology (HTEC8)



Differential pair for increased speed (HSEC8-DP)



Custom designs allow for misalignment in the X-Y axes (HSEC1)

### KEY SPECIFICATIONS

SERIES	PITCH	TOTAL POSITIONS	INSULATOR MATERIAL	CONTACT MATERIAL	OPERATING TEMP RANGE	CURRENT RATING	VOLTAGE RATING	LEAD-FREE SOLDERABLE
HSEC6	0.60 mm	56-168	Black LCP	Copper Alloy	-55 °C to +125 °C	1.9 A (2 pins)	240 VAC	Yes
HTEC8	0.80 mm	20-200	Black LCP	Copper Alloy	-55 °C to +125 °C	3.0 A (2 pins)	215 VAC	Yes
HSEC8	0.80 mm	18-200	Black LCP	BeCu	-55 °C to +125 °C	2.8 A (2 pins)	240 VAC	Yes
HSEC1	1.00 mm	20-140	Black LCP	Phosphor Bronze	-55 °C to +125 °C	2.2 A (2 pins)	215 VAC	Yes



## (0.80 mm) .0315" PITCH • VERTICAL EDGE CARD SOCKET

HSEC8	1	POSITIONS PER ROW	CARD THICKNESS	PLATING OPTION	DV	A	OTHER OPTIONS	"X"R
		<b>09, 10, 13, 20, 25, 30, 37, 40, 49, 50, 60, 70, 80, 100</b> (13, 25, 49 only available with -L or -L2 latching option; 09 only available with -L2 option; 37 only available with -L latching option)	<b>-01</b> = (1.60 mm) .062" thick card  <b>-03</b> = (2.36 mm) .093" thick card	<b>-L</b> = 10 μ" (0.25 μm) Gold on contact area, Matte Tin on tail  <b>-S</b> = 30 μ" (0.76 μm) Gold on contact area, Matte Tin on tail			<b>-K</b> = Polyimide Pick & Place Pad  <b>-BL</b> = Board Locks; -01 card only (Weld tab standard)  <b>-L</b> = Latching Option; -01 card only (13, 25, 37, 49 only) (Weld tab standard)  <b>-L2</b> = ECDP Latching; -01 card only (09, 13, 25, 49 only) (For use with ECDP) (Weld tab standard)  <b>-WT</b> = Weld tab	Leave blank for Tray Packaging  <b>-TR</b> = Tape & Reel (09 - 70 only)  <b>-FR</b> = Full Reel Tape & Reel (must order max. quantities per reel; contact Samtec for quantity breaks) (09-70 only)


### HSEC8-DV

**Card Mates:**  
 (1.60 mm) .062" card,  
 (2.36 mm) .093" card,  
 HSC8

**Cable Mates:**  
 ECDP



10, 20, & 30 POSITIONS



09, 13, 25, 37 & 40 THRU 100 POSITIONS

### OTHER SOLUTIONS

For complete edge card system with cards and sockets, visit [samtec.com?RU8](http://samtec.com?RU8)

For a card to mate with an HSEC8 socket, visit [samtec.com?HSC8](http://samtec.com?HSC8)



POSITIONS PER ROW	A	B
09*†	(4.50) .177	(11.80) .465
13*†	(6.10) .240	(15.00) .591
25*†	(6.10) .240	(24.60) .969
37†	(18.10) .713	(34.20) 1.346
40	(18.90) .744	(36.60) 1.441
49*†	(22.90) .902	(43.80) 1.724
50	(22.90) .902	(44.60) 1.756
60	(26.90) 1.059	(52.60) 2.071
70†	(26.90) 1.059	(60.60) 2.386
80†	(26.90) 1.059	(68.60) 2.701
100†	(26.90) 1.059	(84.60) 3.331

CABLE	CONNECTOR
ECDP-04	HSEC8-109-L2
ECDP-08	HSEC8-113-L2
ECDP-16	HSEC8-125-L2
ECDP-32	HSEC8-149-L2

Positions where no dimensions are given do not have keying feature.

\* Mates with ECDP Series



† Available with -01 Card Only

**Note:**  
 Some sizes, styles and options are non-standard, non-returnable.

View complete specifications at: [samtec.com?HSEC8-DV](http://samtec.com?HSEC8-DV)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View HSEC8-160-01-S-DV-A on WIN SOURCE](#)
-  [Samtec Inc. Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management